



Florida Department of Transportation

CHARLIE CRIST
GOVERNOR

605 Suwannee Street
Tallahassee, FL 32399-0450

STEPHANIE KOPELOUSOS
SECRETARY

December 12, 2007

Dr. Leslie McCarthy, PhD, P.E.
Program Operations Engineer
Federal Highway Administration
545 John Knox Road, Suite 200
Tallahassee, Florida 32303

Re: Office of Design, Specifications
Section 353
Proposed Specification: 3531100.D01 – Concrete Pavement Slab Replacement-Method
of Measurement

Dear Dr. McCarthy:

We are submitting, for your approval, two copies of a proposed Supplemental Specification for Concrete Pavement Slab Replacement-Method of Measurement.

This change was proposed by Bruce Dietrich of the State Pavement Design Office to update the Method of Measurement criteria.

Please review and transmit your comments, if any, within two weeks. Comments should be sent via Email to SP965DB or duane.brautigam@dot.state.fl.us.

If you have any questions relating to this specification change, please call Duane F. Brautigam, State Specifications Engineer at 414-4110.

Sincerely,

Signature on file

Duane F. Brautigam, P.E.
State Specifications Engineer

DFB/sh

Attachment

cc: Gregory Jones, General Counsel
Florida Transportation Builders' Assoc.
State Construction Engineer

CONCRETE PAVEMENT SLAB REPLACEMENT-METHOD OF MEASUREMENT.**(REV ~~10-23-07~~12-11-07)**

ARTICLE 353-11 (Page 353) is deleted and the following substituted:

353-11 Method of Measurement.

The quantity to be paid for will be the volume, in cubic yards, of concrete placed and accepted. The quantity will be calculated on the basis of field-measured *horizontal* dimensions *and nominal-pavement design thickness*. ~~The depth used in this calculation will be determined by averaging an appropriate number of measurements from the plane of the existing pavement surface to the surface of the subgrade, as it exists immediately prior to placing the concrete~~ *No additional compensation will be allowed for additional concrete required to bring the proposed concrete slab up to ~~proposed~~ finished grade.*

CONCRETE PAVEMENT SLAB REPLACEMENT-METHOD OF MEASUREMENT.

(REV 12-11-07)

ARTICLE 353-11 (Page 353) is deleted and the following substituted:

353-11 Method of Measurement.

The quantity to be paid for will be the volume, in cubic yards, of concrete placed and accepted. The quantity will be calculated on the basis of field-measured horizontal dimensions and pavement design thickness. No additional compensation will be allowed for additional concrete required to bring the proposed concrete slab up to finished grade.