

9160101 BITUMINOUS MATERIALS  
COMMENTS FROM INDUSTRY REVIEW

\*\*\*\*\*

Marshall Douberley  
863-519-2382  
[marshall.douberley@dot.state.fl.us](mailto:marshall.douberley@dot.state.fl.us)

Comment: (12-14-09)

How does this change effect products currently listed on the QPL. Will recertification or retesting of products currently list be required, if so how does designation be made on the QPL to identify those products that are allowed on projects let prior to implementation of this specification?

Response:

\*\*\*\*\*

Scott Watson  
Blacklidge Emulsions, Inc.  
800-866-3878  
[swatson@be-inc.com](mailto:swatson@be-inc.com)

Comments: (1-7-10)

As a supplier of EPR-1 the proposed changes in Section 916 are largely acceptable, but the form of the product outlined in Section 916-4.1 is currently diluted to perform properly in the field. Since this is also the case for the other emulsified asphalts used for prime, we recommend that this be addressed in Section 300 Prime and Tack Coats for Asphalt Bases. We suggest that Section 300-2.1 Prime Coat be amended as follows to include the proper EPR-1 Prime dilution:

*300-2.1 Prime Coat: For prime coat, use Cut-back Asphalt Grade RC-70 or RC-250 meeting the requirements of 916-3; Emulsified Asphalt Grades SS-1 or CSS-1, SS-1H, or CSS-1H diluted in equal proportion with water; Emulsified Asphalt Grade AE-60, AE-90, AE-150, or AE-200 diluted at the ratio of six parts emulsified asphalt to four parts water; Special MS-Emulsion diluted at the ratio of six parts emulsified asphalt to four parts water; **EPR-1 Prime diluted at the ratio of one part emulsified asphalt to two parts water**; Asphalt Emulsion Prime (AEP); or Emulsion Prime (RS Type), ~~or EPR-1 Prime~~ meeting the requirements of 916-4, or other types and grades of bituminous material which may be specified in the Contract Documents.*

However, we believe that this dilution should be performed at the manufacturer's location to ensure the accurate addition of water, and this could be addressed by changing the footnote in the EPR-1 Prime specification in Section 916-4.1 as follows:

*(e) When used for prime applications, EPR-1 Prime shall be diluted by the manufacturer in accordance with Section 300-2.1. No further dilution of the product will be allowed. In the event that EPR-1 Prime is not used in a 12 hour period, the material shall be thoroughly mixed by circulation or other suitable means prior to use.*

Response:

\*\*\*\*\*