

990 TEMPORARY TRAFFIC CONTROL DEVICES AND MATERIALS.
(REV 11-22-10) (FA 12-10-10) (7-11)

SECTION 990 (Pages 956 - 966) is deleted and the following substituted:

SECTION 990
TEMPORARY TRAFFIC CONTROL DEVICES MATERIALS

990-1 General.

This Section specifies the material requirements for Temporary Traffic Control Devices.

990-2 Retroreflective Sheeting for Temporary Traffic Control Devices.

990-2.1 Qualified Products List: Sheeting for use on Temporary Traffic Control Devices shall be one of the products listed on the Qualified Products List (QPL). Manufacturers seeking evaluation of their product shall submit an application in accordance with Section 6.

990-2.1.1 Sign Panels, Bands for Tubular Markers, Vertical Panels, Barricades and other Devices: Sign Panels, Bands for Tubular Markers, Vertical Panels, Barricades and other Devices shall meet the requirements of ASTM D 4956 for Type III or higher retroreflective sheeting materials identified in Section 994 except for mesh signs shall meet the color, daytime luminance and nonreflective property requirements of Section 994, Type VI.

990-2.1.2 Collars for Traffic Cones: Collars for Traffic Cones shall meet the requirements of ASTM D 4956 Type VI.

990-2.1.3 Drums: Drums shall meet the requirements of ASTM D 4956 for Type III or higher retroreflective sheeting materials identified in Section 994 including Supplementary requirements for Reboundable Sheeting.

990-3.1 General: All portable devices shall meet the physical display and operational requirements of the MUTCD and be listed on the Approved Products List (APL). Manufacturers seeking approval of their portable devices shall provide a working sample to be evaluated by the Department that meets all requirements specified herein.

990-3.1.1 Electrical Systems:

990-3.1.1.1 Diesel Engine: The Diesel Engine shall meet the following:

(a) The power supply and electrical system shall be self-contained within the unit.

(b) The engine shall have an electrical starting system.

(c) The power source furnished shall be of sufficient size to provide the required maximum load energy plus 25%.

(d) The electrical system shall meet the National Electrical Code where applicable.

(e) A backup power system that will operate the unit for a minimum of three hours automatically when the motor driven generator fails to operate.

(f) The starting batteries and back-up power supply system batteries shall be automatically charged when the generator is operating.

(g) The engine shall be supplied with an ammeter and the generator shall be supplied with a voltmeter showing voltage to the sign assembly.

990-3.1.1.2. Solar Powered Unit: The Solar Powered Unit shall meet the following:

(a) The unit shall provide automatic recharging of power supply batteries to normal operating levels with meters showing charge.

(b) Solar array recovery time for Arrow Boards and Regulatory Signs shall be accomplished in a maximum of three hours.

(c) Arrow Boards and Changeable Variable Message Signs shall be designed to provide 180 days of continuous operation with minimum onsite maintenance.

990-3.1.1.3 Battery Life Test: Meet the following:

(a) The photovoltaic unit shall be designed to provide 21 days of continuous operation without sunlight with a minimum of onsite maintenance for arrow boards and changeable message signs, or 10 days of continuous operation without sunlight with a minimum of onsite maintenance for regulatory signs and radar speed display units.

(b) The battery shall be equipped with a battery controller to prevent overcharging and over-discharging. An external battery level indicator shall be provided.

(c) The battery, controller, and power panel shall be designed to be protected from the elements and vandalism.

(d) Automatic recharging of power supply batteries shall be provided with charge indicator meter.

(e) An AC/DC battery charger unit shall be provided.

990-3.1.2 Display Panel and Housing:

(a) The display housing assembly shall be weather-tight.

(b) All nuts, bolts, washers and other fasteners shall be of corrosion resistant material.

(c) The display assembly shall be equipped with an automatic dimming operational mode capable of a minimum of 50% dimming and a separate manual dimmer switch

(d) The display panel background and frame for the display assembly shall be painted flat black and shall meet Federal Specification TT-E-489.

(e) The display panel for arrow boards and changeable message signs, when raised in the upright position, shall have a minimum height of 7 feet from the bottom of the panel to the ground, in accordance with the MUTCD. The display panel for radar speed display units, when raised in the upright position, will have a minimum height of 5 feet from the bottom of the panel to the ground.

(f) The regulatory speed sign panel for regulatory signs and radar speed display units, when raised in the upright position, shall have a minimum height of 7 feet from the bottom of the regulatory sign panel to the ground.

(g) The unit shall have an accessible mechanism to easily raise and lower the display assembly. A locking device shall also be provided to ensure the display panel will remain in the raised or lowered position.

990-3.1.3 Controller: The Controller shall meet the following:

(a) Controller and control panel shall be housed in a weather, dust, and vandal resistant lockable cabinet.

(b) Controller and associated on-board circuitry shall meet the requirements of the Federal Communications Commission (FCC) Title 47, Subpart B, Section 15 regulations concerning the emission of electronic noise by Class A digital devices.

(c) For Changeable Variable Message Signs and Arrow Boards ensure that the sign control software provides an on-site graphical representation that visibly depicts the message displayed on the sign face.

(d) For Changeable Variable Message Signs, if remote communication is included, meet the following National Transportation Communications for ITS Protocol (NTCIP) requirements: Ensure that the sign controller software implements all mandatory objects as defined in the FDOT Standard Global MIB v01 in Appendix A, all mandatory objects as defined in the FDOT Standard DMS MIB v01 in Appendix B, and all mandatory objects as defined in the FDOT Specific DMS MIB v01 in Appendix C. Ensure that additional objects implemented by the software do not interfere with the standard operation of mandatory objects.

990-3.1.4 Support Chassis: The Support Chassis shall meet the following:

(a) The support chassis shall be self-contained and self-supporting without the use of additional equipment or tools.

(b) Both trailer and truck-mounted units are allowed for arrow panels. Trailer mounted units are required for changeable message signs, regulatory signs and radar speed display units.

(1) Trailer mounted unit:

(a) The sign, power supply unit and all support systems shall be mounted on a wheeled trailer.

(b) The trailer shall be equipped with Class-A lights, using a plug adaptor.

(c) The trailer shall be equipped with adjustable outrigger leveling pads, one on each of the four frame corners.

(d) The trailer shall be designed to be set up at the site with its own chassis and outriggers, without being hitched to a vehicle.

(e) The trailer shall be equipped with fenders over the tires and shall be made from heavy-duty material sufficient to allow a person to stand and operate or perform maintenance on the unit.

(f) The trailer shall meet all equipment specifications set forth in Chapter 316 of the Florida Statutes, and by such rule, regulation or code that may be adopted by the Department of Highway Safety and Motor Vehicles.

(g) The trailers should be delineated on a permanent basis by affixing retroreflective material, known as conspicuity material, in a continuous line on the face of the trailer as seen by oncoming road users.

(2) Truck mounted unit:

(a) The truck-mounted assembly shall be designed to fit on a 1/2 ton or greater duty truck.

(b) The unit shall be self-contained with its own power supply, controls, raising and lowering device and shall be capable of being operated by one person.

(c) The unit shall be secured in the vehicle for normal operation.

990-3.1.5 Other Requirements: Meet the following:

(a) The portable device assembly shall be designed to function in dry, wet, hot or cold weather (ambient temperature ranges from -30 to 165°F. Other environmental requirements shall be as specified in Section A-615 of the Minimum Specifications for Traffic

Control Signal Devices, which can be located at the following URL:
http://www.dot.state.fl.us/trafficoperations/Traf_Sys/terl/apl4.shtm .

(b) The controller shall not be affected by mobile radio, or any other radio transmissions.

(c) An operator's manual shall be furnished with each unit.

(d) The manufacturer's name and FDOT approval number shall be affixed on the equipment.

990-3.2 Portable Arrow Board:

990-3.2.1 Arrow Board Matrix:

(a) The minimum legibility distance for various traffic conditions are based on the decision-sight distance concept. The minimum legibility distance is the distance at which a driver can comprehend the arrow panel message on a sunny day or a clear night. The arrow panel size that is needed to meet the legibility distance is listed as follows:

Type	Minimum Size	Minimum Number of Panel Lamps	Minimum Legibility Distance
B	30 by 60 inches	13	3/4 mile
C	48 by 96 inches	15	1 mile

For use on the state highway system, the Types "B" or "C" advance warning arrow boards may be used for low to intermediate (0 to 50 mph) facilities and for maintenance or moving operations on high-speed roadways. Type "C" arrow boards shall be used on high-speed (50 mph and up).

(b) Devices shall meet all arrow board displays identified in the MUTCD.

(c) The lamp lens should be 5 3/4 inches in diameter. Smaller lamp lens diameters are permissible only if they provide an equivalent or greater brightness indication and meet the legibility criteria in Section (a) of this Specification.

(d) The color of the light emitted shall be in accordance with the MUTCD.

(e) There shall be a 360-degree hood for close-up glare reduction.

(f) For solar powered arrow boards the bulbs shall provide a 350-candle power intensity for day use and an automatic reduction or dimming capacity for night use. The dimmed night operation shall provide adequate indication without excessive glare.

(g) The flashing rate of the lamps shall not be less than 25 nor more than 40 flashes per minute as required in the MUTCD.

(h) The minimum lamp "on time" shall be 50% for the flashing arrow and 25% for the sequential chevron.

990-3.3 Changeable Variable Message Sign:

990-3.3.1 Message Matrix:

(a) Message matrix panel shall be a maximum height of 7 feet by a maximum width of 10 feet.

(b) The message matrix panel shall contain three separate lines. Each line shall consist of eight characters, equally spaced a minimum of 3 inches. Each character shall contain 35 pixels in a five by seven horizontal to vertical grid arrangement.

(c) Each message line of the 7 foot by 10 foot PCMS shall provide for characters 13 inches in width by 18 inches in height minimum and variable graphic and symbol sizes to a minimum of 18 inches in height.

(d) For flip disk matrix signs, the disk elements shall be coated on the display side with a highly reflective florescent yellow Mylar material, and on the back with a flat black to blend in with the flat black background.

(e) Similar components shall be interchangeable.

990-3.3.2 Operation and Performance:

(a) The message shall be displayed in upper case except when lower case is project specific and is allowed by the MUTCD.

(b) The message matrix panel shall be visible from 1/2 mile and legible from a distance of 650 feet under both day and night conditions. Under variable light level conditions the sign shall automatically adjust its light source to meet the 650 feet visibility requirement. The message panel shall have adjustable display rates, so that the entire message can be read at least twice at the posted speed.

(c) The control panel shall have the capability to store a minimum 50 pre-programmed messages.

(d) The controller in the control panel shall be able to remember messages during non-powered conditions.

(e) The controller shall allow the operator to generate additional messages on site via the keyboard.

(f) For a PCMS using Flip-Disk technology, the controller shall have the capability to provide a stipulated default message upon loss of controller function.

(g) All messages shall be flashed or sequenced. In the sequence mode, the controller shall have the capability to sequence three line messages during one cycle.

990-3.4 Portable Regulatory Signs:

990-3.4.1 Sign Panel Assembly: The sign panel assembly shall consist of a 24 by 30 inches "SPEED LIMIT XX" sign panel and a "WHEN FLASHING" sign panel, intended to notify oncoming traffic the speed limit where workers are present. The sign panel assembly shall meet the following minimum physical requirements:

(a) all nuts, bolts, washers, and other fasteners shall be of corrosion resistant material.

(b) the sign panel shall fold down and be pinned in place for towing. Maximum travel height shall be 80 inches.

(c) construct the sign panel and light housing to allow the unit to be operated in the displayed position at speeds of 30 mph. Design the sign panel assembly to withstand transport speeds of 65 mph.

(d) construct the sign panel such that, when in the raised position, the sign panel will have a height of seven feet from the bottom of the lowest panel to the ground, in accordance with the MUTCD.

(e) provide the unit with a mechanism to raise and lower the sign panel. Provide the unit with a device to lock the sign panel in the raised and lowered position.

990-3.4.2 Flashing Lights: Provide a pair of hooded PAR 46 LED advance warning flashing lamps on each side of the top of the sign panel. These lamps shall be visible day or night at a distance of one mile with a flash rate of approximately 55 flashes per minute.

The lamp lens should be at least 5 3/4 inches in diameter. Smaller diameter lens are permissible if they provide an equivalent or greater brightness indication and meet the legibility criteria above.

The color of the light emitted shall be in accordance with the MUTCD. For solar powered units, the bulbs shall provide a 350 candlepower intensity for day use and an automatic reduction or dimming capacity for night use. The dimmed night operation shall provide adequate indication without excessive glare.

990-3.5 Radar Speed Display Unit:

990-3.5.1 Display Unit Panel and Housing: Meet the requirements of 990-3.1.2 and the following physical requirements as a minimum:

- (a) Provide capability to mount a 24 by 30 inches regulatory sign with interchangeable numbers showing the posted speed limit above the message display.
- (b) Provide legend "YOUR SPEED" either above or below the message display.

990-3.5.2 Message Display: The message Display shall meet the following physical requirements as a minimum:

- (a) Provide a bright LED, two digit speed display on a flat black background with bright yellow LEDs.
- (b) Each digit shall contain either a seven-segment layout or matrix-style design. Each digit shall measure a minimum 18 inches in height.
- (c) Speed display shall be visible from a distance of at least 1/2 mile and legible from a distance of at least 650 feet under both day and night conditions.
- (d) Display shall adjust for day and night operation automatically with a photocell.

990-3.5.3 Radar: The radar unit shall not be affected by normal radio transmissions and meet the following physical requirements as a minimum:

- (1) Approach-Only sensor.
- (2) Equipped with a low power K-Band transmitter.
- (3) Part 90 FCC acceptance, 3 amps, 10.8 to 16.6 vdc. Fuse and reverse polarity protected.
- (4) Range of 1,000 feet for mid-size vehicle, capable of accurately sensing speeds of 10 to 99 mph with over speed function that operates when a vehicle approaches over the posted speed limit.

990-3.5.4 Traffic Counter: The unit shall be fitted with a device, which counts the number of vehicles passing the Radar Speed Display Unit. The counter device shall be capable of:

- (1) Digital readout of the number of vehicles passing the radar speed display unit.
- (2) Digital readout of the number of vehicles exceeding the speed shown on the radar speed display unit.

990-4 Removable Tape.

990-4.1 Composition: Removable Tape shall be one of the products listed on the QPL. The pavement stripes and markings shall consist of high quality plastic materials, pigments, and glass spheres or other retroreflective materials uniformly distributed throughout their cross-sectional area, with a reflective layer of spheres or other retroreflective material embedded in the top surface. No foil type materials shall be allowed.

990-4.2 Skid Resistance: The surface of the stripes and markings shall provide a minimum skid resistance value of 35 BPN (British Pendulum Number) when tested according to ASTM E-303. Bike lane symbols and pedestrian crosswalks shall provide a minimum skid resistance value of 55 BPN.

990-4.3 Thickness: The Qualified Products List will list the specified thickness of each approved product.

990-4.4 Durability and Wear Resistance: When properly applied, the material shall provide neat, durable stripes and markings. The materials shall provide a cushioned resilient substrate that reduces sphere crushing and loss. The film shall be weather resistant and, through normal wear, shall show no significant tearing, rollback or other signs of poor adhesion. Durability is the measured percent of pavement marking material completely removed from the pavement. The pavement marking material line loss must not exceed 5.0% of surface area.

990-4.5 Conformability and Resealing: The stripes and markings shall be capable of conforming to pavement contours, breaks and faults under traffic at pavement temperatures recommended by the manufacturer. The film shall be capable of use for patching worn areas of the same types of film in accordance with the manufacturer's recommendations.

990-4.6 Tensile Strength: The stripes and markings shall have a minimum tensile strength of 40 psi when tested according to ASTM D 638. A rectangular test specimen 6 by 1 by 0.05 inch minimum thickness shall be tested at a temperature range of 40 to 80°F using a jaw speed of 0.25 inch/minute.

990-4.7 Elongation: The stripes and markings shall have a minimum elongation of 25% when tested in accordance with ASTM D-638.

990-4.8 Plastic Pull test: The stripes and markings shall support a dead weight of 4 lb for not less than five minutes at a temperature range of 70 to 80°F. Rectangular test specimen size shall be 6 by 1 by 0.05 inch minimum thickness.

990-4.9 Adhesive: Precoat removable tape with a pressure sensitive adhesive capable of being affixed to asphalt concrete and portland cement concrete pavement surfaces without the use of heat, solvents, and other additional adhesives or activators. Ensure that the adhesive does not require a protective liner when the removable tape is in rolled form for shipment. Ensure that the adhesive is capable of temporarily bonding to the roadway pavement at temperatures of 50°F and the above without pick-up distortion by vehicular traffic.

990-4.10 Color: Meet the requirements of 971-1.6.

990-4.11 Removability: Ensure that the manufacturer shows documented reports that the removable tape is capable of being removed intact or in substantially large strips after being in place for a minimum of 90 days and under an average daily traffic count per lane of at least 5,000 vehicles per day.

990-5 Temporary Retroreflective Pavement Markers.

Temporary Retroreflective Pavement Markers (RPM's) shall meet the requirement of 970-1.2.1, be one of the products listed on the QPL and be certified as meeting the following:

(a) Composition: Use markers made of plastic, ceramic or other durable materials. Markers with studs or mechanical attachments will not be allowed.

(b) Dimensions: Marker minimum and maximum surface dimensions is based on an x and y axis where the y dimension is the axis parallel to the centerline and the x axis is 90 degrees to y. Class E markers shall be 4 inch (W) by 2 inch (H) by 1 inch (D).

The x and y dimension of Class D markers shall be a maximum of 5 inches. The x dimension shall be a minimum of 4 inches and the minimum y dimension will be 2.25 inches.

The maximum installed height of Class D markers shall be 1 inch. The maximum installed height of Class E markers shall be 2 inches. Use Class D markers having a minimum reflective face surface of 0.35 square inches. Use Class E markers having a minimum reflective surface area of 1 square inch.

The marker's reflective face shall be completely visible and above the pavement surface after installation, measured from a line even with the pavement perpendicular to the face of the marker.

(c) Optical Performance: Ensure that the specific intensity of each white reflecting surface at 0.2 degrees observation angle shall be at least the following when the incident light is parallel to the base of the marker:

Horizontal Entrance Angle	Specific Intensity
0 deg.	3
20 deg.	1.2

For yellow reflectors, the specific intensity shall be 60% of the value for white.

For red reflectors, the specific intensity shall be 25% of the value for white. Reflectivity of all RPM's shall not be less than 0.2 Specific Intensity (SI) any time after installation.

(d) Strength requirements: Markers shall support a load of 5,000 pounds. Three markers per lot or shipment will be randomly tested as follows:

Position the marker base down, between the flat, parallel 0.5 inch steel plates of a compression testing machine. Place on top of the marker, a flat piece of 60 (Shore A) durometer rubber, 6 inch by 6 inch by 0.37 inch, centered on the marker. Apply the compressive load through the rubber to the top of the marker at a rate of 0.1 inches per minute.

Either cracking or significant deformation of the marker at any load less than 5,000 pounds will constitute failure.

(e) Adhesion: Use bituminous adhesive materials for bonding the markers to the pavement that meet the requirements of Section 970 and are listed on the QPL.

(f) Removability: Ensure that the pavement marker is removable from asphalt pavement and portland cement concrete pavement intact or in substantially large pieces, either manually or by mechanical devices at temperatures above 40°F, and without the use of heat, grinding or blasting.

990-6 Temporary Glare Screen.

990-6.1 Design and Installation: Meet the following requirements:

(a) Glare screen units shall be manufactured in lengths such that when installed the joint between any one modular unit will not span barrier sections. Color shall be green, similar to Federal Color Standard 595-34227.

(b) Blades, rails and/or posts shall be manufactured from polyethylene, fiberglass, plastic, polyester or polystyrene, and be ultraviolet stabilized and inert to all normal atmospheric conditions and temperature ranges found in Florida.

(c) For paddle type designs, the blade width shall not be more than 9 inches. Blades or screen for individual or modular systems shall be 24 to 30 inches high and capable of being locked down at an angle and spacing to provide a cut-off angle not less than 20 degrees.

(d) For glare screen mounted on temporary barrier wall, a strip (6 by 12 inches) of reflective sheeting as specified in 994-2 shall be placed on a panel, centered in each barrier section (at a spacing not to exceed 15 feet) and positioned in such a manner as to permit total

right angle observation by parallel traffic. When glare screen is utilized on temporary concrete barriers, warning lights will not be required.

(e) Prior to approval an impact test shall be performed by the manufacturer to verify the safety performance of the proposed system. The minimum impact strength of the posts, blades, rail and the barrier attachment design shall be sufficient to prevent the unit from separating from the barrier when impacted by a 3 inches outside diameter steel pipe traveling at 30 mph and impacting mid-height on the glare screen assembly.

(f) All hardware shall be galvanized in accordance with ASTM A-123 or stainless steel in accordance with AISI 302/305.

Alternative designs for temporary glare screen may be submitted as a Cost Savings Initiative Proposal in accordance with 4-3.9.

990-6.2 Qualified Products List: Manufactured glare screen systems may be modular or individual units listed on the QPL.

990-7.1 General: Temporary Traffic Control Signals shall be one of the products listed on the APL. Meet the physical display and operational requirements of conventional traffic signal described in the MUTCD for portable traffic signals. The standard includes but is not limited to the following:

(a) Use signal heads having three 12 inch vehicular signal indications (Red, Yellow and Green). Ensure there are two signal heads for each direction of traffic.

(b) The traffic signal heads on this device will be approved by the Department.

(c) Department approved lighting sources will be installed in each section in accordance with the manufacturer's permanent directional marking(s), that is, an "Up Arrow", the word "UP" or "TOP," for correct indexing and orientation within a signal housing.

(d) The masts supporting the traffic signal heads will be manufactured with the lowest point of the vehicular signal head as follows:

(1) Eight feet above finished grade at the point of their installation for "pedestal" type application or

(2) Seventeen to 19 feet above pavement grade at the center of roadway for "overhead" type application.

(e) The yellow clearance interval will be programmed three seconds or more. Under no condition can the yellow clearance interval be manually controlled. It must be timed internally by the controller as per Department specifications.

(f) The green interval must display a minimum of five seconds before being advanced to the yellow clearance interval.

(g) The controller will allow for a variable all red clearance interval from 0 to 999 seconds.

(h) Portable traffic control signals will be either manually controlled or traffic actuated. Indicator lights for monitoring the signal operation of each approach will be supplied and visible from within the work zone area.

(i) When the portable traffic control signals are radio actuated the following will apply:

(1) The transmitter will be FCC Type accepted and not exceed 1 watt output per FCC, Part 90.17. The manufacturer must comply with all "Specific limitations" noted in FCC Part 90.17.

(2) The Controller will force the traffic signal to display red toward the traffic approach in case of radio failure or interference.

(j) The trailer and supports will be painted construction/maintenance orange enamel in accordance with the MUTCD color.

(k) The device will meet NEMA environmental standard. The test report certified by an independent laboratory will be provided.

(l) Ensure the certification number is engraved or labeled permanently on equipment.

(m) Ensure the device has an external, visible, water resistant label with the following information: "Certification of this device by the Florida Department of Transportation allows for its use in Construction Zones Only."

990-8 Work Zone Signs.

Provide steel flanged U-channel or Square Tube steel meeting the mechanical requirements of ASTM A 499, Grade 60. For each U-channel or Square Tube, punch or drill 3/8 inch diameter holes on 1 inch centers through the center of the post, starting approximately 1 inch from the top and extending the full length of the post. Ensure that the weight per foot of a particular manufacturer's post size does not vary more than $\pm 3 \frac{1}{2}\%$ of its specified weight per foot. Taper the bottom end of the post for easier installation. Machine straighten the U-channel to a tolerance of 0.4% of the length. Use only non-corrosive metal, aluminum, or galvanized steel attachment hardware. Work zone sign systems shall be one of the products listed on the QPL.

990-9 Temporary Raised Rumble Strips:

990-9.1 General: Temporary Raised Rumble Strips shall be one of the products listed on the QPL. Meet the physical display and operational requirements in the MUTCD for Temporary Raised Rumble Strips. The Temporary Raised Rumble Strip may be either a removable polymer striping tape type or a molded engineered polymer material type as described below:

990-9.1.1 Removable Polymer Striping Tape:

Characteristic	Requirement
Composition:	Removable Polymer Striping Tape with pre-applied adhesive
Color:	White, Black or Orange
Cross-section:	0.25 in. to 0.50 in. (height) x 4 in. (wide)

990-9.1.2 Molded Engineered Polymer Material:

Characteristic	Requirement
Composition:	Molded Engineered Polymer Material
Weight	Internally ballasted to provide proper weight to maintain position in use without the use of adhesives or mechanical fasteners
Color:	White, Black or Orange
Shape	Beveled on the leading edge
Cross-section:	0.625 in. to 0.875 in. (height) x 12 in. (wide)

990-10 Automated Flagger Assistance Devices (AFAD):

990-10.1 General: AFAD's shall be one of the products listed on the APL. Meet the physical display and operational requirements in the MUTCD for the AFAD as well as the detailed requirements below.

990-10.1.1 Stop/Slow Automated Flagger Assistance Devices: Provide a Stop/Slow AFAD including a Stop/Slow sign that alternately displays the stop face and the slow face of a Stop/Slow paddle without the need for a flagger in the immediate vicinity of the AFAD or on the roadway.

Ensure that the Stop/Slow AFAD includes a gate arm that descends to a down position across the approach lane of traffic when the stop face is displayed and then ascends to an upright position when the slow face is displayed.

Ensure the Gate arm is fully retroreflectorized on both sides, with vertical alternating red and white stripes at 16-inch intervals measured horizontally in accordance with the MUTCD. When the arm is in the down position blocking the approach lane:

A. The minimum vertical aspect of the arm and sheeting shall be 2 inches; and,

B. The end of the arm shall reach at least to the center of the lane being controlled.

990-10.1.2 Red/Yellow Lens Automated Flagger Assistance Devices: Provide a Red/Yellow Lens AFAD that alternately displays a steadily illuminated circular red lens and a flashing circular yellow lens to control traffic without the need for a flagger in the immediate vicinity of the AFAD or on the roadway.

Ensure that the Red/Yellow Lens AFAD includes a gate arm that descends to a down position across the approach lane of traffic when the steady circular red lens is illuminated and then ascends to an upright position when the flashing circular yellow lens is illuminated.

Ensure that the gate arm is fully retroreflectorized on both sides, with vertical alternating red and white stripes at 16-inch intervals measured horizontally in accordance with the MUTCD. When the arm is in the down position blocking the approach lane:

A. The minimum vertical aspect of the arm and sheeting shall be 2 inches; and,

B. The end of the arm shall reach at least to the center of the lane being controlled.

Do not provide a change interval between the display of the steady circular red indication and the display of the flashing circular yellow indication. Provide a steady illuminated circular yellow indication, with at least a 5 second duration, between the transition from flashing circular yellow indication and the display of the steady circular red indication. The Engineer may approve a different duration, provided it falls within the range recommended by the MUTCD.