



Florida Department of Transportation

RICK SCOTT
GOVERNOR

605 Suwannee Street
Tallahassee, FL 32399-0450

ANANTH PRASAD, P.E.
SECRETARY

August 26, 2011

Monica Gourdine
Program Operations Engineer
Federal Highway Administration
545 John Knox Road, Suite 200
Tallahassee, Florida 32303

Re: Office of Design, Specifications
Section 710
Proposed Specification: **7100502 Painted Pavement Markings – Alignment.**

Dear Ms. Gourdine:

We are submitting, **for your records**, two copies of the above referenced Supplemental Specification.

The highlighted changes, which were approved by your office on July 18, 2011, will not be implemented.

If you have any questions relating to this specification change, please call Rudy Powell, State Specifications Engineer at 414-4280.

Sincerely,

Signature on file

Rudy Powell, Jr., P.E.
State Specifications Engineer

RP/dt

Attachment

cc: Gregory Jones, Chief Civil Litigation
Florida Transportation Builders' Assoc.
State Construction Engineer

PAINTED PAVEMENT MARKINGS – ALIGNMENT.**(REV ~~7-9-09~~5-26-11) (FA ~~7-20-09~~7-18-11) (~~1-101-12~~)**

SUBARTICLE 710-5.2 (Page 798) is deleted and the following substituted:

710-5.2 Alignment: Apply painted stripes that will not deviate more than 1 inch from the stringline on tangents and curves one degree or less. Apply painted stripes that will not deviate more than 2 inches from the stringline on curves greater than one degree. ~~Apply painted edge stripes uniformly, not less than 2 inches or more than 4 inches from the edge of pavement, without noticeable breaks or deviations in alignment or width.~~

Remove and replace at no additional cost to the Department, traffic stripes that deviate more than the above stated requirements.

PAINTED PAVEMENT MARKINGS – ALIGNMENT.**(REV-7-9-09) (FA 7-20-09) (1-10)**

SUBARTICLE 710-5.2 (Page 798) is deleted and the following substituted:

710-5.2 Alignment: Apply painted stripes that will not deviate more than 1 inch from the stringline on tangents and curves one degree or less. Apply painted stripes that will not deviate more than 2 inches from the stringline on curves greater than one degree. Apply painted edge stripes uniformly, not less than 2 inches or more than 4 inches from the edge of pavement, without noticeable breaks or deviations in alignment or width.

Remove and replace at no additional cost to the Department, traffic stripes that deviate more than the above stated requirements.