

EXPECTED IMPLEMENTATION JULY 2016

162 PREPARED SOIL LAYER.

(REV 10-30-15) (FA 1-26-16) (7-16)

SUBARTICLE 162-5 is deleted and the following substituted:

162-5 Acceptance Testing.

The Engineer reserves the right to waive or reduce testing requirements for shoulder treatment projects as defined in the Design Standards, Index No. 105.

Immediately after completion of construction operations, sample and test the prepared soil layer at a testing laboratory qualified under 105-6. A LOT is defined as 0.5 shoulder miles. Take random quality control (QC) samples at a minimum of one sample per LOT of prepared surface. When the source of added material changes, the Engineer will require an additional sample. Average four sequential LOTs representing 2.0 shoulder miles to determine compliance with Section 987. Raise the organic matter content of any individual LOT with an organic matter content below 1.5% to at least 1.5%. The Engineer will take a Verification sample at a minimum frequency of one sample per 4 LOTs. If the Verification sample fails (below 1.5% for organics), but the QC sample taken in the corresponding LOT passes, the Engineer will obtain a resolution sample within the same LOT to resolve the non comparison. The Engineer reserves the right to take and test additional samples to determine specification compliance. For failing samples, take and test additional samples, as directed by the Engineer, to delineate areas that need re-treatment. Perform re-treatment at no additional cost to the Department. Perform additional testing of retreated areas, at locations directed by the Engineer, to determine specification compliance. Submit all test results to the Engineer.

162-5.1 Finish Soil Layer: Test sampled material for organic matter content, pH, primary macronutrients (N, P K) and secondary macronutrients (S, Ca, Mg) content. Acquire from the soil testing laboratory fertilizer recommendations for the specific plants to be grown in the area. Do not seed, seed and mulch, or place sod until acceptable values for organic content and pH are obtained in accordance with the requirements of 987-1.

162-5.2 Organic Soil Layer: Test sampled material for organic matter content in accordance with the requirements of 987-1.

162-5.3 Blanket Material: Test blanket material for depth in accordance with the Plans and for soil classification in accordance with AASHTO M145. Add materials as necessary to achieve the required depth.