



Florida Department of Transportation

RICK SCOTT
GOVERNOR

605 Suwannee Street
Tallahassee, FL 32399-0450

JIM BOXOLD
SECRETARY

November 15, 2016

Khoa Nguyen
Director, Office of Technical Services
Federal Highway Administration
3500 Financial Plaza, Suite 400
Tallahassee, Florida 32312

Re: State Specifications Office
Section: **653**
Proposed Specification: **6530205 Pedestrian Signal Assemblies.**

Dear Mr. Nguyen:

We are submitting, for your approval, two copies of the above referenced Supplemental Specification.

The changes are proposed by Steve Duke of the State Materials Office to update an Industry reference. ASTM A325 and ASTM A490 have been withdrawn and consolidated into new ASTM F3125.

Please review and transmit your comments, if any, within two weeks. Comments should be sent via email to dan.hurtado@dot.state.fl.us.

If you have any questions relating to this specification change, please call me at 414-4130.

Sincerely,

Signature on file

Dan Hurtado, P.E.
State Specifications Engineer

DH/dt
Attachment

cc: Florida Transportation Builders' Assoc.
State Construction Engineer

6530205
All Jobs

PEDESTRIAL SIGNAL ASSEMBLIES.
(REV 9-20-16)

SUBARTICLE 653-2.5 is deleted and the following substituted:

653-2.5 Hardware: All brackets used to mount pedestrian signals must be an aluminum alloy cast fitting, pipe or equivalent material approved by the Department. Aluminum and aluminum alloy bars, rods, wires, profiles, and tubes must meet ASTM B221. Aluminum-alloy sand casting must meet ASTM B26. All mounting hardware must be painted black with a reflectance value not exceeding 25 percent as measured by ASTM E97.

Ensure that all assembly hardware, including nuts, bolts, external screws and locking washers less than 5/8 inch in diameter, are Type 304 or 316 passivated stainless steel. Stainless Steel bolts, screws and studs must meet ASTM F593. Nuts must meet ASTM F594. All assembly hardware greater than or equal to 5/8 inch in diameter must be galvanized. Bolts, studs, and threaded rod must meet ASTM A307. Structural bolts must meet ~~ASTM~~Grade A325.

6530205
All Jobs

PEDESTRIAL SIGNAL ASSEMBLIES.
(REV 9-20-16)

SUBARTICLE 653-2.5 is deleted and the following substituted:

653-2.5 Hardware: All brackets used to mount pedestrian signals must be an aluminum alloy cast fitting, pipe or equivalent material approved by the Department. Aluminum and aluminum alloy bars, rods, wires, profiles, and tubes must meet ASTM B221. Aluminum-alloy sand casting must meet ASTM B26. All mounting hardware must be painted black with a reflectance value not exceeding 25 percent as measured by ASTM E97.

Ensure that all assembly hardware, including nuts, bolts, external screws and locking washers less than 5/8 inch in diameter, are Type 304 or 316 passivated stainless steel. Stainless Steel bolts, screws and studs must meet ASTM F593. Nuts must meet ASTM F594. All assembly hardware greater than or equal to 5/8 inch in diameter must be galvanized. Bolts, studs, and threaded rod must meet ASTM A307. Structural bolts must meet [ASTM F3125](#) Grade A325.

Commented [FC1]: A325 structural bolts are now grades under the new F3125 specification; I believe the reference ASTM spec is needed.