

EXPECTED IMPLEMENTATION JANUARY 2018

710 PAINTED PAVEMENT MARKINGS.

(REV 5-26-17) (FA 8-7-17) (1-18)

SUBARTICLE 710-4.1.1 is deleted and the following substituted:

710-4.1.1 Painted Pavement Markings (Final Surface): On concrete surfaces or newly constructed asphalt, the painted pavement markings (final surface) will include one application of standard paint and one application of Class B retroreflective pavement markers applied to the final surface.

For center line and edge line rumble striping where the pavement marking is placed within the grinding, apply a second application of standard paint within 24 hours of each day's grinding operation.

For center line rumble striping installations where retroreflective pavement markers are in conflict with the grinding, install Class D retroreflective pavement markers with the first application of standard paint. Remove Class D markers prior to grinding, then install Class B retroreflective pavement markers in an unground area after grinding.

Do not apply final surface paint for bicycle arrows or bicycle messages, 24 inch longitudinal bars in special emphasis crosswalks, or route shields where preformed thermoplastic will be applied.

Install all retroreflective pavement markers in accordance with Design Standards, Index Nos. 17352 and 17345, prior to opening the road to traffic.

Temporary retroreflective pavement markers must meet the requirements of Section 102.

Permanent retroreflective pavement markers must meet the requirements of Section 706.