

9850202 GEOSYNTHETIC MATERIALS  
COMMENTS FROM INTERNAL/INDUSTRY REVIEW

.....

Charles Boyd  
414-4275  
[charles.boyd@dot.state.fl.us](mailto:charles.boyd@dot.state.fl.us)

Comments: (5-21-18)

In Table 1.1 it looks like the “\*” should be deleted from “US Sieve No. \*” in the first column, second row.

Response:

\*\*\*\*\*

Kevin Hall  
804-275-4109  
[khall@acfenv.com](mailto:khall@acfenv.com)

Comments: (5-24-18)

Will you consider starting to recognize NTPEP certified materials? The NTPEP Datamine has current independent test data for all of their approved fabrics by manufacturer readily available- which would expedite this Spec change for everyone involved.

Response:

\*\*\*\*\*

David Andrews  
770-767-0961  
[david.andrews@propexglobal.com](mailto:david.andrews@propexglobal.com)

Comments: (6-19-18)

1. 985-2.2 – “independent third party” should read “NTPEP” to be consistent with the proposed change in section 985-3.1 Product Acceptance.

Response: 985-2.2 (Materials) states the testing and physical requirements. In 985-3.1 (Product Acceptance), the acceptance requirements states that the manufacturer’s facility must be on NTPEP’s list of compliant producers.

No change made.

2. Table 1.1: Types D-1 & D-2 should allow nonwoven geotextiles as grab tensile properties are included in the table for elongations  $\geq 50\%$ . This is in accordance with AASHTO M288.

Response:

3. Table 1.1: For Minimum Puncture Strength and Minimum Trap Tear, the phrase “other woven geotextiles” should read “other geotextiles”.

Response:

4. Table 1.1 may have a type for D-1a and D-2a. Minimum permittivity should be 0.5 per second.

Response:

5. Table 1.2 should include both US and metric units for AOS to be in accordance with Table 1.1.

Response:

6. The remaining parts of the spec are missing in the review (i.e. sections 985-4.1.2 and 985-4.2.

Response: 985-4.1.2 and 985-4.2 were not revised and are not included for review.  
No change made.

7. Consideration to consolidate Type c and d would simplify the spec considering that AOS is the only differentiator. A standard M288 Class 1 nonwoven has a tighter AOS than both FDOT Types c and d.

Response:

\*\*\*\*\*