

2340100 SUPERPAVE ASPAHLT BASE  
COMMENTS FROM INTERNAL/INDUSTRY REVIEW

Mark Musselman  
(850) 222-7300  
[mmusselman@acaf.org](mailto:mmusselman@acaf.org)

Comments: (5-29-20, Internal)

My members are in favor of this change. We would ask that it be made retroactive so that we could implement it on existing project currently underway. Please let me know if there is anyone else I should discuss this with to see if this could be implemented.

Response:

\*\*\*\*\*

No Name

Comments: (6-4-20, Industry)

The Contractor may use a Type SP-12.5 (Traffic Level B, C, D, or E), mixture or a Type SP-19.0 mixture (Traffic Level B, C, D, or E), Better to say: ...may use a Type-12.5 mixture (Traffic Level ...

Response:

\*\*\*\*\*

Melissa Hollis  
(850) 414-4182  
[Melissa.Hollis@dot.state.fl.us](mailto:Melissa.Hollis@dot.state.fl.us)

Comments: (6-19-20, Industry)

Just a formatting issue- the font seems to change in the bottom line:

purposes only, spread rate calculations should be rounded to the nearest whole number.  
234-8.1.1 Layer Thicknesses: The allowable layer thicknesses for asphalt base mixtures are as follows:  
Type B-12.5, SP-12.5.....1-1/2 to 3-1/2 inches  
Type SP-19.0.....2 to 4 inches

Response:

\*\*\*\*\*