

RON DESANTIS GOVERNOR 605 Suwannee Street Tallahassee, FL 32399-0450 JARED W. PERDUE, P.E. SECRETARY

June 17, 2025

Abi Domond Civil Rights Analysis Intern Federal Highway Administration 3500 Financial Plaza, Suite 400 Tallahassee, Florida 32312

Re: State Specifications Office

Section: 283

Proposed Specification: 2830100 Reclaimed Asphalt Pavement Base

Dear Ms. Domond:

We are submitting, for your approval, two copies of the above referenced Supplemental Specification.

The changes are proposed by Richard Hewitt to expand RAP Base use to limited access shoulders, with the restriction that RAP Base not be used on shoulders designated as Emergency Shoulder Use.

Please review and transmit your comments, if any, within two weeks (10 business days). Comments should be sent via email daniel.strickland@dot.state.fl.us.

If you have any questions relating to this specification change, please call me at (850) 414-4130.

Sincerely,

Signature on File

Daniel Strickland, P.E. State Specifications Engineer

DS/jb

Attachment

cc: Florida Transportation Builders' Assoc.

State Construction Engineer

## RECLAIMED ASPHALT PAVEMENT BASE (REV 4-16-25)

ARTICLE 283-1 is deleted and the following substituted:

## 283-1 Description.

Construct a base course composed of reclaimed asphalt pavement (RAP) material. Use RAP material as base course only on paved shoulders, shared use paths, or other non-traffic bearing applications. If RAP base thickness is not provided in Table 285-1, use RAP base thickness equivalent to the optional base group thickness for limerock. Do not use RAP on shoulders designated as Emergency Shoulder Use nor substitute RAP in lieu of stabilized subgrade. Shoulders designated as Emergency Shoulder Use can be found on the Department's website at the following URL: https://www.fdot.gov/emergencymanagement/esu/default.shtm

## RECLAIMED ASPHALT PAVEMENT BASE (REV 4-16-25)

ARTICLE 283-1 is deleted and the following substituted:

## 283-1 Description.

Construct a base course composed of reclaimed asphalt pavement (RAP) material. Use RAP material as base course only on paved shoulders, shared use paths, or other non-traffic bearing applications. If RAP base thickness is not provided in Table 285-1, use RAP base thickness equivalent to the optional base group thickness for limerock. Do not use RAP on shoulders designated as Emergency Shoulder Use nor substitute RAP in lieu of stabilized subgrade. Shoulders designated as Emergency Shoulder Use can be found on the Department's website at the following URL: <a href="https://www.fdot.gov/emergencymanagement/esu/default.shtm">https://www.fdot.gov/emergencymanagement/esu/default.shtm</a>