



*Florida Department of Transportation*

RON DESANTIS  
GOVERNOR

605 Suwannee Street  
Tallahassee, FL 32399-0450

JARED W. PERDUE, P.E.  
SECRETARY

September 3, 2026

Daniel Holt, PE, PTOE  
Director, Project Delivery  
Director, Technical Services  
FHWA  
400 West Washington Street, Suite 4200  
Orlando, FL 32801

Re: State Specifications Office  
Section: 992  
Proposed Specification: **9920102 Highway Lighting Materials**

Dear Mr. Holt:

We are submitting, for your approval, two copies of the above referenced Supplemental Specification.

The changes are proposed by Richard Stepp to support the usage of different base options as listed on the APL.

Please review and transmit your comments, if any, within two weeks (10 business days). Comments should be sent via email [daniel.strickland@dot.state.fl.us](mailto:daniel.strickland@dot.state.fl.us).

If you have any questions relating to this specification change, please call me at (850) 414-4130.

Sincerely,

Signature on File

Daniel Strickland, P.E.  
State Specifications Engineer

DS/am

Attachment

cc: Florida Transportation Builders' Assoc.  
State Construction Engineer

## **HIGHWAY LIGHTING MATERIALS**

### **(REV 6-30-26)**

SUBARTICLE 992-1.2 is deleted and the following substituted:

**992-1.2 Luminaires, Driver, etc.:** All luminaires shall be one of the products listed on the Department's Approved Product List (APL). Manufacturers seeking evaluation of their product shall submit an application and sample luminaire in accordance with Section 6.

The light source for luminaires shall be either light emitting diodes (LED), magnetic induction or plasma induction.

The luminaire housing shall be constructed of precision cast aluminum with a corrosive resistant polyester powder coat finish. The standard color shall be gray. The housing shall have an electrical terminal block to attach the luminaire cable and a hinged door which provides direct access to internal parts. Hinged doors are not required for high mast luminaires and underdeck luminaires. All hardware on the exterior of the housing shall be stainless steel. The refractor and lens shall consist of glass or an optical grade polymer. The manufacturer shall place a permanent tag in the luminaire housing imprinted with: the manufacturer name, luminaire voltage, lamp wattage, and provide a blank area for the Contractor to inscribe the installation date.

Luminaires shall meet the following requirements: UL 1598 listed and labeled for installation in wet locations by an OSHA recognized "Nationally Recognized Testing Laboratory" (NRTL), be capable of maintaining 94.1% intensity at 10,000 hours with an ambient temperature of 25°C (IES LM-80) and have IESNA light distribution curves (IES LM-79) by an EPA recognized laboratory.

The driver shall be rated for 100,000 hours and have a power factor greater than or equal to 90% at full load with a total harmonic distortion less than or equal to 20% at full load. The fixture shall accommodate a circuit voltage of 480V.

Luminaires shall be provided with a minimum 10kV/10kA internal surge suppression module meeting UL 1449/ANSI C62.41.2 Category C.

The manufacturer shall submit a ten-year non-prorated full warranty on all components of the luminaire to the Department. The warranty shall begin on the date the luminaire is shipped from the vendor.

SUBARTICLE 992-2.2 is deleted and the following substituted:

**992-2.2 Frangible Bases:** Frangible bases are required for aluminum poles mounted to general concrete foundations, excluding median barrier and pedestal mounts per the Standard Plans. Frangible bases shall be one of the products listed on the Department's APL. Manufacturers seeking evaluation of products for inclusion on the APL must submit an application in accordance with Section 6, including documentation showing that the product meets crash test and wind load requirements per the Standard Plans, Index 715 series.