

FREEWAY WEAVING WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 NB
Agency/Company	AECOM	Weaving Segment Location	Seg 1-Bet Copans & Sample
Date Performed		Analysis Year	2020 Build 1
Analysis Time Period	AM		

Project Description SW 10th Street SIMR

Inputs

Weaving configuration	One-Sided	Segment type	Freeway
Weaving number of lanes, N	4	Freeway minimum speed, S_{MIN}	15
Weaving segment length, L_S	2380ft	Freeway maximum capacity, C_{IFL}	2400
Freeway free-flow speed, FFS	70 mph	Terrain type	Level

Conversions to pc/h Under Base Conditions

	V (veh/h)	PHF	Truck (%)	RV (%)	E_T	E_R	f_{HV}	f_p	v (pc/h)
V_{FF}	4435	0.95	3	0	1.5	1.2	0.985	1.00	4738
V_{RF}	345	0.92	2	0	1.5	1.2	0.990	1.00	379
V_{FR}	810	0.92	2	0	1.5	1.2	0.990	1.00	889
V_{RR}	0	0.95	0	0	1.5	1.2	1.000	1.00	0
V_{NW}	4738							V =	6006
V_W	1268								
VR	0.211								

Configuration Characteristics

Minimum maneuver lanes, N_{WL}	2 lc	Minimum weaving lane changes, LC_{MIN}	1268 lc/h
Interchange density, ID	0.7 int/mi	Weaving lane changes, LC_W	1703 lc/h
Minimum RF lane changes, LC_{RF}	1 lc/pc	Non-weaving lane changes, LC_{NW}	1496 lc/h
Minimum FR lane changes, LC_{FR}	1 lc/pc	Total lane changes, LC_{ALL}	3199 lc/h
Minimum RR lane changes, LC_{RR}	lc/pc	Non-weaving vehicle index, I_{NW}	789

Weaving Segment Speed, Density, Level of Service, and Capacity

Weaving segment flow rate, v	5924 veh/h	Weaving intensity factor, W	0.285
Weaving segment capacity, c_w	8772 veh/h	Weaving segment speed, S	54.5 mph
Weaving segment v/c ratio	0.675	Average weaving speed, S_W	57.8 mph
Weaving segment density, D	27.6 pc/mi/ln	Average non-weaving speed, S_{NW}	53.7 mph
Level of Service, LOS	C	Maximum weaving length, L_{MAX}	4650 ft

Notes


- a. Weaving segments longer than the calculated maximum length should be treated as isolated merge and diverge areas using the procedures of Chapter 13, "Freeway Merge and Diverge Segments".
- b. For volumes that exceed the weaving segment capacity, the level of service is "F".

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst		Highway/Direction of Travel	<i>I-95 NB</i>
Agency or Company	<i>AECOM</i>	From/To	<i>Seg 2-Bet On & On from Sample</i>
Date Performed		Jurisdiction	
Analysis Time Period	<i>AM</i>	Analysis Year	<i>2020 Build 1</i>
Project Description <i>SW 10th Street SIMR</i>			
<input checked="" type="checkbox"/> Oper.(LOS)		<input type="checkbox"/> Des.(N)	
		<input type="checkbox"/> Planning Data	
Flow Inputs			
Volume, V	<i>4780</i>	veh/h	Peak-Hour Factor, PHF
AADT		veh/day	%Trucks and Buses, P _T
Peak-Hr Prop. of AADT, K			%RVs, P _R
Peak-Hr Direction Prop, D			General Terrain:
DDHV = AADT x K x D		veh/h	Grade % Length
			Up/Down %
			<i>0.95</i>
			<i>3</i>
			<i>0</i>
			<i>Level</i>
			<i>mi</i>
Calculate Flow Adjustments			
f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>
Speed Inputs		Calc Speed Adj and FFS	
Lane Width		ft	
Rt-Side Lat. Clearance		ft	f _{LV}
Number of Lanes, N	<i>3</i>		f _{LC}
Total Ramp Density, TRD		ramps/mi	TRD Adjustment
FFS (measured)	<i>70.0</i>	mph	FFS
Base free-flow Speed, BFFS		mph	<i>70.0</i>
			mph
LOS and Performance Measures		Design (N)	
Operational (LOS)		Design (N)	
v _p = (V or DDHV) / (PHF x N x f _{HV} x f _p)	<i>1702</i>	pc/h/ln	Design LOS
S	<i>67.1</i>	mph	v _p = (V or DDHV) / (PHF x N x f _{HV} x f _p)
D = v _p / S	<i>25.4</i>	pc/mi/ln	S
LOS	<i>C</i>		D = v _p / S
			Required Number of Lanes, N
Glossary		Factor Location	
N - Number of lanes	S - Speed	E _R - Exhibits 11-10, 11-12	f _{LV} - Exhibit 11-8
V - Hourly volume	D - Density	E _T - Exhibits 11-10, 11-11, 11-13	f _{LC} - Exhibit 11-9
v _p - Flow rate	FFS - Free-flow speed	f _p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v _p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Job: SW 10th Street SIMR
Analyst: AECOM

Location: Seg 3: I-95 Northbound On-Ramp from WB Sample Road
Analysis Period: AM Peak Hour
Analysis Year: 2020 Build 1



	PHF =	0.95	
	$V_{fr} =$	6,030	vph
	$V_r =$	1,250	vph
	$V_f =$	4,780	
Upstream Freeway	Tr % =	3%	
Ramp	Tr % =	2%	
Downstream Freeway	Tr % =	3%	
Freeway	$f_{HV} =$	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	<u>0.985</u>
Ramp	$f_{HV} =$	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	<u>0.9901</u>
flat terrain	$E_T =$	1.5	
	RV % =	0	
Driver Population adj.	$f_P =$	1.000	
	$V_{fr} =$	$=V_{fr}/(PHF)(f_{HV})(f_P) =$	6,443 pc/h
	$V_r =$	$=V_r/(PHF)(f_{HV})(f_P) =$	1,329 pc/h
	$V_f =$	$=V_f/(PHF)(f_{HV})(f_P) =$	5,107 pc/h
No. lanes upstream of ramp	$N =$	3	

<u>No. Ln</u>	<u>Capacity Check (see Exhibits 25-3 and 25-7):</u>	Maximum	Actual	V/c	LOS F?
4	Fwy downstream of ramp (assume 70 mph free-flow speed) =	9,600	6,443	0.67	No
3	Fwy upstream of ramp (assume 70 mph free-flow speed) =	7,200	5,107	0.71	No
1	Capacity on On-Ramp (assume 45 mph free-flow speed) =	2,100	1,329	0.63	No

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst		Highway/Direction of Travel	I-95 NB
Agency or Company	AECOM	From/To	Seg 4-Bet On from Sample & Exp
Date Performed		Jurisdiction	
Analysis Time Period	AM	Analysis Year	2020 Build 1
Project Description SW 10th Street SIMR			
<input checked="" type="checkbox"/> Oper.(LOS)		<input type="checkbox"/> Des.(N)	
		<input type="checkbox"/> Planning Data	
Flow Inputs			
Volume, V	6030	veh/h	Peak-Hour Factor, PHF
AADT		veh/day	%Trucks and Buses, P _T
Peak-Hr Prop. of AADT, K			%RVs, P _R
Peak-Hr Direction Prop, D			General Terrain:
DDHV = AADT x K x D		veh/h	Grade 0.00% Length 0.00mi
			Up/Down % 0.00
Calculate Flow Adjustments			
f _p	1.00	E _R	1.2
E _T	1.5	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	0.985
Speed Inputs		Calc Speed Adj and FFS	
Lane Width	ft	f _{LW}	mph
Rt-Side Lat. Clearance	ft	f _{LC}	mph
Number of Lanes, N	4	TRD Adjustment	mph
Total Ramp Density, TRD	ramps/mi	FFS	70.0 mph
FFS (measured)	70.0 mph		
Base free-flow Speed, BFFS	mph		
LOS and Performance Measures		Design (N)	
Operational (LOS)		Design (N)	
v _p = (V or DDHV) / (PHF x N x f _{HV} x f _p)	1611 pc/h/ln	Design LOS	
S	68.0 mph	v _p = (V or DDHV) / (PHF x N x f _{HV} x f _p)	pc/h/ln
D = v _p / S	23.7 pc/mi/ln	S	mph
LOS	C	D = v _p / S	pc/mi/ln
		Required Number of Lanes, N	
Glossary		Factor Location	
N - Number of lanes	S - Speed	E _R - Exhibits 11-10, 11-12	f _{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E _T - Exhibits 11-10, 11-11, 11-13	f _{LC} - Exhibit 11-9
v _p - Flow rate	FFS - Free-flow speed	f _p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v _p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 NB
Agency or Company	AECOM	Junction	Seg 5-On from Exp
Date Performed		Jurisdiction	
Analysis Time Period	AM	Analysis Year	2020 Build 1

Project Description SW 10th Street SIMR

Inputs

Upstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off $L_{up} =$ ft $V_u =$ veh/h	Freeway Number of Lanes, N 4 Ramp Number of Lanes, N 1 Acceleration Lane Length, L_A 1500 Deceleration Lane Length L_D Freeway Volume, V_F 6030 Ramp Volume, V_R 890 Freeway Free-Flow Speed, S_{FF} 70.0 Ramp Free-Flow Speed, S_{FR} 50.0	Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input type="checkbox"/> On <input type="checkbox"/> No <input checked="" type="checkbox"/> Off $L_{down} =$ 6200 ft $V_D =$ 1070 veh/h
--	--	---

Conversion to pc/h Under Base Conditions

(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f_{HV}	f_p	$v = V/PHF \times f_{HV} \times f_p$
Freeway	6030	0.95	Level	3	0	0.985	1.00	6443
Ramp	890	0.92	Level	2	0	0.990	1.00	977
UpStream								
DownStream	1070	0.92	Level	2	0	0.990	1.00	1175

Merge Areas

Diverge Areas

Estimation of v_{12}

$V_{12} = V_F (P_{FM})$
 (Equation 13-6 or 13-7)
 $L_{EQ} =$
 $P_{FM} =$ 0.096 using Equation (Exhibit 13-6)
 $V_{12} =$ 616 pc/h
 V_3 or V_{av34} 2913 pc/h (Equation 13-14 or 13-17)
 Is V_3 or $V_{av34} > 2,700$ pc/h? Yes No
 Is V_3 or $V_{av34} > 1.5 * V_{12}/2$ Yes No
 If Yes, $V_{12a} =$ 2577 pc/h (Equation 13-16, 13-18, or 13-19)

Estimation of v_{12}

$V_{12} = V_R + (V_F - V_R)P_{FD}$
 (Equation 13-12 or 13-13)
 $L_{EQ} =$
 $P_{FD} =$ using Equation (Exhibit 13-7)
 $V_{12} =$ pc/h
 V_3 or V_{av34} pc/h (Equation 13-14 or 13-17)
 Is V_3 or $V_{av34} > 2,700$ pc/h? Yes No
 Is V_3 or $V_{av34} > 1.5 * V_{12}/2$ Yes No
 If Yes, $V_{12a} =$ pc/h (Equation 13-16, 13-18, or 13-19)

Capacity Checks

	Actual	Capacity	LOS F?		Actual	Capacity	LOS F?
V_{FO}	7420	Exhibit 13-8	No	V_F		Exhibit 13-8	
				$V_{FO} = V_F - V_R$		Exhibit 13-8	
				V_R		Exhibit 13-10	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
V_{R12}	3863	Exhibit 13-8	4600:All
			No

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
V_{12}		Exhibit 13-8	

Level of Service Determination (if not F)

$D_R = 5.475 + 0.00734 V_R + 0.0078 V_{12} - 0.00627 L_A$
 $D_R =$ 27.4 (pc/mi/ln)
 LOS = C (Exhibit 13-2)

Level of Service Determination (if not F)

$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$
 $D_R =$ (pc/mi/ln)
 LOS = (Exhibit 13-2)

Speed Determination

$M_S =$ 0.357 (Exhibit 13-11)
 $S_R =$ 60.0 mph (Exhibit 13-11)
 $S_0 =$ 65.8 mph (Exhibit 13-11)
 $S =$ 62.6 mph (Exhibit 13-13)

Speed Determination

$D_S =$ (Exhibit 13-12)
 $S_R =$ mph (Exhibit 13-12)
 $S_0 =$ mph (Exhibit 13-12)
 $S =$ mph (Exhibit 13-13)

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *AM*

Site Information

Highway/Direction of Travel *I-95 NB*
 From/To *Seg 6-Bet Exp On & Off to 10th*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	6920	veh/h	Peak-Hour Factor, PHF	0.95
AADT		veh/day	%Trucks and Buses, P _T	3
Peak-Hr Prop. of AADT, K			%RVs, P _R	0
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	1.00	E _R	1.2
E _T	1.5	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	0.985

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N 3
 Total Ramp Density, TRD ramps/mi
 FFS (measured) 70.0 mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS 70.0 mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ 2464 pc/h/ln
 S 51.5 mph
 $D = v_p / S$ 47.9 pc/mi/ln
 LOS F

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary


N - Number of lanes S - Speed
 V - Hourly volume D - Density
 v_p - Flow rate FFS - Free-flow speed
 LOS - Level of service BFFS - Base free-flow speed
 DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12 f_{LW} - Exhibit 11-8
 E_T - Exhibits 11-10, 11-11, 11-13 f_{LC} - Exhibit 11-9
 f_p - Page 11-18 TRD - Page 11-11
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3

Job: SW 10th Street SIMR
Analyst: AECOM

Location: Seg 7: I-95 NB Off-Ramp to SW 10th St EB & WB
Analysis Period: AM Peak Hour
Analysis Year: 2020 Build 1



	PHF =	0.95	
	$V_{fr} =$	6,920	vph
	$V_r =$	1,070	vph
	$V_f =$	5,850	
Upstream Freeway	Tr % =	3%	
Ramp	Tr % =	2%	
Downstream Freeway	Tr % =	3%	
	Freeway $f_{HV} =$	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	0.985
	Ramp $f_{HV} =$	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	0.990099
	flat terrain $E_T =$	1.5	
	RV % =	0	
Driver Population adj.	$f_P =$	1.000	
	$V_{fr} =$	$=V_{fr}/(PHF)(f_{HV})(f_P) =$	7,393 pc/h
	$V_r =$	$=V_r/(PHF)(f_{HV})(f_P) =$	1,138 pc/h
	$V_f =$	$=V_f/(PHF)(f_{HV})(f_P) =$	6,250 pc/h
No. lanes upstream of ramp	$N =$	4	

Average Freeway Density Upstream of Diverge (see Equation 13-26):

$D = 0.0175 (V_{fr}/N) = 32.3 \text{ pc/ln}$

LOS in the Diverge Area (from Density and Exhibit 13-2) =

D

No. Ln	Capacity Check (see Exhibits 13-2, 13-8 and 13.10)	Maximum	Actual	LOS F?
4	Fwy upstream of ramp (assume 70 mph free-flow speed) =	9,600	7,393	No
3	Fwy downstream of ramp (assume 70 mph free-flow speed) =	7,200	6,250	No
1	Capacity on Off-Ramp (assume 45 mph free-flow speed) =	2,100	1,138	No

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *AM*

Site Information

Highway/Direction of Travel *I-95 NB*
 From/To *Seg 8-Bet Off & Off Ramps*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>5850</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *2083* pc/h/ln
 S *61.0* mph
 $D = v_p / S$ *34.2* pc/mi/ln
 LOS *D*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 NB
Agency or Company	AECOM	Junction	Seg 9-Off to Hillsboro EB&WB
Date Performed		Jurisdiction	
Analysis Time Period	AM	Analysis Year	2020 Build 1

Project Description SW 10th Street SIMR

Inputs			
Upstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L _{up} = ft V _u = veh/h	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;"> Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L_A Deceleration Lane Length L_D 200 Freeway Volume, V_F 5850 Ramp Volume, V_R 1310 Freeway Free-Flow Speed, S_{FF} 70.0 Ramp Free-Flow Speed, S_{FR} 45.0 </td> <td style="width: 50%; vertical-align: top;"> Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L_{down} = 2800 ft V_D = 1460 veh/h </td> </tr> </table>	Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A Deceleration Lane Length L _D 200 Freeway Volume, V _F 5850 Ramp Volume, V _R 1310 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 45.0	Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L _{down} = 2800 ft V _D = 1460 veh/h
Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A Deceleration Lane Length L _D 200 Freeway Volume, V _F 5850 Ramp Volume, V _R 1310 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 45.0	Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L _{down} = 2800 ft V _D = 1460 veh/h		

Conversion to pc/h Under Base Conditions								
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p
Freeway	5850	0.95	Level	3	0	0.985	1.00	6250
Ramp	1310	0.92	Level	2	0	0.990	1.00	1438
UpStream								
DownStream	1460	0.92	Level	2	0	0.990	1.00	1603

Merge Areas	Diverge Areas
Estimation of v₁₂ $V_{12} = V_F (P_{FM})$ L _{EQ} = (Equation 13-6 or 13-7) P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)	Estimation of v₁₂ $V_{12} = V_R + (V_F - V_R)P_{FD}$ L _{EQ} = (Equation 13-12 or 13-13) P _{FD} = 0.538 using Equation (Exhibit 13-7) V ₁₂ = 4025 pc/h V ₃ or V _{av34} 2225 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)

Capacity Checks				Capacity Checks					
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	6250	Exhibit 13-8	7200	No
			V _{FO} = V _F - V _R	4812	Exhibit 13-8	7200	No		
			V _R	1438	Exhibit 13-10	2100	No		

Flow Entering Merge Influence Area				Flow Entering Diverge Influence Area				
	Actual	Max Desirable	Violation?		Actual	Max Desirable	Violation?	
V _{R12}		Exhibit 13-8		V ₁₂	4025	Exhibit 13-8	4400:All	No

Level of Service Determination (if not F)	Level of Service Determination (if not F)
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)	$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 37.1 (pc/mi/ln) LOS = E (Exhibit 13-2)

Speed Determination	Speed Determination
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)	D _s = 0.427 (Exhibit 13-12) S _R = 58.0 mph (Exhibit 13-12) S ₀ = 72.0 mph (Exhibit 13-12) S = 62.3 mph (Exhibit 13-13)

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *AM*

Site Information

Highway/Direction of Travel *I-95 NB*
 From/To *Seg 10-Bet Off & On Ramps*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>4540</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1617* pc/h/ln
 S *68.0* mph
 $D = v_p / S$ *23.8* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 NB
Agency or Company	AECOM	Junction	Seg 11-On Ramp 10th St EB & WB
Date Performed		Jurisdiction	
Analysis Time Period	AM	Analysis Year	2020 Build 1
Project Description SW 10th Street SIMR			

Inputs			
Upstream Adj Ramp	Freeway Number of Lanes, N	3	Downstream Adj Ramp
<input checked="" type="checkbox"/> Yes <input type="checkbox"/> On	Ramp Number of Lanes, N	1	<input type="checkbox"/> Yes <input type="checkbox"/> On
<input type="checkbox"/> No <input checked="" type="checkbox"/> Off	Acceleration Lane Length, L _A	1200	<input checked="" type="checkbox"/> No <input type="checkbox"/> Off
L _{up} = 2800 ft	Deceleration Lane Length L _D		L _{down} = ft
V _u = 1310 veh/h	Freeway Volume, V _F	4540	V _D = veh/h
	Ramp Volume, V _R	1460	
	Freeway Free-Flow Speed, S _{FF}	70.0	
	Ramp Free-Flow Speed, S _{FR}	50.0	

Conversion to pc/h Under Base Conditions								
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p
Freeway	4540	0.95	Level	3	0	0.985	1.00	4851
Ramp	1460	0.92	Level	2	0	0.990	1.00	1603
UpStream	1310	0.92	Level	2	0	0.990	1.00	1438
DownStream								

Merge Areas				Diverge Areas			
Estimation of v ₁₂				Estimation of v ₁₂			
$V_{12} = V_F (P_{FM})$ L _{EQ} = 2126.96 (Equation 13-6 or 13-7) P _{FM} = 0.611 using Equation (Exhibit 13-6) V ₁₂ = 2964 pc/h V ₃ or V _{av34} = 1887 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = 2964 pc/h (Equation 13-16, 13-18, or 13-19)				$V_{12} = V_R + (V_F - V_R)P_{FD}$ L _{EQ} = (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)			

Capacity Checks				Capacity Checks			
	Actual	Capacity	LOS F?		Actual	Capacity	LOS F?
V _{FO}	6454	Exhibit 13-8	No	V _F		Exhibit 13-8	
				V _{FO} = V _F - V _R		Exhibit 13-8	
				V _R		Exhibit 13-10	

Flow Entering Merge Influence Area				Flow Entering Diverge Influence Area			
	Actual	Max Desirable	Violation?		Actual	Max Desirable	Violation?
V _{R12}	4567	Exhibit 13-8	4600:All	No	V ₁₂	Exhibit 13-8	

Level of Service Determination (if not F)				Level of Service Determination (if not F)			
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 32.8 (pc/mi/ln) LOS = D (Exhibit 13-2)				$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)			

Speed Determination		Speed Determination	
S _s = 0.576 (Exhibit 13-11)	S _R = 53.9 mph (Exhibit 13-11)	S _s = (Exhibit 13-12)	S _R = mph (Exhibit 13-12)
S ₀ = 65.0 mph (Exhibit 13-11)	S = 56.7 mph (Exhibit 13-13)	S ₀ = mph (Exhibit 13-12)	S = mph (Exhibit 13-13)

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *AM*

Site Information

Highway/Direction of Travel *I-95 NB*
 From/To *Seg 12-Bet On Ramps*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>6000</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *2137* pc/h/ln
 S *59.8* mph
 $D = v_p / S$ *35.7* pc/mi/ln
 LOS *E*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes S - Speed
 V - Hourly volume D - Density
 v_p - Flow rate FFS - Free-flow speed
 LOS - Level of service BFFS - Base free-flow speed
 DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12 f_{LW} - Exhibit 11-8
 E_T - Exhibits 11-10, 11-11, 11-13 f_{LC} - Exhibit 11-9
 f_p - Page 11-18 TRD - Page 11-11
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3

FREEWAY WEAVING WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 NB
Agency/Company	AECOM	Weaving Segment Location	Seg 13-Bet On & Off to Exp
Date Performed		Analysis Year	2020 Build 1
Analysis Time Period	AM		

Project Description SW 10th Street SIMR

Inputs

Weaving configuration	Two-Sided	Segment type	Freeway
Weaving number of lanes, N	4	Freeway minimum speed, S_{MIN}	15
Weaving segment length, L_S	4600ft	Freeway maximum capacity, C_{IFL}	2400
Freeway free-flow speed, FFS	70 mph	Terrain type	Level

Conversions to pc/h Under Base Conditions

	V (veh/h)	PHF	Truck (%)	RV (%)	E_T	E_R	f_{HV}	f_p	v (pc/h)
V_{FF}	4765	0.95	3	0	1.5	1.2	0.985	1.00	5091
V_{RF}	1145	0.92	2	0	1.5	1.2	0.990	1.00	1257
V_{FR}	1235	0.92	2	0	1.5	1.2	0.990	1.00	1356
V_{RR}	125	0.92	2	0	1.5	1.2	0.990	1.00	137
V_{NW}	7704							V =	7841
V_W	137								
VR	0.017								

Configuration Characteristics

Minimum maneuver lanes, N_{WL}	0 lc	Minimum weaving lane changes, LC_{MIN}	411 lc/h
Interchange density, ID	0.7 int/mi	Weaving lane changes, LC_W	1037 lc/h
Minimum RF lane changes, LC_{RF}	0 lc/pc	Non-weaving lane changes, LC_{NW}	3407 lc/h
Minimum FR lane changes, LC_{FR}	0 lc/pc	Total lane changes, LC_{ALL}	4444 lc/h
Minimum RR lane changes, LC_{RR}	3 lc/pc	Non-weaving vehicle index, I_{NW}	2481

Weaving Segment Speed, Density, Level of Service, and Capacity

Weaving segment flow rate, v	7739 veh/h	Weaving intensity factor, W	0.220
Weaving segment capacity, c_w	9068 veh/h	Weaving segment speed, S	57.7 mph
Weaving segment v/c ratio	0.853	Average weaving speed, S_W	60.1 mph
Weaving segment density, D	34.0 pc/mi/ln	Average non-weaving speed, S_{NW}	57.6 mph
Level of Service, LOS	D	Maximum weaving length, L_{MAX}	5889 ft

Notes

- a. Weaving segments longer than the calculated maximum length should be treated as isolated merge and diverge areas using the procedures of Chapter 13, "Freeway Merge and Diverge Segments".
- b. For volumes that exceed the weaving segment capacity, the level of service is "F".

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *AM*

Site Information

Highway/Direction of Travel *I-95 NB*
 From/To *Seg 14-North of Hillsboro*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>5910</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>4</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.980</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *4*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1586* pc/h/ln
 S *68.3* mph
 $D = v_p / S$ *23.2* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

FREEWAY WEAVING WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 NB
Agency/Company	AECOM	Weaving Segment Location	Seg 1-Bet Copans & Sample
Date Performed		Analysis Year	2020 Build 1
Analysis Time Period	PM		

Project Description SW 10th Street SIMR

Inputs

Weaving configuration	One-Sided	Segment type	Freeway
Weaving number of lanes, N	4	Freeway minimum speed, S_{MIN}	15
Weaving segment length, L_S	2380ft	Freeway maximum capacity, C_{IFL}	2400
Freeway free-flow speed, FFS	70 mph	Terrain type	Level

Conversions to pc/h Under Base Conditions

	V (veh/h)	PHF	Truck (%)	RV (%)	E_T	E_R	f_{HV}	f_p	v (pc/h)
V_{FF}	4400	0.95	3	0	1.5	1.2	0.985	1.00	4701
V_{RF}	410	0.92	2	0	1.5	1.2	0.990	1.00	450
V_{FR}	1570	0.92	2	0	1.5	1.2	0.990	1.00	1724
V_{RR}	0	0.95	0	0	1.5	1.2	1.000	1.00	0
V_{NW}	4701							V =	6875
V_W	2174								
VR	0.316								

Configuration Characteristics

Minimum maneuver lanes, N_{WL}	2 lc	Minimum weaving lane changes, LC_{MIN}	2174 lc/h
Interchange density, ID	0.7 int/mi	Weaving lane changes, LC_W	2609 lc/h
Minimum RF lane changes, LC_{RF}	1 lc/pc	Non-weaving lane changes, LC_{NW}	1488 lc/h
Minimum FR lane changes, LC_{FR}	1 lc/pc	Total lane changes, LC_{ALL}	4097 lc/h
Minimum RR lane changes, LC_{RR}	lc/pc	Non-weaving vehicle index, I_{NW}	783

Weaving Segment Speed, Density, Level of Service, and Capacity

Weaving segment flow rate, v	6784 veh/h	Weaving intensity factor, W	0.347
Weaving segment capacity, c_w	7478 veh/h	Weaving segment speed, S	48.8 mph
Weaving segment v/c ratio	0.907	Average weaving speed, S_W	55.8 mph
Weaving segment density, D	35.2 pc/mi/ln	Average non-weaving speed, S_{NW}	46.1 mph
Level of Service, LOS	E	Maximum weaving length, L_{MAX}	5759 ft

Notes


- a. Weaving segments longer than the calculated maximum length should be treated as isolated merge and diverge areas using the procedures of Chapter 13, "Freeway Merge and Diverge Segments".
- b. For volumes that exceed the weaving segment capacity, the level of service is "F".

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst		Highway/Direction of Travel	I-95 NB
Agency or Company	AECOM	From/To	Seg 2-Bet On & On from Sample
Date Performed		Jurisdiction	
Analysis Time Period	PM	Analysis Year	2020 Build 1
Project Description SW 10th Street SIMR			
<input checked="" type="checkbox"/> Oper.(LOS)		<input type="checkbox"/> Des.(N)	
<input type="checkbox"/> Planning Data			
Flow Inputs			
Volume, V	4810	veh/h	Peak-Hour Factor, PHF
AADT		veh/day	%Trucks and Buses, P _T
Peak-Hr Prop. of AADT, K			%RVs, P _R
Peak-Hr Direction Prop, D			General Terrain:
DDHV = AADT x K x D		veh/h	Grade % Length
			Up/Down %
			0.95
			3
			0
			Level
			mi
Calculate Flow Adjustments			
f _p	1.00	E _R	1.2
E _T	1.5	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	0.985
Speed Inputs		Calc Speed Adj and FFS	
Lane Width	ft	f _{LW}	mph
Rt-Side Lat. Clearance	ft	f _{LC}	mph
Number of Lanes, N	3	TRD Adjustment	mph
Total Ramp Density, TRD	ramps/mi	FFS	70.0
FFS (measured)	70.0		mph
Base free-flow Speed, BFFS	mph		
LOS and Performance Measures		Design (N)	
Operational (LOS)		Design (N)	
v _p = (V or DDHV) / (PHF x N x f _{HV} x f _p)	1713 pc/h/ln	Design LOS	
S	66.9 mph	v _p = (V or DDHV) / (PHF x N x f _{HV} x f _p)	pc/h/ln
D = v _p / S	25.6 pc/mi/ln	S	mph
LOS	C	D = v _p / S	pc/mi/ln
		Required Number of Lanes, N	
Glossary		Factor Location	
N - Number of lanes	S - Speed	E _R - Exhibits 11-10, 11-12	f _{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E _T - Exhibits 11-10, 11-11, 11-13	f _{LC} - Exhibit 11-9
v _p - Flow rate	FFS - Free-flow speed	f _p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v _p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Job: SW 10th Street SIMR
Analyst: AECOM

Location: Seg 3: I-95 Northbound On-Ramp from WB Sample Road
Analysis Period: PM Peak Hour
Analysis Year: 2020 Build 1



	PHF =	0.95	
	$V_{fr} =$	5,780	vph
	$V_r =$	970	vph
	$V_f =$	4,810	
Upstream Freeway	Tr % =	3%	
Ramp	Tr % =	2%	
Downstream Freeway	Tr % =	3%	
Freeway	$f_{HV} = 1/(1+P_T(E_T-1)+P_R(E_R-1)) =$		0.985
Ramp	$f_{HV} = 1/(1+P_T(E_T-1)+P_R(E_R-1)) =$		0.9901
flat terrain	$E_T =$	1.5	
	RV % =	0	
Driver Population adj.	$f_P =$	1.000	
	$V_{fr} = v_{fr}/(PHF)(f_{HV})(f_P) =$		6,175 pc/h
	$V_r = v_r/(PHF)(f_{HV})(f_P) =$		1,031 pc/h
	$V_f = v_f/(PHF)(f_{HV})(f_P) =$		5,139 pc/h
No. lanes upstream of ramp	$N =$	3	

No. Ln	Capacity Check (see Exhibits 25-3 and 25-7):	Maximum	Actual	V/c	LOS F?
4	Fwy downstream of ramp (assume 70 mph free-flow speed) =	9,600	6,175	0.64	No
3	Fwy upstream of ramp (assume 70 mph free-flow speed) =	7,200	5,139	0.71	No
1	Capacity on On-Ramp (assume 45 mph free-flow speed) =	2,100	1,031	0.49	No

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst		Highway/Direction of Travel	I-95 NB
Agency or Company	AECOM	From/To	Seg 4-Bet On from Sample & Exp
Date Performed		Jurisdiction	
Analysis Time Period	PM	Analysis Year	2020 Build 1
Project Description SW 10th Street SIMR			
<input checked="" type="checkbox"/> Oper.(LOS)		<input type="checkbox"/> Des.(N)	
		<input type="checkbox"/> Planning Data	
Flow Inputs			
Volume, V	5780	veh/h	Peak-Hour Factor, PHF
AADT		veh/day	%Trucks and Buses, P _T
Peak-Hr Prop. of AADT, K			%RVs, P _R
Peak-Hr Direction Prop, D			General Terrain: Grade
DDHV = AADT x K x D		veh/h	Grade 0.00% Length 0.00mi
			Up/Down % 0.00
Calculate Flow Adjustments			
f _p	1.00	E _R	1.2
E _T	1.5	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	0.985
Speed Inputs		Calc Speed Adj and FFS	
Lane Width	ft	f _{LW}	mph
Rt-Side Lat. Clearance	ft	f _{LC}	mph
Number of Lanes, N	4	TRD Adjustment	mph
Total Ramp Density, TRD	ramps/mi	FFS	70.0 mph
FFS (measured)	70.0 mph		
Base free-flow Speed, BFFS	mph		
LOS and Performance Measures		Design (N)	
Operational (LOS)		Design (N)	
v _p = (V or DDHV) / (PHF x N x f _{HV} x f _p)	1544 pc/h/ln	Design LOS	
S	68.6 mph	v _p = (V or DDHV) / (PHF x N x f _{HV} x f _p)	pc/h/ln
D = v _p / S	22.5 pc/mi/ln	S	mph
LOS	C	D = v _p / S	pc/mi/ln
		Required Number of Lanes, N	
Glossary		Factor Location	
N - Number of lanes	S - Speed	E _R - Exhibits 11-10, 11-12	f _{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E _T - Exhibits 11-10, 11-11, 11-13	f _{LC} - Exhibit 11-9
v _p - Flow rate	FFS - Free-flow speed	f _p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v _p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 NB
Agency or Company	AECOM	Junction	Seg 5-On from Exp
Date Performed		Jurisdiction	
Analysis Time Period	PM	Analysis Year	2020 Build 1
Project Description SW 10th Street SIMR			

Inputs

Upstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off $L_{up} =$ ft $V_u =$ veh/h	Freeway Number of Lanes, N 4 Ramp Number of Lanes, N 1 Acceleration Lane Length, L_A 1500 Deceleration Lane Length L_D Freeway Volume, V_F 5780 Ramp Volume, V_R 730 Freeway Free-Flow Speed, S_{FF} 70.0 Ramp Free-Flow Speed, S_{FR} 50.0	Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input type="checkbox"/> On <input type="checkbox"/> No <input checked="" type="checkbox"/> Off $L_{down} =$ 6200 ft $V_D =$ 1300 veh/h
--	--	---

Conversion to pc/h Under Base Conditions

(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f_{HV}	f_p	$v = V/PHF \times f_{HV} \times f_p$
Freeway	5780	0.95	Level	3	0	0.985	1.00	6175
Ramp	730	0.92	Level	2	0	0.990	1.00	801
UpStream								
DownStream	1300	0.92	Level	2	0	0.990	1.00	1427

Merge Areas

Diverge Areas

Estimation of v_{12}

$V_{12} = V_F (P_{FM})$
 (Equation 13-6 or 13-7)
 $L_{EQ} =$
 $P_{FM} =$ 0.118 using Equation (Exhibit 13-6)
 $V_{12} =$ 727 pc/h
 V_3 or V_{av34} 2724 pc/h (Equation 13-14 or 13-17)
 Is V_3 or $V_{av34} > 2,700$ pc/h? Yes No
 Is V_3 or $V_{av34} > 1.5 * V_{12}/2$ Yes No
 If Yes, $V_{12a} =$ 2470 pc/h (Equation 13-16, 13-18, or 13-19)

Estimation of v_{12}

$V_{12} = V_R + (V_F - V_R)P_{FD}$
 (Equation 13-12 or 13-13)
 $L_{EQ} =$
 $P_{FD} =$ using Equation (Exhibit 13-7)
 $V_{12} =$ pc/h
 V_3 or V_{av34} pc/h (Equation 13-14 or 13-17)
 Is V_3 or $V_{av34} > 2,700$ pc/h? Yes No
 Is V_3 or $V_{av34} > 1.5 * V_{12}/2$ Yes No
 If Yes, $V_{12a} =$ pc/h (Equation 13-16, 13-18, or 13-19)

Capacity Checks

	Actual	Capacity	LOS F?		Actual	Capacity	LOS F?
V_{FO}	6976	Exhibit 13-8	No	V_F		Exhibit 13-8	
				$V_{FO} = V_F - V_R$		Exhibit 13-8	
				V_R		Exhibit 13-10	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
V_{R12}	3567	Exhibit 13-8 4600:All	No

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
V_{12}		Exhibit 13-8	

Level of Service Determination (if not F)

$D_R = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A$
 $D_R =$ 25.1 (pc/mi/ln)
 LOS = C (Exhibit 13-2)

Level of Service Determination (if not F)

$D_R = 4.252 + 0.0086 v_{12} - 0.009 L_D$
 $D_R =$ (pc/mi/ln)
 LOS = (Exhibit 13-2)

Speed Determination

$M_S =$ 0.309 (Exhibit 13-11)
 $S_R =$ 61.3 mph (Exhibit 13-11)
 $S_0 =$ 66.0 mph (Exhibit 13-11)
 $S =$ 63.5 mph (Exhibit 13-13)

Speed Determination

$D_s =$ (Exhibit 13-12)
 $S_R =$ mph (Exhibit 13-12)
 $S_0 =$ mph (Exhibit 13-12)
 $S =$ mph (Exhibit 13-13)

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *PM*

Site Information

Highway/Direction of Travel *I-95 NB*
 From/To *Seg 6-Bet Exp On & Off to 10th*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>6510</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *2318* pc/h/ln
 S *55.5* mph
 $D = v_p / S$ *41.8* pc/mi/ln
 LOS *E*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary


N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

Job: SW 10th Street SIMR
Analyst: AECOM

Location: Seg 7: I-95 NB Off-Ramp to SW 10th St EB & WB
Analysis Period: PM Peak Hour
Analysis Year: 2020 Build 1



	PHF =	0.95	
	$V_{fr} =$	6,510	vph
	$V_r =$	1,300	vph
	$V_f =$	5,210	
Upstream Freeway	Tr % =	3%	
Ramp	Tr % =	2%	
Downstream Freeway	Tr % =	3%	
	Freeway $f_{HV} =$	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	0.985
	Ramp $f_{HV} =$	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	0.990099
	flat terrain $E_T =$	1.5	
	RV % =	0	
Driver Population adj.	$f_P =$	1.000	
	$V_{fr} =$	$=V_{fr}/(PHF)(f_{HV})(f_P) =$	6,955 pc/h
	$V_r =$	$=V_r/(PHF)(f_{HV})(f_P) =$	1,382 pc/h
	$V_f =$	$=V_f/(PHF)(f_{HV})(f_P) =$	5,566 pc/h
No. lanes upstream of ramp	$N =$	4	

Average Freeway Density Upstream of Diverge (see Equation 13-26):

$D = 0.0175 (V_{fr}/N) = 30.4 \text{ pc/ln}$

LOS in the Diverge Area (from Density and Exhibit 13-2) =

D

No. Ln	Capacity Check (see Exhibits 13-2, 13-8 and 13.10)	Maximum	Actual	LOS F?
4	Fwy upstream of ramp (assume 70 mph free-flow speed) =	9,600	6,955	No
3	Fwy downstream of ramp (assume 70 mph free-flow speed) =	7,200	5,566	No
1	Capacity on Off-Ramp (assume 45 mph free-flow speed) =	2,100	1,382	No

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *PM*

Site Information

Highway/Direction of Travel *I-95 NB*
 From/To *Seg 8-Bet Off & Off Ramps*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>5210</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1855* pc/h/ln
 S *65.0* mph
 $D = v_p / S$ *28.5* pc/mi/ln
 LOS *D*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 NB
Agency or Company	AECOM	Junction	Seg 9-Off to Hillsboro EB&WB
Date Performed		Jurisdiction	
Analysis Time Period	PM	Analysis Year	2020 Build 1

Project Description SW 10th Street SIMR

Inputs			
Upstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L _{up} = ft V _u = veh/h	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;"> Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L_A Deceleration Lane Length L_D 200 Freeway Volume, V_F 5210 Ramp Volume, V_R 1310 Freeway Free-Flow Speed, S_{FF} 70.0 Ramp Free-Flow Speed, S_{FR} 45.0 </td> <td style="width: 50%; vertical-align: top;"> Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L_{down} = 2800 ft V_D = 1160 veh/h </td> </tr> </table>	Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A Deceleration Lane Length L _D 200 Freeway Volume, V _F 5210 Ramp Volume, V _R 1310 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 45.0	Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L _{down} = 2800 ft V _D = 1160 veh/h
Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A Deceleration Lane Length L _D 200 Freeway Volume, V _F 5210 Ramp Volume, V _R 1310 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 45.0	Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L _{down} = 2800 ft V _D = 1160 veh/h		

Conversion to pc/h Under Base Conditions

(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p
Freeway	5210	0.95	Level	3	0	0.985	1.00	5566
Ramp	1310	0.92	Level	2	0	0.990	1.00	1438
UpStream								
DownStream	1160	0.92	Level	2	0	0.990	1.00	1273

Merge Areas	Diverge Areas
--------------------	----------------------

Estimation of v ₁₂	Estimation of v ₁₂
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)	$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 0.555 using Equation (Exhibit 13-7) V ₁₂ = 3728 pc/h V ₃ or V _{av34} 1838 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)

Capacity Checks

	Actual	Capacity	LOS F?		Actual	Capacity	LOS F?	
V _{FO}		Exhibit 13-8		V _F	5566	Exhibit 13-8	7200	No
				V _{FO} = V _F - V _R	4128	Exhibit 13-8	7200	No
				V _R	1438	Exhibit 13-10	2100	No

Flow Entering Merge Influence Area	Flow Entering Diverge Influence Area
---	---

	Actual	Max Desirable	Violation?		Actual	Max Desirable	Violation?	
V _{R12}		Exhibit 13-8		V ₁₂	3728	Exhibit 13-8	4400:All	No

Level of Service Determination (if not F)	Level of Service Determination (if not F)
--	--

$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)	$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 34.5 (pc/mi/ln) LOS = D (Exhibit 13-2)
---	--

Speed Determination	Speed Determination
----------------------------	----------------------------

M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)	D _s = 0.427 (Exhibit 13-12) S _R = 58.0 mph (Exhibit 13-12) S ₀ = 73.5 mph (Exhibit 13-12) S = 62.4 mph (Exhibit 13-13)
---	--

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *PM*

Site Information

Highway/Direction of Travel *I-95 NB*
 From/To *Seg 10-Bet Off & On Ramps*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	3900	veh/h	Peak-Hour Factor, PHF	0.95
AADT		veh/day	%Trucks and Buses, P _T	3
Peak-Hr Prop. of AADT, K			%RVs, P _R	0
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	1.00	E _R	1.2
E _T	1.5	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	0.985

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N 3
 Total Ramp Density, TRD ramps/mi
 FFS (measured) 70.0 mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS 70.0 mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ 1389 pc/h/ln
 S 69.6 mph
 $D = v_p / S$ 20.0 pc/mi/ln
 LOS C

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume

S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3

f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 NB
Agency or Company	AECOM	Junction	Seg 11-On Ramp 10th St EB & WB
Date Performed		Jurisdiction	
Analysis Time Period	PM	Analysis Year	2020 Build 1
Project Description SW 10th Street SIMR			

Inputs			
Upstream Adj Ramp	Freeway Number of Lanes, N	3	Downstream Adj Ramp
<input checked="" type="checkbox"/> Yes <input type="checkbox"/> On	Ramp Number of Lanes, N	1	<input type="checkbox"/> Yes <input type="checkbox"/> On
<input type="checkbox"/> No <input checked="" type="checkbox"/> Off	Acceleration Lane Length, L _A	1200	<input checked="" type="checkbox"/> No <input type="checkbox"/> Off
L _{up} = 2800 ft	Deceleration Lane Length L _D		L _{down} = ft
V _u = 1310 veh/h	Freeway Volume, V _F	3900	V _D = veh/h
	Ramp Volume, V _R	1160	
	Freeway Free-Flow Speed, S _{FF}	70.0	
	Ramp Free-Flow Speed, S _{FR}	50.0	

Conversion to pc/h Under Base Conditions								
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p
Freeway	3900	0.95	Level	3	0	0.985	1.00	4167
Ramp	1160	0.92	Level	2	0	0.990	1.00	1273
UpStream	1310	0.92	Level	2	0	0.990	1.00	1438
DownStream								

Merge Areas				Diverge Areas			
Estimation of v ₁₂				Estimation of v ₁₂			
$V_{12} = V_F (P_{FM})$ L _{EQ} = 1909.96 (Equation 13-6 or 13-7) P _{FM} = 0.611 using Equation (Exhibit 13-6) V ₁₂ = 2546 pc/h V ₃ or V _{av34} = 1621 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = 2546 pc/h (Equation 13-16, 13-18, or 13-19)				$V_{12} = V_R + (V_F - V_R)P_{FD}$ L _{EQ} = (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)			

Capacity Checks				Capacity Checks			
	Actual	Capacity	LOS F?		Actual	Capacity	LOS F?
V _{FO}	5440	Exhibit 13-8	No	V _F		Exhibit 13-8	
				V _{FO} = V _F - V _R		Exhibit 13-8	
				V _R		Exhibit 13-10	

Flow Entering Merge Influence Area				Flow Entering Diverge Influence Area			
	Actual	Max Desirable	Violation?		Actual	Max Desirable	Violation?
V _{R12}	3819	Exhibit 13-8	4600:All	No	V ₁₂	Exhibit 13-8	

Level of Service Determination (if not F)				Level of Service Determination (if not F)			
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 27.2 (pc/mi/ln) LOS = C (Exhibit 13-2)				$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)			

Speed Determination				Speed Determination			
M _S = 0.379 (Exhibit 13-11) S _R = 59.4 mph (Exhibit 13-11) S ₀ = 66.0 mph (Exhibit 13-11) S = 61.2 mph (Exhibit 13-13)				D _s = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)			

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *PM*

Site Information

Highway/Direction of Travel *I-95 NB*
 From/To *Seg 12-Bet On Ramps*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>5060</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1802* pc/h/ln
 S *65.8* mph
 $D = v_p / S$ *27.4* pc/mi/ln
 LOS *D*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

FREEWAY WEAVING WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 NB
Agency/Company	AECOM	Weaving Segment Location	Seg 13-Bet On & Off to Exp
Date Performed		Analysis Year	2020 Build 1
Analysis Time Period	PM		

Project Description SW 10th Street SIMR

Inputs

Weaving configuration	Two-Sided	Segment type	Freeway
Weaving number of lanes, N	4	Freeway minimum speed, S_{MIN}	15
Weaving segment length, L_S	4600ft	Freeway maximum capacity, C_{IFL}	2400
Freeway free-flow speed, FFS	70 mph	Terrain type	Level

Conversions to pc/h Under Base Conditions

	V (veh/h)	PHF	Truck (%)	RV (%)	E_T	E_R	f_{HV}	f_p	v (pc/h)
V_{FF}	4095	0.95	3	0	1.5	1.2	0.985	1.00	4375
V_{RF}	1145	0.92	2	0	1.5	1.2	0.990	1.00	1257
V_{FR}	965	0.92	2	0	1.5	1.2	0.990	1.00	1059
V_{RR}	125	0.92	2	0	1.5	1.2	0.990	1.00	137
V_{NW}	6691							V =	6828
V_W	137								
VR	0.020								

Configuration Characteristics

Minimum maneuver lanes, N_{WL}	0 lc	Minimum weaving lane changes, LC_{MIN}	411 lc/h
Interchange density, ID	0.7 int/mi	Weaving lane changes, LC_W	1037 lc/h
Minimum RF lane changes, LC_{RF}	0 lc/pc	Non-weaving lane changes, LC_{NW}	3181 lc/h
Minimum FR lane changes, LC_{FR}	0 lc/pc	Total lane changes, LC_{ALL}	4218 lc/h
Minimum RR lane changes, LC_{RR}	3 lc/pc	Non-weaving vehicle index, I_{NW}	2155

Weaving Segment Speed, Density, Level of Service, and Capacity

Weaving segment flow rate, v	6740 veh/h	Weaving intensity factor, W	0.211
Weaving segment capacity, c_w	9064 veh/h	Weaving segment speed, S	58.9 mph
Weaving segment v/c ratio	0.744	Average weaving speed, S_W	60.4 mph
Weaving segment density, D	29.0 pc/mi/ln	Average non-weaving speed, S_{NW}	58.8 mph
Level of Service, LOS	D	Maximum weaving length, L_{MAX}	5913 ft

Notes

- a. Weaving segments longer than the calculated maximum length should be treated as isolated merge and diverge areas using the procedures of Chapter 13, "Freeway Merge and Diverge Segments".
- b. For volumes that exceed the weaving segment capacity, the level of service is "F".

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *AM*

Site Information

Highway/Direction of Travel *I-95 NB*
 From/To *Seg 14-North of Hillsboro*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>5240</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>4</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.980</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *4*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1407* pc/h/ln
 S *69.5* mph
 $D = v_p / S$ *20.2* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *AM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 1-Bet Hillsboro & Palmetto*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>4540</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *4*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1213* pc/h/ln
 S *70.0* mph
 $D = v_p / S$ *17.3* pc/mi/ln
 LOS *B*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

FREEWAY WEAVING WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	195/SB
Agency/Company	AECOM	Weaving Segment Location	Seg 2-Bet On from Exp & Off
Date Performed		Analysis Year	2020 Build 1
Analysis Time Period	AM		

Project Description SW 10th Street SIMR

Inputs

Weaving configuration	Two-Sided	Segment type	Freeway
Weaving number of lanes, N	4	Freeway minimum speed, S_{MIN}	15
Weaving segment length, L_S	5200ft	Freeway maximum capacity, C_{IFL}	2400
Freeway free-flow speed, FFS	70 mph	Terrain type	Level

Conversions to pc/h Under Base Conditions

	V (veh/h)	PHF	Truck (%)	RV (%)	E_T	E_R	f_{HV}	f_p	v (pc/h)
V_{FF}	3440	0.95	3	0	1.5	1.2	0.985	1.00	3675
V_{RF}	1070	0.92	2	0	1.5	1.2	0.990	1.00	1175
V_{FR}	1100	0.92	2	0	1.5	1.2	0.990	1.00	1208
V_{RR}	120	0.92	2	0	1.5	1.2	0.990	1.00	132
V_{NW}	6058							V =	6190
V_W	132								
VR	0.021								

Configuration Characteristics

Minimum maneuver lanes, N_{WL}	0 lc	Minimum weaving lane changes, LC_{MIN}	396 lc/h
Interchange density, ID	0.7 int/mi	Weaving lane changes, LC_W	1064 lc/h
Minimum RF lane changes, LC_{RF}	0 lc/pc	Non-weaving lane changes, LC_{NW}	3040 lc/h
Minimum FR lane changes, LC_{FR}	0 lc/pc	Total lane changes, LC_{ALL}	4104 lc/h
Minimum RR lane changes, LC_{RR}	3 lc/pc	Non-weaving vehicle index, I_{NW}	2205

Weaving Segment Speed, Density, Level of Service, and Capacity

Weaving segment flow rate, v	6111 veh/h	Weaving intensity factor, W	0.188
Weaving segment capacity, c_w	9241 veh/h	Weaving segment speed, S	59.8 mph
Weaving segment v/c ratio	0.661	Average weaving speed, S_W	61.3 mph
Weaving segment density, D	25.9 pc/mi/ln	Average non-weaving speed, S_{NW}	59.7 mph
Level of Service, LOS	C	Maximum weaving length, L_{MAX}	5925 ft

Notes

- a. Weaving segments longer than the calculated maximum length should be treated as isolated merge and diverge areas using the procedures of Chapter 13, "Freeway Merge and Diverge Segments".
- b. For volumes that exceed the weaving segment capacity, the level of service is "F".

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *AM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 3-Bet Off & On Ramp*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>4510</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1606* pc/h/ln
 S *68.1* mph
 $D = v_p / S$ *23.6* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 SB
Agency or Company	AECOM	Junction	Seg 4-Diverge to SW 10th St
Date Performed		Jurisdiction	
Analysis Time Period	AM	Analysis Year	2020 Build 1

Project Description SW 10th Street SIMR

Inputs			
Upstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L _{up} = ft V _u = veh/h	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;"> Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L_A Deceleration Lane Length L_D 200 Freeway Volume, V_F 4510 Ramp Volume, V_R 1180 Freeway Free-Flow Speed, S_{FF} 70.0 Ramp Free-Flow Speed, S_{FR} 45.0 </td> <td style="width: 50%; vertical-align: top;"> Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L_{down} = 1200 ft V_D = 1370 veh/h </td> </tr> </table>	Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A Deceleration Lane Length L _D 200 Freeway Volume, V _F 4510 Ramp Volume, V _R 1180 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 45.0	Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L _{down} = 1200 ft V _D = 1370 veh/h
Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A Deceleration Lane Length L _D 200 Freeway Volume, V _F 4510 Ramp Volume, V _R 1180 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 45.0	Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L _{down} = 1200 ft V _D = 1370 veh/h		

Conversion to pc/h Under Base Conditions								
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p
Freeway	4510	0.95	Level	3	0	0.985	1.00	4819
Ramp	1180	0.92	Level	2	0	0.990	1.00	1295
UpStream								
DownStream	1370	0.92	Level	2	0	0.990	1.00	1504

Merge Areas	Diverge Areas
Estimation of v₁₂ $V_{12} = V_F (P_{FM})$ L _{EQ} = (Equation 13-6 or 13-7) P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)	Estimation of v₁₂ $V_{12} = V_R + (V_F - V_R)P_{FD}$ L _{EQ} = (Equation 13-12 or 13-13) P _{FD} = 0.580 using Equation (Exhibit 13-7) V ₁₂ = 3339 pc/h V ₃ or V _{av34} 1480 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)

Capacity Checks				Capacity Checks			
	Actual	Capacity	LOS F?		Actual	Capacity	LOS F?
V _{FO}		Exhibit 13-8		V _F	4819	Exhibit 13-8	7200 No
				V _{FO} = V _F - V _R	3524	Exhibit 13-8	7200 No
				V _R	1295	Exhibit 13-10	2100 No

Flow Entering Merge Influence Area				Flow Entering Diverge Influence Area			
	Actual	Max Desirable	Violation?		Actual	Max Desirable	Violation?
V _{R12}		Exhibit 13-8		V ₁₂	3339	Exhibit 13-8	4400:All No

Level of Service Determination (if not F)	Level of Service Determination (if not F)
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)	$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 31.2 (pc/mi/ln) LOS = D (Exhibit 13-2)

Speed Determination	Speed Determination
M _S = (Exhibit 13-11)	D _s = 0.415 (Exhibit 13-12)
S _R = mph (Exhibit 13-11)	S _R = 58.4 mph (Exhibit 13-12)
S ₀ = mph (Exhibit 13-11)	S ₀ = 74.9 mph (Exhibit 13-12)
S = mph (Exhibit 13-13)	S = 62.6 mph (Exhibit 13-13)

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Site Information

Analyst		Highway/Direction of Travel	<i>I-95 SB</i>
Agency or Company	<i>AECOM</i>	From/To	<i>Seg 5-Bet Off & On Ramps</i>
Date Performed		Jurisdiction	
Analysis Time Period	<i>AM</i>	Analysis Year	<i>2020 Build 1</i>

Project Description *SW 10th Street SIMR*

Oper.(LOS) Des.(N) Planning Data

Flow Inputs

Volume, V	<i>3300</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Calc Speed Adj and FFS

Lane Width		ft		
Rt-Side Lat. Clearance		ft	f _{LW}	mph
Number of Lanes, N	<i>3</i>		f _{LC}	mph
Total Ramp Density, TRD		ramps/mi	TRD Adjustment	mph
FFS (measured)	<i>70.0</i>	mph	FFS	<i>70.0</i> mph
Base free-flow Speed, BFFS		mph		

LOS and Performance Measures

Design (N)

<u>Operational (LOS)</u>			<u>Design (N)</u>	
$v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$	<i>1175</i>	pc/h/ln	Design LOS	
S	<i>70.0</i>	mph	$v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$	pc/h/ln
D = v _p / S	<i>16.8</i>	pc/mi/ln	S	mph
LOS	<i>B</i>		D = v _p / S	pc/mi/ln
			Required Number of Lanes, N	

Glossary

Factor Location

N - Number of lanes	S - Speed	E _R - Exhibits 11-10, 11-12	f _{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E _T - Exhibits 11-10, 11-11, 11-13	f _{LC} - Exhibit 11-9
v _p - Flow rate	FFS - Free-flow speed	f _p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v _p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 SB
Agency or Company	AECOM	Junction	Seg 6-Merge from Hillsboro E&W
Date Performed		Jurisdiction	
Analysis Time Period	AM	Analysis Year	2020 Build 1
Project Description SW 10th Street SIMR			

Inputs

Upstream Adj Ramp	Freeway Number of Lanes, N	3	Downstream Adj Ramp
<input checked="" type="checkbox"/> Yes <input type="checkbox"/> On	Ramp Number of Lanes, N	1	<input type="checkbox"/> Yes <input type="checkbox"/> On
<input type="checkbox"/> No <input checked="" type="checkbox"/> Off	Acceleration Lane Length, L _A	1100	<input checked="" type="checkbox"/> No <input type="checkbox"/> Off
L _{up} = 1200 ft	Deceleration Lane Length L _D		L _{down} = ft
V _u = 1180 veh/h	Freeway Volume, V _F	3300	V _D = veh/h
	Ramp Volume, V _R	1370	
	Freeway Free-Flow Speed, S _{FF}	70.0	
	Ramp Free-Flow Speed, S _{FR}	50.0	

Conversion to pc/h Under Base Conditions

(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p
Freeway	3300	0.95	Level	3	0	0.985	1.00	3526
Ramp	1370	0.92	Level	2	0	0.990	1.00	1504
UpStream	1180	0.92	Level	2	0	0.990	1.00	1295
DownStream								

Merge Areas	Diverge Areas
-------------	---------------

Estimation of v₁₂

$V_{12} = V_F (P_{FM})$ L _{EQ} = 1777.82 (Equation 13-6 or 13-7) P _{FM} = 0.572 using Equation (Exhibit 13-6) V ₁₂ = 2016 pc/h V ₃ or V _{av34} = 1510 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = 2016 pc/h (Equation 13-16, 13-18, or 13-19)	$V_{12} = V_R + (V_F - V_R)P_{FD}$ L _{EQ} = (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)
--	--

Estimation of v₁₂

Capacity Checks

	Actual	Capacity	LOS F?
V _{FO}	5030	Exhibit 13-8	No

Capacity Checks

	Actual	Capacity	LOS F?
V _F		Exhibit 13-8	
V _{FO} = V _F - V _R		Exhibit 13-8	
V _R		Exhibit 13-10	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
V _{R12}	3520	Exhibit 13-8	4600:All No

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
V ₁₂		Exhibit 13-8	

Level of Service Determination (if not F)

$D_R = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A$ D _R = 25.3 (pc/mi/ln) LOS = C (Exhibit 13-2)	$D_R = 4.252 + 0.0086 v_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)
---	--

Level of Service Determination (if not F)

Speed Determination

M _S = 0.343 (Exhibit 13-11)
S _R = 60.4 mph (Exhibit 13-11)
S ₀ = 66.4 mph (Exhibit 13-11)
S = 62.1 mph (Exhibit 13-13)

Speed Determination

D _s = (Exhibit 13-12)
S _R = mph (Exhibit 13-12)
S ₀ = mph (Exhibit 13-12)
S = mph (Exhibit 13-13)

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *AM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 7-Bet On Ramps*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>4700</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1674* pc/h/ln
 S *67.4* mph
 $D = v_p / S$ *24.8* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume

S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed


Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3

f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

Job: SW 10th Street SIMR
Analyst: AECOM

Location: Seg 8: I-95 Southbound On-Ramp from SW 10th Street EB & WB
Analysis Period: AM Peak Hour
Analysis Year: 2020 Build 1



	PHF =	0.95	
	v_{fr} =	5,920	vph
	v_r =	1,220	vph
	v_f =	4,700	
Upstream Freeway	Tr % =	3%	
Ramp	Tr % =	2%	
Downstream Freeway	Tr % =	3%	
Freeway	f_{HV} =	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	<u>0.985</u>
Ramp	f_{HV} =	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	<u>0.9901</u>
flat terrain	E_T =	1.5	
	RV % =	0	
Driver Population adj.	f_p =	1.000	
	V_{fr} =	$=v_{fr}/(PHF)(f_{HV})(f_p) =$	6,325 pc/h
	V_r =	$=v_r/(PHF)(f_{HV})(f_p) =$	1,297 pc/h
	V_f =	$=v_f/(PHF)(f_{HV})(f_p) =$	5,022 pc/h
No. lanes upstream of ramp	N =	3	

No. Ln	Capacity Check (see Exhibits 25-3 and 25-7):	Maximum	Actual	V/c	LOS F?
4	Fwy downstream of ramp (assume 70 mph free-flow speed) =	9,600	6,325	0.66	No
3	Fwy upstream of ramp (assume 70 mph free-flow speed) =	7,200	5,022	0.70	No
1	Capacity on On-Ramp (assume 45 mph free-flow speed) =	2,100	1,297	0.62	No

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *AM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 9-Bet 10th & Exit to Exp*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>5920</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *4*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1581* pc/h/ln
 S *68.3* mph
 $D = v_p / S$ *23.1* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 SB
Agency or Company	AECOM	Junction	Seg 10- Diverge to Express
Date Performed		Jurisdiction	
Analysis Time Period	AM	Analysis Year	2020 Build 1

Project Description SW 10th Street SIMR

Inputs																		
Upstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L _{up} = 4500 ft V _u = 1220 veh/h	<table style="width: 100%;"> <tr> <td>Freeway Number of Lanes, N</td> <td style="text-align: center;">4</td> </tr> <tr> <td>Ramp Number of Lanes, N</td> <td style="text-align: center;">1</td> </tr> <tr> <td>Acceleration Lane Length, L_A</td> <td></td> </tr> <tr> <td>Deceleration Lane Length L_D</td> <td style="text-align: center;">300</td> </tr> <tr> <td>Freeway Volume, V_F</td> <td style="text-align: center;">5920</td> </tr> <tr> <td>Ramp Volume, V_R</td> <td style="text-align: center;">860</td> </tr> <tr> <td>Freeway Free-Flow Speed, S_{FF}</td> <td style="text-align: center;">70.0</td> </tr> <tr> <td>Ramp Free-Flow Speed, S_{FR}</td> <td style="text-align: center;">45.0</td> </tr> </table>	Freeway Number of Lanes, N	4	Ramp Number of Lanes, N	1	Acceleration Lane Length, L _A		Deceleration Lane Length L _D	300	Freeway Volume, V _F	5920	Ramp Volume, V _R	860	Freeway Free-Flow Speed, S _{FF}	70.0	Ramp Free-Flow Speed, S _{FR}	45.0	Downstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L _{down} = ft V _D = veh/h
Freeway Number of Lanes, N	4																	
Ramp Number of Lanes, N	1																	
Acceleration Lane Length, L _A																		
Deceleration Lane Length L _D	300																	
Freeway Volume, V _F	5920																	
Ramp Volume, V _R	860																	
Freeway Free-Flow Speed, S _{FF}	70.0																	
Ramp Free-Flow Speed, S _{FR}	45.0																	

Conversion to pc/h Under Base Conditions								
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p
Freeway	5920	0.95	Level	3	0	0.985	1.00	6325
Ramp	860	0.92	Level	2	0	0.990	1.00	944
UpStream	1220	0.92	Level	2	0	0.990	1.00	1339
DownStream								

Merge Areas	Diverge Areas
Estimation of v₁₂ $V_{12} = V_F (P_{FM})$ L _{EQ} = (Equation 13-6 or 13-7) P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)	Estimation of v₁₂ $V_{12} = V_R + (V_F - V_R)P_{FD}$ L _{EQ} = (Equation 13-12 or 13-13) P _{FD} = 0.436 using Equation (Exhibit 13-7) V ₁₂ = 3290 pc/h V ₃ or V _{av34} 1517 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)

Capacity Checks				Capacity Checks			
	Actual	Capacity	LOS F?		Actual	Capacity	LOS F?
V _{FO}		Exhibit 13-8		V _F	6325	Exhibit 13-8	9600 No
				V _{FO} = V _F - V _R	5381	Exhibit 13-8	9600 No
				V _R	944	Exhibit 13-10	2100 No

Flow Entering Merge Influence Area				Flow Entering Diverge Influence Area			
	Actual	Max Desirable	Violation?		Actual	Max Desirable	Violation?
V _{R12}		Exhibit 13-8		V ₁₂	3290	Exhibit 13-8	4400:All No

Level of Service Determination (if not F)	Level of Service Determination (if not F)
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)	$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 32.7 (pc/mi/ln) LOS = D (Exhibit 13-2)

Speed Determination	Speed Determination
M _S = (Exhibit 13-11)	D _s = 0.383 (Exhibit 13-12)
S _R = mph (Exhibit 13-11)	S _R = 59.3 mph (Exhibit 13-12)
S ₀ = mph (Exhibit 13-11)	S ₀ = 75.4 mph (Exhibit 13-12)
S = mph (Exhibit 13-13)	S = 65.3 mph (Exhibit 13-13)

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *AM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 11-Bet Off Exp Off Sample*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>5060</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *4*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1352* pc/h/ln
 S *69.7* mph
 $D = v_p / S$ *19.4* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary


N - Number of lanes S - Speed
 V - Hourly volume D - Density
 v_p - Flow rate FFS - Free-flow speed
 LOS - Level of service BFFS - Base free-flow speed
 DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12 f_{LW} - Exhibit 11-8
 E_T - Exhibits 11-10, 11-11, 11-13 f_{LC} - Exhibit 11-9
 f_p - Page 11-18 TRD - Page 11-11
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3

Job: SW 10th Street SIMR
Analyst: AECOM

Location: Seg 12: I-95 SB Off-Ramp to Sample Road EB & WB
Analysis Period: AM Peak Hour
Analysis Year: 2020 Build 1



PHF =	0.95	
v_{fr} =	5,060	vph
v_r =	880	vph
v_f =	4,180	
Upstream Freeway Tr % =	3%	
Ramp Tr % =	2%	
Downstream Freeway Tr % =	3%	
Freeway f_{HV} =	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	<u>0.985</u>
Ramp f_{HV} =	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	<u>0.9901</u>
flat terrain E_T =	1.5	
RV % =	0	
Driver Population adj. f_P =	1.000	
V_{fr} =	$=v_{fr}/(PHF)(f_{HV})(f_P) =$	5,406 pc/h
V_r =	$=v_r/(PHF)(f_{HV})(f_P) =$	936 pc/h
V_f =	$=v_f/(PHF)(f_{HV})(f_P) =$	4,466 pc/h
No. lanes upstream of ramp N =	4	

Average Freeway Density Upstream of Diverge (see Equation 13-26):

$D = 0.0175 (V_{fr}/N) = 23.7 \text{ pc/ln}$

LOS in the Diverge Area (from Density and Exhibit 13-2) =

C

No. Ln	Capacity Check (see Exhibits 13-2, 13-8 and 13.10)	Maximum	Actual	LOS F?
4	Fwy upstream of ramp (assume 70 mph free-flow speed) =	9,600	5,406	No
3	Fwy downstream of ramp (assume 70 mph free-flow speed) =	7,200	4,466	No
1	Capacity on Off-Ramp (assume 45 mph free-flow speed) =	2,100	936	No

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *AM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 13-Bet Off & On Ramps*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>4180</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1489* pc/h/ln
 S *69.0* mph
 $D = v_p / S$ *21.6* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

FREEWAY WEAVING WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 SB
Agency/Company	AECOM	Weaving Segment Location	Seg 14- Bet Sample & Copans
Date Performed		Analysis Year	2020 Build 1
Analysis Time Period	AM		

Project Description SW 10th Street SIMR

Inputs

Weaving configuration	One-Sided	Segment type	Freeway
Weaving number of lanes, N	4	Freeway minimum speed, S_{MIN}	15
Weaving segment length, L_S	2520ft	Freeway maximum capacity, C_{IFL}	2400
Freeway free-flow speed, FFS	70 mph	Terrain type	Level

Conversions to pc/h Under Base Conditions

	V (veh/h)	PHF	Truck (%)	RV (%)	E_T	E_R	f_{HV}	f_p	v (pc/h)
V_{FF}	3575	0.95	3	0	1.5	1.2	0.985	1.00	3820
V_{RF}	1790	0.92	2	0	1.5	1.2	0.990	1.00	1965
V_{FR}	605	0.92	2	0	1.5	1.2	0.990	1.00	664
V_{RR}	0	0.95	0	0	1.5	1.2	1.000	1.00	0
V_{NW}	3820							V =	6449
V_W	2629								
VR	0.408								

Configuration Characteristics

Minimum maneuver lanes, N_{WL}	2 lc	Minimum weaving lane changes, LC_{MIN}	lc/h
Interchange density, ID	0.7 int/mi	Weaving lane changes, LC_W	lc/h
Minimum RF lane changes, LC_{RF}	1 lc/pc	Non-weaving lane changes, LC_{NW}	lc/h
Minimum FR lane changes, LC_{FR}	1 lc/pc	Total lane changes, LC_{ALL}	lc/h
Minimum RR lane changes, LC_{RR}	lc/pc	Non-weaving vehicle index, I_{NW}	792

Weaving Segment Speed, Density, Level of Service, and Capacity

Weaving segment flow rate, v	6367 veh/h	Weaving intensity factor, W	
Weaving segment capacity, c_w	5800 veh/h	Weaving segment speed, S	mph
Weaving segment v/c ratio	1.098	Average weaving speed, S_W	mph
Weaving segment density, D	pc/mi/ln	Average non-weaving speed, S_{NW}	mph
Level of Service, LOS	F	Maximum weaving length, L_{MAX}	6767 ft

Notes

- a. Weaving segments longer than the calculated maximum length should be treated as isolated merge and diverge areas using the procedures of Chapter 13, "Freeway Merge and Diverge Segments".
- b. For volumes that exceed the weaving segment capacity, the level of service is "F".

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *PM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 1-Bet Hillsboro & Palmetto*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>4990</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *4*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1333* pc/h/ln
 S *69.8* mph
 $D = v_p / S$ *19.1* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

FREEWAY WEAVING WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	195/SB
Agency/Company	AECOM	Weaving Segment Location	Seg 2-Bet On from Exp & Off
Date Performed		Analysis Year	2020 Build 1
Analysis Time Period	PM		

Project Description SW 10th Street SIMR

Inputs

Weaving configuration	Two-Sided	Segment type	Freeway
Weaving number of lanes, N	4	Freeway minimum speed, S_{MIN}	15
Weaving segment length, L_S	5200ft	Freeway maximum capacity, C_{IFL}	2400
Freeway free-flow speed, FFS	70 mph	Terrain type	Level

Conversions to pc/h Under Base Conditions

	V (veh/h)	PHF	Truck (%)	RV (%)	E_T	E_R	f_{HV}	f_p	v (pc/h)
V_{FF}	4055	0.95	3	0	1.5	1.2	0.985	1.00	4332
V_{RF}	1105	0.92	2	0	1.5	1.2	0.990	1.00	1213
V_{FR}	935	0.92	2	0	1.5	1.2	0.990	1.00	1026
V_{RR}	125	0.92	2	0	1.5	1.2	0.990	1.00	137
V_{NW}	6571							V =	6708
V_W	137								
VR	0.020								

Configuration Characteristics

Minimum maneuver lanes, N_{WL}	0 lc	Minimum weaving lane changes, LC_{MIN}	411 lc/h
Interchange density, ID	0.7 int/mi	Weaving lane changes, LC_W	1079 lc/h
Minimum RF lane changes, LC_{RF}	0 lc/pc	Non-weaving lane changes, LC_{NW}	3154 lc/h
Minimum FR lane changes, LC_{FR}	0 lc/pc	Total lane changes, LC_{ALL}	4233 lc/h
Minimum RR lane changes, LC_{RR}	3 lc/pc	Non-weaving vehicle index, I_{NW}	2392

Weaving Segment Speed, Density, Level of Service, and Capacity

Weaving segment flow rate, v	6622 veh/h	Weaving intensity factor, W	0.192
Weaving segment capacity, c_w	9241 veh/h	Weaving segment speed, S	59.0 mph
Weaving segment v/c ratio	0.717	Average weaving speed, S_W	61.1 mph
Weaving segment density, D	28.4 pc/mi/ln	Average non-weaving speed, S_{NW}	59.0 mph
Level of Service, LOS	D	Maximum weaving length, L_{MAX}	5916 ft

Notes

- a. Weaving segments longer than the calculated maximum length should be treated as isolated merge and diverge areas using the procedures of Chapter 13, "Freeway Merge and Diverge Segments".
- b. For volumes that exceed the weaving segment capacity, the level of service is "F".

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *PM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 3-Bet Off & On Ramp*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>5160</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1838* pc/h/ln
 S *65.3* mph
 $D = v_p / S$ *28.2* pc/mi/ln
 LOS *D*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *PM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 5-Bet Off & On Ramps*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>3910</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1393* pc/h/ln
 S *69.6* mph
 $D = v_p / S$ *20.0* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 SB
Agency or Company	AECOM	Junction	Seg 6-Merge from Hillsboro E&W
Date Performed		Jurisdiction	
Analysis Time Period	PM	Analysis Year	2020 Build 1
Project Description SW 10th Street SIMR			

Inputs

Upstream Adj Ramp	Freeway Number of Lanes, N	3	Downstream Adj Ramp
<input checked="" type="checkbox"/> Yes <input type="checkbox"/> On	Ramp Number of Lanes, N	1	<input type="checkbox"/> Yes <input type="checkbox"/> On
<input type="checkbox"/> No <input checked="" type="checkbox"/> Off	Acceleration Lane Length, L _A	1100	<input checked="" type="checkbox"/> No <input type="checkbox"/> Off
L _{up} = 1200 ft	Deceleration Lane Length L _D		L _{down} = ft
V _u = 1250 veh/h	Freeway Volume, V _F	3910	V _D = veh/h
	Ramp Volume, V _R	1500	
	Freeway Free-Flow Speed, S _{FF}	70.0	
	Ramp Free-Flow Speed, S _{FR}	50.0	

Conversion to pc/h Under Base Conditions

(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p
Freeway	3910	0.95	Level	3	0	0.985	1.00	4178
Ramp	1500	0.92	Level	2	0	0.990	1.00	1647
UpStream	1250	0.92	Level	2	0	0.990	1.00	1372
DownStream								

Merge Areas

Diverge Areas

Estimation of v₁₂

V ₁₂ = V _F (P _{FM})
L _{EQ} = 1947.95 (Equation 13-6 or 13-7)
P _{FM} = 0.561 using Equation (Exhibit 13-6)
V ₁₂ = 2344 pc/h
V ₃ or V _{av34} = 1834 pc/h (Equation 13-14 or 13-17)
Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
If Yes, V _{12a} = 2387 pc/h (Equation 13-16, 13-18, or 13-19)

Estimation of v₁₂

V ₁₂ = V _R + (V _F - V _R)P _{FD}
L _{EQ} = (Equation 13-12 or 13-13)
P _{FD} = using Equation (Exhibit 13-7)
V ₁₂ = pc/h
V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17)
Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No
Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No
If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)

Capacity Checks

	Actual	Capacity	LOS F?
V _{FO}	5825	Exhibit 13-8	No

Capacity Checks

	Actual	Capacity	LOS F?
V _F		Exhibit 13-8	
V _{FO} = V _F - V _R		Exhibit 13-8	
V _R		Exhibit 13-10	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
V _{R12}	4034	Exhibit 13-8	4600:All
			No

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
V ₁₂		Exhibit 13-8	

Level of Service Determination (if not F)

D _R = 5.475 + 0.00734 v _R + 0.0078 V ₁₂ - 0.00627 L _A
D _R = 29.3 (pc/mi/ln)
LOS = D (Exhibit 13-2)

Level of Service Determination (if not F)

D _R = 4.252 + 0.0086 V ₁₂ - 0.009 L _D
D _R = (pc/mi/ln)
LOS = (Exhibit 13-2)

Speed Determination

M _S = 0.431 (Exhibit 13-11)
S _R = 57.9 mph (Exhibit 13-11)
S ₀ = 65.4 mph (Exhibit 13-11)
S = 60.0 mph (Exhibit 13-13)

Speed Determination

D _s = (Exhibit 13-12)
S _R = mph (Exhibit 13-12)
S ₀ = mph (Exhibit 13-12)
S = mph (Exhibit 13-13)

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *PM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 7-Bet On Ramps*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>5410</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1927* pc/h/ln
 S *63.9* mph
 $D = v_p / S$ *30.2* pc/mi/ln
 LOS *D*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary


N - Number of lanes S - Speed
 V - Hourly volume D - Density
 v_p - Flow rate FFS - Free-flow speed
 LOS - Level of service BFFS - Base free-flow speed
 DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12 f_{LW} - Exhibit 11-8
 E_T - Exhibits 11-10, 11-11, 11-13 f_{LC} - Exhibit 11-9
 f_p - Page 11-18 TRD - Page 11-11
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3

Job: SW 10th Street SIMR
Analyst: AECOM

Location: Seg 8: I-95 Southbound On-Ramp from SW 10th Street EB & WB
Analysis Period: PM Peak Hour
Analysis Year: 2020 Build 1



	PHF =	0.95	
	v_{fr} =	6,630	vph
	v_r =	1,220	vph
	v_f =	5,410	
Upstream Freeway	Tr % =	3%	
Ramp	Tr % =	2%	
Downstream Freeway	Tr % =	3%	
Freeway	f_{HV} =	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	0.985
Ramp	f_{HV} =	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	0.9901
flat terrain	E_T =	1.5	
	RV % =	0	
Driver Population adj.	f_P =	1.000	
	V_{fr} =	$=v_{fr}/(PHF)(f_{HV})(f_P) =$	7,084 pc/h
	V_r =	$=v_r/(PHF)(f_{HV})(f_P) =$	1,297 pc/h
	V_f =	$=v_f/(PHF)(f_{HV})(f_P) =$	5,780 pc/h
No. lanes upstream of ramp	N =	3	

No. Ln	Capacity Check (see Exhibits 25-3 and 25-7):	Maximum	Actual	V/c	LOS F?
4	Fwy downstream of ramp (assume 70 mph free-flow speed) =	9,600	7,084	0.74	No
3	Fwy upstream of ramp (assume 70 mph free-flow speed) =	7,200	5,780	0.80	No
1	Capacity on On-Ramp (assume 45 mph free-flow speed) =	2,100	1,297	0.62	No

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *PM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 9-Bet 10th & Exit to Exp*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	6630	veh/h	Peak-Hour Factor, PHF	0.95
AADT		veh/day	%Trucks and Buses, P _T	3
Peak-Hr Prop. of AADT, K			%RVs, P _R	0
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	1.00	E _R	1.2
E _T	1.5	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	0.985

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *4*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1771* pc/h/ln
 S *66.2* mph
 $D = v_p / S$ *26.7* pc/mi/ln
 LOS *D*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume

S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3

f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 SB
Agency or Company	AECOM	Junction	Seg 10- Diverge to Express
Date Performed		Jurisdiction	
Analysis Time Period	PM	Analysis Year	2020 Build 1

Project Description SW 10th Street SIMR

Inputs																		
Upstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L _{up} = 4500 ft V _u = 1220 veh/h	<table style="width: 100%;"> <tr> <td>Freeway Number of Lanes, N</td> <td style="text-align: center;">4</td> </tr> <tr> <td>Ramp Number of Lanes, N</td> <td style="text-align: center;">1</td> </tr> <tr> <td>Acceleration Lane Length, L_A</td> <td></td> </tr> <tr> <td>Deceleration Lane Length L_D</td> <td style="text-align: center;">300</td> </tr> <tr> <td>Freeway Volume, V_F</td> <td style="text-align: center;">6630</td> </tr> <tr> <td>Ramp Volume, V_R</td> <td style="text-align: center;">720</td> </tr> <tr> <td>Freeway Free-Flow Speed, S_{FF}</td> <td style="text-align: center;">70.0</td> </tr> <tr> <td>Ramp Free-Flow Speed, S_{FR}</td> <td style="text-align: center;">45.0</td> </tr> </table>	Freeway Number of Lanes, N	4	Ramp Number of Lanes, N	1	Acceleration Lane Length, L _A		Deceleration Lane Length L _D	300	Freeway Volume, V _F	6630	Ramp Volume, V _R	720	Freeway Free-Flow Speed, S _{FF}	70.0	Ramp Free-Flow Speed, S _{FR}	45.0	Downstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L _{down} = ft V _D = veh/h
Freeway Number of Lanes, N	4																	
Ramp Number of Lanes, N	1																	
Acceleration Lane Length, L _A																		
Deceleration Lane Length L _D	300																	
Freeway Volume, V _F	6630																	
Ramp Volume, V _R	720																	
Freeway Free-Flow Speed, S _{FF}	70.0																	
Ramp Free-Flow Speed, S _{FR}	45.0																	

Conversion to pc/h Under Base Conditions								
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p
Freeway	6630	0.95	Level	3	0	0.985	1.00	7084
Ramp	720	0.92	Level	2	0	0.990	1.00	790
UpStream	1220	0.92	Level	2	0	0.990	1.00	1339
DownStream								

Merge Areas	Diverge Areas
Estimation of v₁₂ $V_{12} = V_F (P_{FM})$ L _{EQ} = (Equation 13-6 or 13-7) P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)	Estimation of v₁₂ $V_{12} = V_R + (V_F - V_R)P_{FD}$ L _{EQ} = (Equation 13-12 or 13-13) P _{FD} = 0.436 using Equation (Exhibit 13-7) V ₁₂ = 3534 pc/h V ₃ or V _{av34} 1775 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)

Capacity Checks				Capacity Checks				
	Actual	Capacity	LOS F?		Actual	Capacity	LOS F?	
V _{FO}		Exhibit 13-8		V _F	7084	Exhibit 13-8	9600	No
				V _{FO} = V _F - V _R	6294	Exhibit 13-8	9600	No
				V _R	790	Exhibit 13-10	2100	No

Flow Entering Merge Influence Area				Flow Entering Diverge Influence Area				
	Actual	Max Desirable	Violation?		Actual	Max Desirable	Violation?	
V _{R12}		Exhibit 13-8		V ₁₂	3534	Exhibit 13-8	4400:All	No

Level of Service Determination (if not F)	Level of Service Determination (if not F)
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)	$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 35.0 (pc/mi/ln) LOS = D (Exhibit 13-2)

Speed Determination	Speed Determination
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)	D _s = 0.369 (Exhibit 13-12) S _R = 59.7 mph (Exhibit 13-12) S ₀ = 74.5 mph (Exhibit 13-12) S = 65.5 mph (Exhibit 13-13)

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *PM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 11-Bet Off Exp Off Sample*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>5910</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *4*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1579* pc/h/ln
 S *68.3* mph
 $D = v_p / S$ *23.1* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary


N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

Job: SW 10th Street SIMR
Analyst: AECOM

Location: Seg 12: I-95 SB Off-Ramp to Sample Road EB & WB
Analysis Period: PM Peak Hour
Analysis Year: 2020 Build 1



PHF =	0.95	
$v_{fr} =$	5,910	vph
$v_r =$	1,110	vph
$v_f =$	4,800	
Upstream Freeway Tr % =	3%	
Ramp Tr % =	2%	
Downstream Freeway Tr % =	3%	
Freeway $f_{HV} =$	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	<u>0.985</u>
Ramp $f_{HV} =$	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	<u>0.9901</u>
flat terrain $E_T =$	1.5	
RV % =	0	
Driver Population adj. $f_P =$	1.000	
$V_{fr} = v_{fr}/(PHF)(f_{HV})(f_P) =$		6,314 pc/h
$V_r = v_r/(PHF)(f_{HV})(f_P) =$		1,180 pc/h
$V_f = v_f/(PHF)(f_{HV})(f_P) =$		5,128 pc/h
No. lanes upstream of ramp $N =$	4	

Average Freeway Density Upstream of Diverge (see Equation 13-26):

$D = 0.0175 (V_{fr}/N) = 27.6 \text{ pc/ln}$

LOS in the Diverge Area (from Density and Exhibit 13-2) =

C

No. Ln	Capacity Check (see Exhibits 13-2, 13-8 and 13.10)	Maximum	Actual	LOS F?
4	Fwy upstream of ramp (assume 70 mph free-flow speed) =	9,600	6,314	No
3	Fwy downstream of ramp (assume 70 mph free-flow speed) =	7,200	5,128	No
1	Capacity on Off-Ramp (assume 45 mph free-flow speed) =	2,100	1,180	No

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *PM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 13-Bet Off & On Ramps*
 Jurisdiction
 Analysis Year *2020 Build 1*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>4800</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1709* pc/h/ln
 S *67.0* mph
 $D = v_p / S$ *25.5* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume

S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3

f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

FREEWAY WEAVING WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 SB
Agency/Company	AECOM	Weaving Segment Location	Seg 14- Bet Sample & Copans
Date Performed		Analysis Year	2020 Build 1
Analysis Time Period	PM		

Project Description SW 10th Street SIMR

Inputs

Weaving configuration	One-Sided	Segment type	Freeway
Weaving number of lanes, N	4	Freeway minimum speed, S_{MIN}	15
Weaving segment length, L_S	2520ft	Freeway maximum capacity, C_{IFL}	2400
Freeway free-flow speed, FFS	70 mph	Terrain type	Level

Conversions to pc/h Under Base Conditions

	V (veh/h)	PHF	Truck (%)	RV (%)	E_T	E_R	f_{HV}	f_p	v (pc/h)
V_{FF}	4170	0.95	3	0	1.5	1.2	0.985	1.00	4455
V_{RF}	1420	0.92	2	0	1.5	1.2	0.990	1.00	1559
V_{FR}	630	0.92	2	0	1.5	1.2	0.990	1.00	692
V_{RR}	0	0.95	0	0	1.5	1.2	1.000	1.00	0
V_{NW}	4455							V =	6706
V_W	2251								
VR	0.336								

Configuration Characteristics

Minimum maneuver lanes, N_{WL}	2 lc	Minimum weaving lane changes, LC_{MIN}	2251 lc/h
Interchange density, ID	0.7 int/mi	Weaving lane changes, LC_W	2700 lc/h
Minimum RF lane changes, LC_{RF}	1 lc/pc	Non-weaving lane changes, LC_{NW}	1513 lc/h
Minimum FR lane changes, LC_{FR}	1 lc/pc	Total lane changes, LC_{ALL}	4213 lc/h
Minimum RR lane changes, LC_{RR}	lc/pc	Non-weaving vehicle index, I_{NW}	786

Weaving Segment Speed, Density, Level of Service, and Capacity

Weaving segment flow rate, v	6618 veh/h	Weaving intensity factor, W	0.339
Weaving segment capacity, c_w	7044 veh/h	Weaving segment speed, S	48.8 mph
Weaving segment v/c ratio	0.939	Average weaving speed, S_W	56.1 mph
Weaving segment density, D	34.4 pc/mi/ln	Average non-weaving speed, S_{NW}	45.7 mph
Level of Service, LOS	D	Maximum weaving length, L_{MAX}	5970 ft

Notes

- a. Weaving segments longer than the calculated maximum length should be treated as isolated merge and diverge areas using the procedures of Chapter 13, "Freeway Merge and Diverge Segments".
- b. For volumes that exceed the weaving segment capacity, the level of service is "F".