

FREEWAY WEAVING WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 NB
Agency/Company	AECOM	Weaving Segment Location	Seg 1-Bet Copans & Sample
Date Performed		Analysis Year	2020 Build 2
Analysis Time Period	AM		

Project Description SW 10th Street SIMR

Inputs

Weaving configuration	One-Sided	Segment type	Freeway
Weaving number of lanes, N	4	Freeway minimum speed, S_{MIN}	15
Weaving segment length, L_S	2380ft	Freeway maximum capacity, C_{IFL}	2400
Freeway free-flow speed, FFS	70 mph	Terrain type	Level

Conversions to pc/h Under Base Conditions

	V (veh/h)	PHF	Truck (%)	RV (%)	E_T	E_R	f_{HV}	f_p	v (pc/h)
V_{FF}	4565	0.95	3	0	1.5	1.2	0.985	1.00	4877
V_{RF}	355	0.92	2	0	1.5	1.2	0.990	1.00	390
V_{FR}	800	0.92	2	0	1.5	1.2	0.990	1.00	878
V_{RR}	0	0.95	0	0	1.5	1.2	1.000	1.00	0
V_{NW}	4877							V =	6145
V_W	1268								
VR	0.206								

Configuration Characteristics

Minimum maneuver lanes, N_{WL}	2 lc	Minimum weaving lane changes, LC_{MIN}	1268 lc/h
Interchange density, ID	0.7 int/mi	Weaving lane changes, LC_W	1703 lc/h
Minimum RF lane changes, LC_{RF}	1 lc/pc	Non-weaving lane changes, LC_{NW}	1524 lc/h
Minimum FR lane changes, LC_{FR}	1 lc/pc	Total lane changes, LC_{ALL}	3227 lc/h
Minimum RR lane changes, LC_{RR}	lc/pc	Non-weaving vehicle index, I_{NW}	813

Weaving Segment Speed, Density, Level of Service, and Capacity

Weaving segment flow rate, v	6061 veh/h	Weaving intensity factor, W	0.287
Weaving segment capacity, c_w	8788 veh/h	Weaving segment speed, S	54.3 mph
Weaving segment v/c ratio	0.690	Average weaving speed, S_W	57.7 mph
Weaving segment density, D	28.3 pc/mi/ln	Average non-weaving speed, S_{NW}	53.5 mph
Level of Service, LOS	D	Maximum weaving length, L_{MAX}	4601 ft

Notes


- a. Weaving segments longer than the calculated maximum length should be treated as isolated merge and diverge areas using the procedures of Chapter 13, "Freeway Merge and Diverge Segments".
- b. For volumes that exceed the weaving segment capacity, the level of service is "F".

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst		Highway/Direction of Travel	<i>I-95 NB</i>
Agency or Company	<i>AECOM</i>	From/To	<i>Seg 2-Bet Off & On from Sample</i>
Date Performed		Jurisdiction	
Analysis Time Period	<i>AM</i>	Analysis Year	<i>2020 Build 2</i>
Project Description <i>SW 10th Street SIMR</i>			
<input checked="" type="checkbox"/> Oper.(LOS)		<input type="checkbox"/> Des.(N)	
		<input type="checkbox"/> Planning Data	
Flow Inputs			
Volume, V	<i>4920</i>	veh/h	Peak-Hour Factor, PHF
AADT		veh/day	%Trucks and Buses, P _T
Peak-Hr Prop. of AADT, K			%RVs, P _R
Peak-Hr Direction Prop, D			General Terrain:
DDHV = AADT x K x D		veh/h	Grade % Length
			Up/Down %
			<i>0.95</i>
			<i>3</i>
			<i>0</i>
			<i>Level</i>
			<i>mi</i>
Calculate Flow Adjustments			
f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>
Speed Inputs		Calc Speed Adj and FFS	
Lane Width		ft	
Rt-Side Lat. Clearance		ft	f _{LV}
Number of Lanes, N	<i>3</i>		f _{LC}
Total Ramp Density, TRD		ramps/mi	TRD Adjustment
FFS (measured)	<i>70.0</i>	mph	FFS
Base free-flow Speed, BFFS		mph	<i>70.0</i>
			mph
LOS and Performance Measures		Design (N)	
Operational (LOS)		Design (N)	
v _p = (V or DDHV) / (PHF x N x f _{HV} x f _p)	<i>1752</i>	pc/h/ln	Design LOS
S	<i>66.5</i>	mph	v _p = (V or DDHV) / (PHF x N x f _{HV} x f _p)
D = v _p / S	<i>26.4</i>	pc/mi/ln	S
LOS	<i>D</i>		D = v _p / S
			Required Number of Lanes, N
Glossary		Factor Location	
N - Number of lanes	S - Speed	E _R - Exhibits 11-10, 11-12	f _{LV} - Exhibit 11-8
V - Hourly volume	D - Density	E _T - Exhibits 11-10, 11-11, 11-13	f _{LC} - Exhibit 11-9
v _p - Flow rate	FFS - Free-flow speed	f _p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v _p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Job: SW 10th Street SIMR
Analyst: AECOM

Location: Seg 3: I-95 Northbound On-Ramp from WB Sample Road
Analysis Period: AM Peak Hour
Analysis Year: 2020 Build 2



	PHF =	0.95	
	$V_{fr} =$	6,140	vph
	$V_r =$	1,220	vph
	$V_f =$	4,920	
Upstream Freeway	Tr % =	3%	
Ramp	Tr % =	2%	
Downstream Freeway	Tr % =	3%	
Freeway	$f_{HV} = 1/(1+P_T(E_T-1)+P_R(E_R-1)) =$		0.985
Ramp	$f_{HV} = 1/(1+P_T(E_T-1)+P_R(E_R-1)) =$		0.9901
flat terrain	$E_T =$	1.5	
	RV % =	0	
Driver Population adj.	$f_P =$	1.000	
	$V_{fr} = v_{fr}/(PHF)(f_{HV})(f_P) =$	6,560	pc/h
	$V_r = v_r/(PHF)(f_{HV})(f_P) =$	1,297	pc/h
	$V_f = v_f/(PHF)(f_{HV})(f_P) =$	5,257	pc/h
No. lanes upstream of ramp	$N =$	3	

<u>No. Ln</u>	<u>Capacity Check (see Exhibits 25-3 and 25-7):</u>	Maximum	Actual	V/c	LOS F?
4	Fwy downstream of ramp (assume 70 mph free-flow speed) =	9,600	6,560	0.68	No
3	Fwy upstream of ramp (assume 70 mph free-flow speed) =	7,200	5,257	0.73	No
1	Capacity on On-Ramp (assume 45 mph free-flow speed) =	2,100	1,297	0.62	No

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 NB
Agency or Company	AECOM	Junction	Seg 4-On from Exp
Date Performed		Jurisdiction	
Analysis Time Period	AM	Analysis Year	2020 Build 2
Project Description SW 10th Street SIMR			

Inputs

Upstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off $L_{up} =$ ft $V_u =$ veh/h	Freeway Number of Lanes, N 4 Ramp Number of Lanes, N 1 Acceleration Lane Length, L_A 1500 Deceleration Lane Length L_D Freeway Volume, V_F 6140 Ramp Volume, V_R 690 Freeway Free-Flow Speed, S_{FF} 70.0 Ramp Free-Flow Speed, S_{FR} 50.0	Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input type="checkbox"/> On <input type="checkbox"/> No <input checked="" type="checkbox"/> Off $L_{down} =$ 2950 ft $V_D =$ 140 veh/h
--	--	--

Conversion to pc/h Under Base Conditions

(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f_{HV}	f_p	$v = V/PHF \times f_{HV} \times f_p$
Freeway	6140	0.95	Level	3	0	0.985	1.00	6560
Ramp	690	0.92	Level	2	0	0.990	1.00	757
UpStream								
DownStream	140	0.92	Level	2	0	0.990	1.00	154

Merge Areas

Diverge Areas

Estimation of v_{12}

$V_{12} = V_F (P_{FM})$
 (Equation 13-6 or 13-7)
 $L_{EQ} =$
 $P_{FM} =$ 0.123 using Equation (Exhibit 13-6)
 $V_{12} =$ 808 pc/h
 V_3 or V_{av34} 2876 pc/h (Equation 13-14 or 13-17)
 Is V_3 or $V_{av34} > 2,700$ pc/h? Yes No
 Is V_3 or $V_{av34} > 1.5 * V_{12}/2$ Yes No
 If Yes, $V_{12a} =$ 2624 pc/h (Equation 13-16, 13-18, or 13-19)

Estimation of v_{12}

$V_{12} = V_R + (V_F - V_R)P_{FD}$
 (Equation 13-12 or 13-13)
 $L_{EQ} =$
 $P_{FD} =$ using Equation (Exhibit 13-7)
 $V_{12} =$ pc/h
 V_3 or V_{av34} pc/h (Equation 13-14 or 13-17)
 Is V_3 or $V_{av34} > 2,700$ pc/h? Yes No
 Is V_3 or $V_{av34} > 1.5 * V_{12}/2$ Yes No
 If Yes, $V_{12a} =$ pc/h (Equation 13-16, 13-18, or 13-19)

Capacity Checks

	Actual	Capacity	LOS F?		Actual	Capacity	LOS F?
V_{FO}	7317	Exhibit 13-8	No	V_F		Exhibit 13-8	
				$V_{FO} = V_F - V_R$		Exhibit 13-8	
				V_R		Exhibit 13-10	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
V_{R12}	3695	Exhibit 13-8 4600:All	No

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
V_{12}		Exhibit 13-8	

Level of Service Determination (if not F)

$D_R = 5.475 + 0.00734 V_R + 0.0078 V_{12} - 0.00627 L_A$
 $D_R =$ 26.2 (pc/mi/ln)
 LOS = C (Exhibit 13-2)

Level of Service Determination (if not F)

$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$
 $D_R =$ (pc/mi/ln)
 LOS = (Exhibit 13-2)

Speed Determination

$M_S =$ 0.328 (Exhibit 13-11)
 $S_R =$ 60.8 mph (Exhibit 13-11)
 $S_0 =$ 65.7 mph (Exhibit 13-11)
 $S =$ 63.0 mph (Exhibit 13-13)

Speed Determination

$D_s =$ (Exhibit 13-12)
 $S_R =$ mph (Exhibit 13-12)
 $S_0 =$ mph (Exhibit 13-12)
 $S =$ mph (Exhibit 13-13)

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 NB
Agency or Company	AECOM	Junction	Seg 5-Off to Exp from GPL
Date Performed		Jurisdiction	
Analysis Time Period	AM	Analysis Year	2020 Build 2

Project Description SW 10th Street SIMR

Inputs			
Upstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L _{up} = 2950 ft V _u = 690 veh/h	<table style="width: 100%;"> <tr> <td style="width: 50%;"> Freeway Number of Lanes, N 4 Ramp Number of Lanes, N 1 Acceleration Lane Length, L_A Deceleration Lane Length L_D 200 Freeway Volume, V_F 6830 Ramp Volume, V_R 140 Freeway Free-Flow Speed, S_{FF} 70.0 Ramp Free-Flow Speed, S_{FR} 45.0 </td> <td style="width: 50%;"> Downstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L_{down} = ft V_D = veh/h </td> </tr> </table>	Freeway Number of Lanes, N 4 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A Deceleration Lane Length L _D 200 Freeway Volume, V _F 6830 Ramp Volume, V _R 140 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 45.0	Downstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L _{down} = ft V _D = veh/h
Freeway Number of Lanes, N 4 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A Deceleration Lane Length L _D 200 Freeway Volume, V _F 6830 Ramp Volume, V _R 140 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 45.0	Downstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L _{down} = ft V _D = veh/h		

Conversion to pc/h Under Base Conditions								
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p
Freeway	6830	0.95	Level	3	0	0.985	1.00	7297
Ramp	140	0.92	Level	2	0	0.990	1.00	154
UpStream	690	0.92	Level	2	0	0.990	1.00	757
DownStream								

Merge Areas	Diverge Areas
Estimation of v₁₂ $V_{12} = V_F (P_{FM})$ L _{EQ} = (Equation 13-6 or 13-7) P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)	Estimation of v₁₂ $V_{12} = V_R + (V_F - V_R)P_{FD}$ L _{EQ} = (Equation 13-12 or 13-13) P _{FD} = 0.436 using Equation (Exhibit 13-7) V ₁₂ = 3268 pc/h V ₃ or V _{av34} 2014 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)

Capacity Checks				Capacity Checks			
	Actual	Capacity	LOS F?		Actual	Capacity	LOS F?
V _{FO}		Exhibit 13-8		V _F	7297	Exhibit 13-8	9600 No
				V _{FO} = V _F - V _R	7143	Exhibit 13-8	9600 No
				V _R	154	Exhibit 13-10	2100 No

Flow Entering Merge Influence Area				Flow Entering Diverge Influence Area			
	Actual	Max Desirable	Violation?		Actual	Max Desirable	Violation?
V _{R12}		Exhibit 13-8		V ₁₂	3268	Exhibit 13-8	4400:All No

Level of Service Determination (if not F)	Level of Service Determination (if not F)
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)	$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 30.6 (pc/mi/ln) LOS = D (Exhibit 13-2)

Speed Determination	Speed Determination
M _S = (Exhibit 13-11)	D _s = 0.312 (Exhibit 13-12)
S _R = mph (Exhibit 13-11)	S _R = 61.3 mph (Exhibit 13-12)
S ₀ = mph (Exhibit 13-11)	S ₀ = 72.8 mph (Exhibit 13-12)
S = mph (Exhibit 13-13)	S = 67.2 mph (Exhibit 13-13)

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *AM*

Site Information

Highway/Direction of Travel *I-95 NB*
 From/To *Seg 6-South of Off to 10th*
 Jurisdiction
 Analysis Year *2020 Build 2*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>6690</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *4*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1787* pc/h/ln
 S *66.0* mph
 $D = v_p / S$ *27.1* pc/mi/ln
 LOS *D*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary


N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

Job: SW 10th Street SIMR
Analyst: AECOM

Location: Seg 7: I-95 NB Off-Ramp to SW 10th St EB & WB
Analysis Period: AM Peak Hour
Analysis Year: 2020 Build 2



PHF =	0.95	
$V_{fr} =$	6,690	vph
$V_r =$	1,020	vph
$V_f =$	5,670	
Upstream Freeway Tr % =	3%	
Ramp Tr % =	2%	
Downstream Freeway Tr % =	3%	
Freeway $f_{HV} =$	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	0.985
Ramp $f_{HV} =$	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	0.990099
flat terrain $E_T =$	1.5	
RV % =	0	
Driver Population adj. $f_p =$	1.000	
$V_{fr} =$	$=V_{fr}/(PHF)(f_{HV})(f_p) =$	7,148 pc/h
$V_r =$	$=V_r/(PHF)(f_{HV})(f_p) =$	1,084 pc/h
$V_f =$	$=V_f/(PHF)(f_{HV})(f_p) =$	6,058 pc/h
No. lanes upstream of ramp $N =$	4	

Average Freeway Density Upstream of Diverge (see Equation 13-26):

$D = 0.0175 (V_{fr}/N) = 31.3 \text{ pc/ln}$

LOS in the Diverge Area (from Density and Exhibit 13-2) =

D

No. Ln	Capacity Check (see Exhibits 13-2, 13-8 and 13.10)	Maximum	Actual	LOS F?
4	Fwy upstream of ramp (assume 70 mph free-flow speed) =	9,600	7,148	No
3	Fwy downstream of ramp (assume 70 mph free-flow speed) =	7,200	6,058	No
1	Capacity on Off-Ramp (assume 45 mph free-flow speed) =	2,100	1,084	No

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *AM*

Site Information

Highway/Direction of Travel *I-95 NB*
 From/To *Seg 8-Bet Off & Off Ramps*
 Jurisdiction
 Analysis Year *2020 Build 2*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>5670</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ 2019 pc/h/ln
 S *62.2* mph
 D = v_p / S *32.4* pc/mi/ln
 LOS *D*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 D = v_p / S pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes S - Speed
 V - Hourly volume D - Density
 v_p - Flow rate FFS - Free-flow speed
 LOS - Level of service BFFS - Base free-flow speed
 DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12 f_{LW} - Exhibit 11-8
 E_T - Exhibits 11-10, 11-11, 11-13 f_{LC} - Exhibit 11-9
 f_p - Page 11-18 TRD - Page 11-11
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 NB
Agency or Company	AECOM	Junction	Seg 9-Off to Hillsboro EB&WB
Date Performed		Jurisdiction	
Analysis Time Period	AM	Analysis Year	2020 Build 2

Project Description SW 10th Street SIMR

Inputs			
Upstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L _{up} = ft V _u = veh/h	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;"> Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L_A Deceleration Lane Length L_D 200 Freeway Volume, V_F 5670 Ramp Volume, V_R 1250 Freeway Free-Flow Speed, S_{FF} 70.0 Ramp Free-Flow Speed, S_{FR} 45.0 </td> <td style="width: 50%; border-left: 1px solid black;"> Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L_{down} = 2100 ft V_D = 1060 veh/h </td> </tr> </table>	Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A Deceleration Lane Length L _D 200 Freeway Volume, V _F 5670 Ramp Volume, V _R 1250 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 45.0	Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L _{down} = 2100 ft V _D = 1060 veh/h
Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A Deceleration Lane Length L _D 200 Freeway Volume, V _F 5670 Ramp Volume, V _R 1250 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 45.0	Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L _{down} = 2100 ft V _D = 1060 veh/h		

Conversion to pc/h Under Base Conditions								
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p
Freeway	5670	0.95	Level	3	0	0.985	1.00	6058
Ramp	1250	0.92	Level	2	0	0.990	1.00	1372
UpStream								
DownStream	1060	0.92	Level	2	0	0.990	1.00	1164

Merge Areas	Diverge Areas
Estimation of v₁₂ $V_{12} = V_F (P_{FM})$ L _{EQ} = (Equation 13-6 or 13-7) P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)	Estimation of v₁₂ $V_{12} = V_R + (V_F - V_R)P_{FD}$ L _{EQ} = (Equation 13-12 or 13-13) P _{FD} = 0.545 using Equation (Exhibit 13-7) V ₁₂ = 3928 pc/h V ₃ or V _{av34} 2130 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)

Capacity Checks				Capacity Checks			
	Actual	Capacity	LOS F?		Actual	Capacity	LOS F?
V _{FO}		Exhibit 13-8		V _F	6058	Exhibit 13-8	7200 No
				V _{FO} = V _F - V _R	4686	Exhibit 13-8	7200 No
				V _R	1372	Exhibit 13-10	2100 No

Flow Entering Merge Influence Area				Flow Entering Diverge Influence Area			
	Actual	Max Desirable	Violation?		Actual	Max Desirable	Violation?
V _{R12}		Exhibit 13-8		V ₁₂	3928	Exhibit 13-8	4400:All No

Level of Service Determination (if not F)	Level of Service Determination (if not F)
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)	$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 36.2 (pc/mi/ln) LOS = E (Exhibit 13-2)

Speed Determination	Speed Determination
M _S = (Exhibit 13-11)	D _s = 0.421 (Exhibit 13-12)
S _R = mph (Exhibit 13-11)	S _R = 58.2 mph (Exhibit 13-12)
S ₀ = mph (Exhibit 13-11)	S ₀ = 72.4 mph (Exhibit 13-12)
S = mph (Exhibit 13-13)	S = 62.5 mph (Exhibit 13-13)

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *AM*

Site Information

Highway/Direction of Travel *I-95 NB*
 From/To *Seg 10-Bet Off & On Ramps*
 Jurisdiction
 Analysis Year *2020 Build 2*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>4420</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1574* pc/h/ln
 S *68.4* mph
 $D = v_p / S$ *23.0* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

FREEWAY WEAVING WORKSHEET										
General Information					Site Information					
Analyst					Freeway/Dir of Travel					
Agency/Company AECOM					I-95 NB					
Date Performed					Weaving Segment Location					
Analysis Time Period AM					Seg 11-Bet On & Off to Exp					
					Analysis Year					
					2020 Build 2					
Project Description SW 10th Street SIMR										
Inputs										
Weaving configuration				Two-Sided		Segment type				Freeway
Weaving number of lanes, N				4		Freeway minimum speed, S_{MIN}				15
Weaving segment length, L_S				2970ft		Freeway maximum capacity, C_{IFL}				2400
Freeway free-flow speed, FFS				70 mph		Terrain type				Level
Conversions to pc/h Under Base Conditions										
	V (veh/h)	PHF	Truck (%)	RV (%)	E_T	E_R	f_{HV}	f_p	v (pc/h)	
V_{FF}	3770	0.95	3	0	1.5	1.2	0.985	1.00	4028	
V_{RF}	1970	0.92	2	0	1.5	1.2	0.990	1.00	2163	
V_{FR}	650	0.92	2	0	1.5	1.2	0.990	1.00	714	
V_{RR}	340	0.92	2	0	1.5	1.2	0.990	1.00	373	
V_{NW}	6905							V =	7278	
V_W	373									
VR	0.051									
Configuration Characteristics										
Minimum maneuver lanes, N_{WL}				0 lc		Minimum weaving lane changes, LC_{MIN}				1119 lc/h
Interchange density, ID				0.7 int/mi		Weaving lane changes, LC_W				1612 lc/h
Minimum RF lane changes, LC_{RF}				0 lc/pc		Non-weaving lane changes, LC_{NW}				2463 lc/h
Minimum FR lane changes, LC_{FR}				0 lc/pc		Total lane changes, LC_{ALL}				4075 lc/h
Minimum RR lane changes, LC_{RR}				3 lc/pc		Non-weaving vehicle index, I_{NW}				1436
Weaving Segment Speed, Density, Level of Service, and Capacity										
Weaving segment flow rate, v				7186 veh/h		Weaving intensity factor, W				0.290
Weaving segment capacity, c_w				8485 veh/h		Weaving segment speed, S				53.4 mph
Weaving segment v/c ratio				0.847		Average weaving speed, S_W				57.6 mph
Weaving segment density, D				34.1 pc/mi/ln		Average non-weaving speed, S_{NW}				53.2 mph
Level of Service, LOS				D		Maximum weaving length, L_{MAX}				6205 ft
Notes										
a. Weaving segments longer than the calculated maximum length should be treated as isolated merge and diverge areas using the procedures of Chapter 13, "Freeway Merge and Diverge Segments".										
b. For volumes that exceed the weaving segment capacity, the level of service is "F".										

BASIC FREEWAY SEGMENTS WORKSHEET			
General Information		Site Information	
Analyst		Highway/Direction of Travel	<i>I-95 NB</i>
Agency or Company	<i>AECOM</i>	From/To	<i>Seg 12-North of Hillsboro</i>
Date Performed		Jurisdiction	
Analysis Time Period	<i>AM</i>	Analysis Year	<i>2020 Build 2</i>
Project Description <i>SW 10th Street SIMR</i>			
<input checked="" type="checkbox"/> Oper.(LOS) <input type="checkbox"/> Des.(N) <input type="checkbox"/> Planning Data			
Flow Inputs			
Volume, V	<i>5740</i>	veh/h	Peak-Hour Factor, PHF
AADT		veh/day	<i>0.95</i>
Peak-Hr Prop. of AADT, K			%Trucks and Buses, P _T
Peak-Hr Direction Prop, D			<i>3</i>
DDHV = AADT x K x D		veh/h	%RVs, P _R
			<i>0</i>
			General Terrain:
			<i>Level</i>
			Grade % Length
			<i>mi</i>
			Up/Down %
Calculate Flow Adjustments			
f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>
Speed Inputs		Calc Speed Adj and FFS	
Lane Width	ft		
Rt-Side Lat. Clearance	ft	f _{LW}	mph
Number of Lanes, N	<i>4</i>	f _{LC}	mph
Total Ramp Density, TRD	ramps/mi	TRD Adjustment	mph
FFS (measured)	<i>70.0</i>	FFS	<i>70.0</i>
Base free-flow Speed, BFFS	mph		
LOS and Performance Measures		Design (N)	
<u>Operational (LOS)</u>		<u>Design (N)</u>	
v _p = (V or DDHV) / (PHF x N x f _{HV} x f _p)	<i>1533</i> pc/h/ln	Design LOS	
S	<i>68.7</i> mph	v _p = (V or DDHV) / (PHF x N x f _{HV} x f _p)	pc/h/ln
D = v _p / S	<i>22.3</i> pc/mi/ln	S	mph
LOS	<i>C</i>	D = v _p / S	pc/mi/ln
		Required Number of Lanes, N	
Glossary		Factor Location	
N - Number of lanes	S - Speed	E _R - Exhibits 11-10, 11-12	f _{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E _T - Exhibits 11-10, 11-11, 11-13	f _{LC} - Exhibit 11-9
v _p - Flow rate	FFS - Free-flow speed	f _p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v _p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

FREEWAY WEAVING WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 NB
Agency/Company	AECOM	Weaving Segment Location	Seg 1-Bet Copans & Sample
Date Performed		Analysis Year	2020 Build 2
Analysis Time Period	PM		

Project Description SW 10th Street SIMR

Inputs

Weaving configuration	One-Sided	Segment type	Freeway
Weaving number of lanes, N	4	Freeway minimum speed, S_{MIN}	15
Weaving segment length, L_S	2380ft	Freeway maximum capacity, C_{IFL}	2400
Freeway free-flow speed, FFS	70 mph	Terrain type	Level

Conversions to pc/h Under Base Conditions

	V (veh/h)	PHF	Truck (%)	RV (%)	E_T	E_R	f_{HV}	f_p	v (pc/h)
V_{FF}	4265	0.95	3	0	1.5	1.2	0.985	1.00	4557
V_{RF}	415	0.92	2	0	1.5	1.2	0.990	1.00	456
V_{FR}	1560	0.92	2	0	1.5	1.2	0.990	1.00	1713
V_{RR}	0	0.95	0	0	1.5	1.2	1.000	1.00	0
V_{NW}	4557							V =	6726
V_W	2169								
VR	0.322								

Configuration Characteristics

Minimum maneuver lanes, N_{WL}	2 lc	Minimum weaving lane changes, LC_{MIN}	2169 lc/h
Interchange density, ID	0.7 int/mi	Weaving lane changes, LC_W	2604 lc/h
Minimum RF lane changes, LC_{RF}	1 lc/pc	Non-weaving lane changes, LC_{NW}	1458 lc/h
Minimum FR lane changes, LC_{FR}	1 lc/pc	Total lane changes, LC_{ALL}	4062 lc/h
Minimum RR lane changes, LC_{RR}	lc/pc	Non-weaving vehicle index, I_{NW}	759

Weaving Segment Speed, Density, Level of Service, and Capacity

Weaving segment flow rate, v	6637 veh/h	Weaving intensity factor, W	0.345
Weaving segment capacity, c_w	7332 veh/h	Weaving segment speed, S	49.0 mph
Weaving segment v/c ratio	0.905	Average weaving speed, S_W	55.9 mph
Weaving segment density, D	34.3 pc/mi/ln	Average non-weaving speed, S_{NW}	46.3 mph
Level of Service, LOS	D	Maximum weaving length, L_{MAX}	5826 ft

Notes


- a. Weaving segments longer than the calculated maximum length should be treated as isolated merge and diverge areas using the procedures of Chapter 13, "Freeway Merge and Diverge Segments".
- b. For volumes that exceed the weaving segment capacity, the level of service is "F".

BASIC FREEWAY SEGMENTS WORKSHEET

General Information		Site Information	
Analyst		Highway/Direction of Travel	I-95 NB
Agency or Company	AECOM	From/To	Seg 2-Bet Off & On from Sample
Date Performed		Jurisdiction	
Analysis Time Period	PM	Analysis Year	2020 Build 2
Project Description SW 10th Street SIMR			
<input checked="" type="checkbox"/> Oper.(LOS)		<input type="checkbox"/> Des.(N)	
<input type="checkbox"/> Planning Data			
Flow Inputs			
Volume, V	4680	veh/h	Peak-Hour Factor, PHF
AADT		veh/day	%Trucks and Buses, P _T
Peak-Hr Prop. of AADT, K			%RVs, P _R
Peak-Hr Direction Prop, D			General Terrain:
DDHV = AADT x K x D		veh/h	Grade % Length
			Up/Down %
			0.95
			3
			0
			Level
			mi
Calculate Flow Adjustments			
f _p	1.00	E _R	1.2
E _T	1.5	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	0.985
Speed Inputs		Calc Speed Adj and FFS	
Lane Width	ft	f _{LV}	mph
Rt-Side Lat. Clearance	ft	f _{LC}	mph
Number of Lanes, N	3	TRD Adjustment	mph
Total Ramp Density, TRD	ramps/mi	FFS	70.0
FFS (measured)	70.0	mph	mph
Base free-flow Speed, BFFS	mph		
LOS and Performance Measures		Design (N)	
Operational (LOS)		Design (N)	
v _p = (V or DDHV) / (PHF x N x f _{HV} x f _p)	1667	Design LOS	
S	67.5	v _p = (V or DDHV) / (PHF x N x f _{HV} x f _p)	pc/h/ln
D = v _p / S	24.7	S	mph
LOS	C	D = v _p / S	pc/mi/ln
		Required Number of Lanes, N	
Glossary		Factor Location	
N - Number of lanes	S - Speed	E _R - Exhibits 11-10, 11-12	f _{LV} - Exhibit 11-8
V - Hourly volume	D - Density	E _T - Exhibits 11-10, 11-11, 11-13	f _{LC} - Exhibit 11-9
v _p - Flow rate	FFS - Free-flow speed	f _p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v _p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

Job: SW 10th Street SIMR
Analyst: AECOM

Location: Seg 3: I-95 Northbound On-Ramp from WB Sample Road
Analysis Period: PM Peak Hour
Analysis Year: 2020 Build 2



	PHF =	0.95	
	$V_{fr} =$	5,620	vph
	$V_r =$	940	vph
	$V_f =$	4,680	
Upstream Freeway	Tr % =	3%	
Ramp	Tr % =	2%	
Downstream Freeway	Tr % =	3%	
Freeway	$f_{HV} = 1/(1+P_T(E_T-1)+P_R(E_R-1)) =$		0.985
Ramp	$f_{HV} = 1/(1+P_T(E_T-1)+P_R(E_R-1)) =$		0.9901
flat terrain	$E_T =$	1.5	
	RV % =	0	
Driver Population adj.	$f_P =$	1.000	
	$V_{fr} = V_r/(PHF)(f_{HV})(f_P) =$		6,005 pc/h
	$V_r = V_r/(PHF)(f_{HV})(f_P) =$		999 pc/h
	$V_f = V_f/(PHF)(f_{HV})(f_P) =$		5,000 pc/h
No. lanes upstream of ramp	$N =$	3	

<u>No. Ln</u>	<u>Capacity Check (see Exhibits 25-3 and 25-7):</u>	Maximum	Actual	V/c	LOS F?
4	Fwy downstream of ramp (assume 70 mph free-flow speed) =	9,600	6,005	0.63	No
3	Fwy upstream of ramp (assume 70 mph free-flow speed) =	7,200	5,000	0.69	No
1	Capacity on On-Ramp (assume 45 mph free-flow speed) =	2,100	999	0.48	No

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 NB
Agency or Company	AECOM	Junction	Seg 4-On from Exp
Date Performed		Jurisdiction	
Analysis Time Period	PM	Analysis Year	2020 Build 2
Project Description SW 10th Street SIMR			

Inputs

Upstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off $L_{up} =$ ft $V_u =$ veh/h	Freeway Number of Lanes, N 4 Ramp Number of Lanes, N 1 Acceleration Lane Length, L_A 1500 Deceleration Lane Length L_D Freeway Volume, V_F 5620 Ramp Volume, V_R 610 Freeway Free-Flow Speed, S_{FF} 70.0 Ramp Free-Flow Speed, S_{FR} 50.0	Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input type="checkbox"/> On <input type="checkbox"/> No <input checked="" type="checkbox"/> Off $L_{down} =$ 2950 ft $V_D =$ 230 veh/h
--	--	--

Conversion to pc/h Under Base Conditions

(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f_{HV}	f_p	$v = V/PHF \times f_{HV} \times f_p$
Freeway	5620	0.95	Level	3	0	0.985	1.00	6005
Ramp	610	0.92	Level	2	0	0.990	1.00	670
UpStream								
DownStream	230	0.92	Level	2	0	0.990	1.00	252

Merge Areas

Diverge Areas

Estimation of v_{12}

$V_{12} = V_F (P_{FM})$
 (Equation 13-6 or 13-7)
 $L_{EQ} =$
 $P_{FM} =$ 0.134 using Equation (Exhibit 13-6)
 $V_{12} =$ 805 pc/h
 V_3 or V_{av34} 2600 pc/h (Equation 13-14 or 13-17)
 Is V_3 or $V_{av34} > 2,700$ pc/h? Yes No
 Is V_3 or $V_{av34} > 1.5 * V_{12}/2$ Yes No
 If Yes, $V_{12a} =$ 2402 pc/h (Equation 13-16, 13-18, or 13-19)

Estimation of v_{12}

$V_{12} = V_R + (V_F - V_R)P_{FD}$
 (Equation 13-12 or 13-13)
 $L_{EQ} =$
 $P_{FD} =$ using Equation (Exhibit 13-7)
 $V_{12} =$ pc/h
 V_3 or V_{av34} pc/h (Equation 13-14 or 13-17)
 Is V_3 or $V_{av34} > 2,700$ pc/h? Yes No
 Is V_3 or $V_{av34} > 1.5 * V_{12}/2$ Yes No
 If Yes, $V_{12a} =$ pc/h (Equation 13-16, 13-18, or 13-19)

Capacity Checks

	Actual	Capacity	LOS F?
V_{FO}	6675	Exhibit 13-8	No

Capacity Checks

	Actual	Capacity	LOS F?
V_F		Exhibit 13-8	
$V_{FO} = V_F - V_R$		Exhibit 13-8	
V_R		Exhibit 13-10	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
V_{R12}	3360	Exhibit 13-8	4600:All No

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
V_{12}		Exhibit 13-8	

Level of Service Determination (if not F)

$D_R = 5.475 + 0.00734 V_R + 0.0078 V_{12} - 0.00627 L_A$
 $D_R =$ 23.5 (pc/mi/ln)
 LOS = C (Exhibit 13-2)

Level of Service Determination (if not F)

$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$
 $D_R =$ (pc/mi/ln)
 LOS = (Exhibit 13-2)

Speed Determination

$M_S =$ 0.283 (Exhibit 13-11)
 $S_R =$ 62.1 mph (Exhibit 13-11)
 $S_0 =$ 66.2 mph (Exhibit 13-11)
 $S =$ 64.0 mph (Exhibit 13-13)

Speed Determination

$D_s =$ (Exhibit 13-12)
 $S_R =$ mph (Exhibit 13-12)
 $S_0 =$ mph (Exhibit 13-12)
 $S =$ mph (Exhibit 13-13)

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 NB
Agency or Company	AECOM	Junction	Seg 5-Off to Exp from GPL
Date Performed		Jurisdiction	
Analysis Time Period	PM	Analysis Year	2020 Build 2

Project Description SW 10th Street SIMR

Inputs		
Upstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L _{up} = 2950 ft V _u = 610 veh/h	Freeway Number of Lanes, N 4 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A Deceleration Lane Length L _D 200 Freeway Volume, V _F 6230 Ramp Volume, V _R 230 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 45.0	Downstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L _{down} = ft V _D = veh/h

Conversion to pc/h Under Base Conditions								
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p
Freeway	6230	0.95	Level	3	0	0.985	1.00	6656
Ramp	230	0.92	Level	2	0	0.990	1.00	252
UpStream	610	0.92	Level	2	0	0.990	1.00	670
DownStream								

Merge Areas	Diverge Areas
Estimation of v₁₂ $V_{12} = V_F (P_{FM})$ L _{EQ} = (Equation 13-6 or 13-7) P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)	Estimation of v₁₂ $V_{12} = V_R + (V_F - V_R)P_{FD}$ L _{EQ} = (Equation 13-12 or 13-13) P _{FD} = 0.436 using Equation (Exhibit 13-7) V ₁₂ = 3044 pc/h V ₃ or V _{av34} 1806 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)

Capacity Checks				Capacity Checks			
	Actual	Capacity	LOS F?		Actual	Capacity	LOS F?
V _{FO}		Exhibit 13-8		V _F	6656	Exhibit 13-8	9600 No
				V _{FO} = V _F - V _R	6404	Exhibit 13-8	9600 No
				V _R	252	Exhibit 13-10	2100 No

Flow Entering Merge Influence Area				Flow Entering Diverge Influence Area			
	Actual	Max Desirable	Violation?		Actual	Max Desirable	Violation?
V _{R12}		Exhibit 13-8		V ₁₂	3044	Exhibit 13-8	4400:All No

Level of Service Determination (if not F)	Level of Service Determination (if not F)
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)	$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 28.6 (pc/mi/ln) LOS = D (Exhibit 13-2)

Speed Determination	Speed Determination
M _S = (Exhibit 13-11)	D _s = 0.321 (Exhibit 13-12)
S _R = mph (Exhibit 13-11)	S _R = 61.0 mph (Exhibit 13-12)
S ₀ = mph (Exhibit 13-11)	S ₀ = 73.6 mph (Exhibit 13-12)
S = mph (Exhibit 13-13)	S = 67.3 mph (Exhibit 13-13)

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *PM*

Site Information

Highway/Direction of Travel *I-95 NB*
 From/To *Seg 6-South of Off to 10th*
 Jurisdiction
 Analysis Year *2020 Build 2*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>6000</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *4*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1603* pc/h/ln
 S *68.1* mph
 $D = v_p / S$ *23.5* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume

S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed


Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3

f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

Job: SW 10th Street SIMR
Analyst: AECOM

Location: Seg 7: I-95 NB Off-Ramp to SW 10th St EB & WB
Analysis Period: PM Peak Hour
Analysis Year: 2020 Build 2



PHF =	0.95	
v_{fr} =	6,000	vph
v_r =	1,060	vph
v_f =	4,940	
Upstream Freeway Tr % =	3%	
Ramp Tr % =	2%	
Downstream Freeway Tr % =	3%	
Freeway f_{HV} =	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	0.985
Ramp f_{HV} =	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	0.990099
flat terrain E_T =	1.5	
RV % =	0	
Driver Population adj. f_p =	1.000	
V_{fr} =	$=v_{fr}/(PHF)(f_{HV})(f_p) =$	6,411 pc/h
V_r =	$=v_r/(PHF)(f_{HV})(f_p) =$	1,127 pc/h
V_f =	$=v_f/(PHF)(f_{HV})(f_p) =$	5,278 pc/h
No. lanes upstream of ramp N =	4	

Average Freeway Density Upstream of Diverge (see Equation 13-26):

$D = 0.0175 (V_{fr}/N) = 28.0 \text{ pc/ln}$

LOS in the Diverge Area (from Density and Exhibit 13-2) =

D

No. Ln	Capacity Check (see Exhibits 13-2, 13-8 and 13.10)	Maximum	Actual	LOS F?
4	Fwy upstream of ramp (assume 70 mph free-flow speed) =	9,600	6,411	No
3	Fwy downstream of ramp (assume 70 mph free-flow speed) =	7,200	5,278	No
1	Capacity on Off-Ramp (assume 45 mph free-flow speed) =	2,100	1,127	No

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *PM*

Site Information

Highway/Direction of Travel *I-95 NB*
 From/To *Seg 8-Bet Off & Off Ramps*
 Jurisdiction
 Analysis Year *2020 Build 2*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>4940</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1759* pc/h/ln
 S *66.4* mph
 $D = v_p / S$ *26.5* pc/mi/ln
 LOS *D*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 NB
Agency or Company	AECOM	Junction	Seg 9-Off to Hillsboro EB&WB
Date Performed		Jurisdiction	
Analysis Time Period	PM	Analysis Year	2020 Build 2

Project Description SW 10th Street SIMR

Inputs			
Upstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L _{up} = ft V _u = veh/h	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;"> Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L_A Deceleration Lane Length L_D 200 Freeway Volume, V_F 4940 Ramp Volume, V_R 1250 Freeway Free-Flow Speed, S_{FF} 70.0 Ramp Free-Flow Speed, S_{FR} 45.0 </td> <td style="width: 50%; vertical-align: top;"> Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L_{down} = 2100 ft V_D = 1200 veh/h </td> </tr> </table>	Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A Deceleration Lane Length L _D 200 Freeway Volume, V _F 4940 Ramp Volume, V _R 1250 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 45.0	Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L _{down} = 2100 ft V _D = 1200 veh/h
Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A Deceleration Lane Length L _D 200 Freeway Volume, V _F 4940 Ramp Volume, V _R 1250 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 45.0	Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L _{down} = 2100 ft V _D = 1200 veh/h		

Conversion to pc/h Under Base Conditions								
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p
Freeway	4940	0.95	Level	3	0	0.985	1.00	5278
Ramp	1250	0.92	Level	2	0	0.990	1.00	1372
UpStream								
DownStream	1200	0.92	Level	2	0	0.990	1.00	1317

Merge Areas	Diverge Areas
Estimation of v₁₂ $V_{12} = V_F (P_{FM})$ L _{EQ} = (Equation 13-6 or 13-7) P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)	Estimation of v₁₂ $V_{12} = V_R + (V_F - V_R)P_{FD}$ L _{EQ} = (Equation 13-12 or 13-13) P _{FD} = 0.565 using Equation (Exhibit 13-7) V ₁₂ = 3579 pc/h V ₃ or V _{av34} 1699 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)

Capacity Checks				Capacity Checks			
	Actual	Capacity	LOS F?		Actual	Capacity	LOS F?
V _{FO}		Exhibit 13-8		V _F	5278	Exhibit 13-8	7200 No
				V _{FO} = V _F - V _R	3906	Exhibit 13-8	7200 No
				V _R	1372	Exhibit 13-10	2100 No

Flow Entering Merge Influence Area				Flow Entering Diverge Influence Area			
	Actual	Max Desirable	Violation?		Actual	Max Desirable	Violation?
V _{R12}		Exhibit 13-8		V ₁₂	3579	Exhibit 13-8	4400:All No

Level of Service Determination (if not F)	Level of Service Determination (if not F)
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)	$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 33.2 (pc/mi/ln) LOS = D (Exhibit 13-2)

Speed Determination	Speed Determination
M _S = (Exhibit 13-11)	D _s = 0.421 (Exhibit 13-12)
S _R = mph (Exhibit 13-11)	S _R = 58.2 mph (Exhibit 13-12)
S ₀ = mph (Exhibit 13-11)	S ₀ = 74.1 mph (Exhibit 13-12)
S = mph (Exhibit 13-13)	S = 62.5 mph (Exhibit 13-13)

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *PM*

Site Information

Highway/Direction of Travel *I-95 NB*
 From/To *Seg 10-Bet Off & On Ramps*
 Jurisdiction
 Analysis Year *2020 Build 2*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	3690	veh/h	Peak-Hour Factor, PHF	0.95
AADT		veh/day	%Trucks and Buses, P _T	3
Peak-Hr Prop. of AADT, K			%RVs, P _R	0
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	1.00	E _R	1.2
E _T	1.5	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	0.985

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1314* pc/h/ln
 S *69.8* mph
 $D = v_p / S$ *18.8* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes S - Speed
 V - Hourly volume D - Density
 v_p - Flow rate FFS - Free-flow speed
 LOS - Level of service BFFS - Base free-flow speed
 DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12 f_{LW} - Exhibit 11-8
 E_T - Exhibits 11-10, 11-11, 11-13 f_{LC} - Exhibit 11-9
 f_p - Page 11-18 TRD - Page 11-11
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3

FREEWAY WEAVING WORKSHEET										
General Information					Site Information					
Analyst					Freeway/Dir of Travel					
Agency/Company AECOM					I-95 NB					
Date Performed					Weaving Segment Location					
Analysis Time Period PM					Seg 11-Bet On & Off to Exp					
					Analysis Year					
					2020 Build 2					
Project Description SW 10th Street SIMR										
Inputs										
Weaving configuration				Two-Sided		Segment type				Freeway
Weaving number of lanes, N				4		Freeway minimum speed, S _{MIN}				15
Weaving segment length, L _S				2970ft		Freeway maximum capacity, C _{IFL}				2400
Freeway free-flow speed, FFS				70 mph		Terrain type				Level
Conversions to pc/h Under Base Conditions										
	V (veh/h)	PHF	Truck (%)	RV (%)	E _T	E _R	f _{HV}	f _p	v (pc/h)	
V _{FF}	3198	0.95	3	0	1.5	1.2	0.985	1.00	3417	
V _{RF}	2132	0.92	2	0	1.5	1.2	0.990	1.00	2341	
V _{FR}	492	0.92	2	0	1.5	1.2	0.990	1.00	540	
V _{RR}	328	0.92	2	0	1.5	1.2	0.990	1.00	360	
V _{NW}	6298							V =	6658	
V _W	360									
VR	0.054									
Configuration Characteristics										
Minimum maneuver lanes, N _{WL}				0 lc		Minimum weaving lane changes, LC _{MIN}				1080 lc/h
Interchange density, ID				0.7 int/mi		Weaving lane changes, LC _W				1573 lc/h
Minimum RF lane changes, LC _{RF}				0 lc/pc		Non-weaving lane changes, LC _{NW}				2150 lc/h
Minimum FR lane changes, LC _{FR}				0 lc/pc		Total lane changes, LC _{ALL}				3723 lc/h
Minimum RR lane changes, LC _{RR}				3 lc/pc		Non-weaving vehicle index, I _{NW}				1309
Weaving Segment Speed, Density, Level of Service, and Capacity										
Weaving segment flow rate, v				6576 veh/h		Weaving intensity factor, W				0.270
Weaving segment capacity, c _w				8473 veh/h		Weaving segment speed, S				54.4 mph
Weaving segment v/c ratio				0.776		Average weaving speed, S _w				58.3 mph
Weaving segment density, D				30.6 pc/mi/ln		Average non-weaving speed, S _{NW}				54.2 mph
Level of Service, LOS				D		Maximum weaving length, L _{MAX}				6232 ft
Notes										
a. Weaving segments longer than the calculated maximum length should be treated as isolated merge and diverge areas using the procedures of Chapter 13, "Freeway Merge and Diverge Segments".										
b. For volumes that exceed the weaving segment capacity, the level of service is "F".										

BASIC FREEWAY SEGMENTS WORKSHEET			
General Information		Site Information	
Analyst		Highway/Direction of Travel	<i>I-95 NB</i>
Agency or Company	<i>AECOM</i>	From/To	<i>Seg 12-North of Hillsboro</i>
Date Performed		Jurisdiction	
Analysis Time Period	<i>PM</i>	Analysis Year	<i>2020 Build 2</i>
Project Description <i>SW 10th Street SIMR</i>			
<input checked="" type="checkbox"/> Oper.(LOS)		<input type="checkbox"/> Des.(N)	
<input type="checkbox"/> Planning Data			
Flow Inputs			
Volume, V	<i>5330</i>	veh/h	Peak-Hour Factor, PHF <i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T <i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R <i>0</i>
Peak-Hr Direction Prop, D			General Terrain: <i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length <i>mi</i>
			Up/Down %
Calculate Flow Adjustments			
f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>
Speed Inputs		Calc Speed Adj and FFS	
Lane Width		ft	
Rt-Side Lat. Clearance		ft	f _{LW}
Number of Lanes, N	<i>4</i>		mph
Total Ramp Density, TRD		ramps/mi	f _{LC}
FFS (measured)	<i>70.0</i>	mph	TRD Adjustment
Base free-flow Speed, BFFS		mph	FFS
			<i>70.0</i>
			mph
LOS and Performance Measures		Design (N)	
<u>Operational (LOS)</u>		<u>Design (N)</u>	
v _p = (V or DDHV) / (PHF x N x f _{HV})		Design LOS	
	<i>1424</i>	pc/h/ln	v _p = (V or DDHV) / (PHF x N x f _{HV})
x f _p)			pc/h/ln
S	<i>69.4</i>	mph	x f _p)
D = v _p / S	<i>20.5</i>	pc/mi/ln	S
LOS	<i>C</i>		mph
			D = v _p / S
			pc/mi/ln
			Required Number of Lanes, N
Glossary		Factor Location	
N - Number of lanes	S - Speed	E _R - Exhibits 11-10, 11-12	f _{LW} - Exhibit 11-8
V - Hourly volume	D - Density	E _T - Exhibits 11-10, 11-11, 11-13	f _{LC} - Exhibit 11-9
v _p - Flow rate	FFS - Free-flow speed	f _p - Page 11-18	TRD - Page 11-11
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v _p - Exhibits 11-2, 11-3	
DDHV - Directional design hour volume			

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *AM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 1-Bet Hillsboro & Palmetto*
 Jurisdiction
 Analysis Year *2020 Build 2*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>4580</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *4*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1223* pc/h/ln
 S *70.0* mph
 $D = v_p / S$ *17.5* pc/mi/ln
 LOS *B*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume

S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3

f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

FREEWAY WEAVING WORKSHEET									
General Information					Site Information				
Analyst Agency/Company AECOM Date Performed Analysis Time Period AM					Freeway/Dir of Travel 195/SB Weaving Segment Location Seg 2-Bet On from Exp & Off Analysis Year 2020 Build 2				
Project Description SW 10th Street SIMR									
Inputs									
Weaving configuration Two-Sided Weaving number of lanes, N 4 Weaving segment length, L _S 3900ft Freeway free-flow speed, FFS 70 mph					Segment type Freeway Freeway minimum speed, S _{MIN} 15 Freeway maximum capacity, C _{IFL} 2400 Terrain type Level				
Conversions to pc/h Under Base Conditions									
	V (veh/h)	PHF	Truck (%)	RV (%)	E _T	E _R	f _{HV}	f _p	v (pc/h)
V _{FF}	3460	0.95	3	0	1.5	1.2	0.985	1.00	3697
V _{RF}	850	0.92	2	0	1.5	1.2	0.990	1.00	933
V _{FR}	1120	0.92	2	0	1.5	1.2	0.990	1.00	1230
V _{RR}	90	0.92	2	0	1.5	1.2	0.990	1.00	99
V _{NW}	5860							V =	5959
V _W	99								
VR	0.017								
Configuration Characteristics									
Minimum maneuver lanes, N _{WL} 0 lc					Minimum weaving lane changes, LC _{MIN} 297 lc/h				
Interchange density, ID 0.7 int/mi					Weaving lane changes, LC _W 869 lc/h				
Minimum RF lane changes, LC _{RF} 0 lc/pc					Non-weaving lane changes, LC _{NW} 2756 lc/h				
Minimum FR lane changes, LC _{FR} 0 lc/pc					Total lane changes, LC _{ALL} 3625 lc/h				
Minimum RR lane changes, LC _{RR} 3 lc/pc					Non-weaving vehicle index, I _{NW} 1600				
Weaving Segment Speed, Density, Level of Service, and Capacity									
Weaving segment flow rate, v 5882 veh/h					Weaving intensity factor, W 0.213				
Weaving segment capacity, c _w 8859 veh/h					Weaving segment speed, S 60.7 mph				
Weaving segment v/c ratio 0.664					Average weaving speed, S _w 60.3 mph				
Weaving segment density, D 24.5 pc/mi/ln					Average non-weaving speed, S _{NW} 60.7 mph				
Level of Service, LOS C					Maximum weaving length, L _{MAX} 5881 ft				
Notes									
a. Weaving segments longer than the calculated maximum length should be treated as isolated merge and diverge areas using the procedures of Chapter 13, "Freeway Merge and Diverge Segments".									
b. For volumes that exceed the weaving segment capacity, the level of service is "F".									

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *AM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 3-Bet Off & On Ramp*
 Jurisdiction
 Analysis Year *2020 Build 2*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>4310</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1535* pc/h/ln
 S *68.7* mph
 $D = v_p / S$ *22.3* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume

S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3

f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 SB
Agency or Company	AECOM	Junction	Seg 4-Diverge to SW 10th St
Date Performed		Jurisdiction	
Analysis Time Period	AM	Analysis Year	2020 Build 2

Project Description SW 10th Street SIMR

Inputs			
Upstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L _{up} = ft V _u = veh/h	<table style="width: 100%;"> <tr> <td style="width: 50%;"> Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L_A Deceleration Lane Length L_D 200 Freeway Volume, V_F 4310 Ramp Volume, V_R 1100 Freeway Free-Flow Speed, S_{FF} 70.0 Ramp Free-Flow Speed, S_{FR} 45.0 </td> <td style="width: 50%; vertical-align: top;"> Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L_{down} = 2400 ft V_D = 1290 veh/h </td> </tr> </table>	Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A Deceleration Lane Length L _D 200 Freeway Volume, V _F 4310 Ramp Volume, V _R 1100 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 45.0	Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L _{down} = 2400 ft V _D = 1290 veh/h
Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A Deceleration Lane Length L _D 200 Freeway Volume, V _F 4310 Ramp Volume, V _R 1100 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 45.0	Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L _{down} = 2400 ft V _D = 1290 veh/h		

Conversion to pc/h Under Base Conditions								
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p
Freeway	4310	0.95	Level	3	0	0.985	1.00	4605
Ramp	1100	0.92	Level	2	0	0.990	1.00	1208
UpStream								
DownStream	1290	0.92	Level	2	0	0.990	1.00	1416

Merge Areas	Diverge Areas
Estimation of v₁₂ $V_{12} = V_F (P_{FM})$ L _{EQ} = (Equation 13-6 or 13-7) P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)	Estimation of v₁₂ $V_{12} = V_R + (V_F - V_R)P_{FD}$ L _{EQ} = (Equation 13-12 or 13-13) P _{FD} = 0.589 using Equation (Exhibit 13-7) V ₁₂ = 3210 pc/h V ₃ or V _{av34} 1395 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)

Capacity Checks				Capacity Checks			
	Actual	Capacity	LOS F?		Actual	Capacity	LOS F?
V _{FO}		Exhibit 13-8		V _F	4605	Exhibit 13-8	7200 No
				V _{FO} = V _F - V _R	3397	Exhibit 13-8	7200 No
				V _R	1208	Exhibit 13-10	2100 No

Flow Entering Merge Influence Area				Flow Entering Diverge Influence Area			
	Actual	Max Desirable	Violation?		Actual	Max Desirable	Violation?
V _{R12}		Exhibit 13-8		V ₁₂	3210	Exhibit 13-8	4400:All No

Level of Service Determination (if not F)	Level of Service Determination (if not F)
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)	$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 30.1 (pc/mi/ln) LOS = D (Exhibit 13-2)

Speed Determination	Speed Determination
M _S = (Exhibit 13-11)	D _s = 0.407 (Exhibit 13-12)
S _R = mph (Exhibit 13-11)	S _R = 58.6 mph (Exhibit 13-12)
S ₀ = mph (Exhibit 13-11)	S ₀ = 75.2 mph (Exhibit 13-12)
S = mph (Exhibit 13-13)	S = 62.8 mph (Exhibit 13-13)

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *AM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 5-Bet Off & On Ramps*
 Jurisdiction
 Analysis Year *2020 Build 2*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	3210	veh/h	Peak-Hour Factor, PHF	0.95
AADT		veh/day	%Trucks and Buses, P _T	3
Peak-Hr Prop. of AADT, K			%RVs, P _R	0
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	1.00	E _R	1.2
E _T	1.5	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	0.985

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1143* pc/h/ln
 S *70.0* mph
 $D = v_p / S$ *16.3* pc/mi/ln
 LOS *B*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume

S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3

f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 SB
Agency or Company	AECOM	Junction	Seg 6-Merge from Hillsboro E&W
Date Performed		Jurisdiction	
Analysis Time Period	AM	Analysis Year	2020 Build 2
Project Description SW 10th Street SIMR			

Inputs

Upstream Adj Ramp <input checked="" type="checkbox"/> Yes <input type="checkbox"/> On <input type="checkbox"/> No <input checked="" type="checkbox"/> Off	Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A 300 Deceleration Lane Length L _D Freeway Volume, V _F 3210 Ramp Volume, V _R 1290 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 50.0	Downstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L _{down} = ft V _D = veh/h
L _{up} = 2400 ft V _u = 1100 veh/h		

Conversion to pc/h Under Base Conditions

(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p
Freeway	3210	0.95	Level	3	0	0.985	1.00	3430
Ramp	1290	0.92	Level	2	0	0.990	1.00	1416
UpStream	1100	0.92	Level	2	0	0.990	1.00	1208
DownStream								

Merge Areas	Diverge Areas
--------------------	----------------------

Estimation of v₁₂

$V_{12} = V_F (P_{FM})$ L _{EQ} = 1383.24 (Equation 13-6 or 13-7) P _{FM} = 0.586 using Equation (Exhibit 13-6) V ₁₂ = 2010 pc/h V ₃ or V _{av34} = 1420 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = 2010 pc/h (Equation 13-16, 13-18, or 13-19)	$V_{12} = V_R + (V_F - V_R)P_{FD}$ L _{EQ} = (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)
--	--

Estimation of v₁₂

$V_{12} = V_F (P_{FM})$ L _{EQ} = 1383.24 (Equation 13-6 or 13-7) P _{FM} = 0.586 using Equation (Exhibit 13-6) V ₁₂ = 2010 pc/h V ₃ or V _{av34} = 1420 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = 2010 pc/h (Equation 13-16, 13-18, or 13-19)	$V_{12} = V_R + (V_F - V_R)P_{FD}$ L _{EQ} = (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)
--	--

Capacity Checks

	Actual	Capacity	LOS F?
V _{FO}	4846	Exhibit 13-8	No

Capacity Checks

	Actual	Capacity	LOS F?
V _F		Exhibit 13-8	
V _{FO} = V _F - V _R		Exhibit 13-8	
V _R		Exhibit 13-10	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
V _{R12}	3426	Exhibit 13-8	4600:All No

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
V ₁₂		Exhibit 13-8	

Level of Service Determination (if not F)

$D_R = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A$ D _R = 29.7 (pc/mi/ln) LOS = D (Exhibit 13-2)	$D_R = 4.252 + 0.0086 v_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)
---	--

Level of Service Determination (if not F)

$D_R = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A$ D _R = 29.7 (pc/mi/ln) LOS = D (Exhibit 13-2)	$D_R = 4.252 + 0.0086 v_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)
---	--

Speed Determination

M _S = 0.411 (Exhibit 13-11) S _R = 58.5 mph (Exhibit 13-11) S ₀ = 66.7 mph (Exhibit 13-11) S = 60.7 mph (Exhibit 13-13)	D _s = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)
--	---

Speed Determination

M _S = 0.411 (Exhibit 13-11) S _R = 58.5 mph (Exhibit 13-11) S ₀ = 66.7 mph (Exhibit 13-11) S = 60.7 mph (Exhibit 13-13)	D _s = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)
--	---

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *AM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 7-Bet On Ramps*
 Jurisdiction
 Analysis Year *2020 Build 2*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>4500</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1603* pc/h/ln
 S *68.1* mph
 $D = v_p / S$ *23.5* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary


N - Number of lanes S - Speed
 V - Hourly volume D - Density
 v_p - Flow rate FFS - Free-flow speed
 LOS - Level of service BFFS - Base free-flow speed
 DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12 f_{LW} - Exhibit 11-8
 E_T - Exhibits 11-10, 11-11, 11-13 f_{LC} - Exhibit 11-9
 f_p - Page 11-18 TRD - Page 11-11
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3

Job: SW 10th Street SIMR
Analyst: AECOM

Location: Seg 8: I-95 Southbound On-Ramp from SW 10th Street EB & WB
Analysis Period: AM Peak Hour
Analysis Year: 2020 Build 2



	PHF =	0.95	
	v_{fr} =	5,460	vph
	v_r =	960	vph
	v_f =	4,500	
Upstream Freeway	Tr % =	3%	
Ramp	Tr % =	2%	
Downstream Freeway	Tr % =	3%	
Freeway	f_{HV} =	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	0.985
Ramp	f_{HV} =	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	0.9901
flat terrain	E_T =	1.5	
	RV % =	0	
Driver Population adj.	f_P =	1.000	
	V_{fr} =	$=v_{fr}/(PHF)(f_{HV})(f_P) =$	5,834 pc/h
	V_r =	$=v_r/(PHF)(f_{HV})(f_P) =$	1,021 pc/h
	V_f =	$=v_f/(PHF)(f_{HV})(f_P) =$	4,808 pc/h
No. lanes upstream of ramp	N =	3	

No. Ln	Capacity Check (see Exhibits 25-3 and 25-7):	Maximum	Actual	V/c	LOS F?
4	Fwy downstream of ramp (assume 70 mph free-flow speed) =	9,600	5,834	0.61	No
3	Fwy upstream of ramp (assume 70 mph free-flow speed) =	7,200	4,808	0.67	No
1	Capacity on On-Ramp (assume 45 mph free-flow speed) =	2,100	1,021	0.49	No

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *AM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 9-Bet 10th & Exit to Exp*
 Jurisdiction
 Analysis Year *2020 Build 2*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>5460</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *4*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1458* pc/h/ln
 S *69.2* mph
 $D = v_p / S$ *21.1* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

RAMPS AND RAMP JUNCTIONS WORKSHEET

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information

Site Information

Analyst		Freeway/Dir of Travel	I-95 SB
Agency or Company	AECOM	Junction	Seg 10-Merge from Ex to GP
Date Performed		Jurisdiction	
Analysis Time Period	AM	Analysis Year	2020 Build 2

Project Description SW 10th Street SIMR

Inputs

Upstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off	Freeway Number of Lanes, N Ramp Number of Lanes, N Acceleration Lane Length, L _A Deceleration Lane Length L _D Freeway Volume, V _F Ramp Volume, V _R Freeway Free-Flow Speed, S _{FF} Ramp Free-Flow Speed, S _{FR}	4 1 600 5460 270 70.0 50.0	Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input type="checkbox"/> On <input type="checkbox"/> No <input checked="" type="checkbox"/> Off L _{down} = 1150 ft V _D = 650 veh/h
--	--	--	--

Conversion to pc/h Under Base Conditions

(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p
Freeway	5460	0.95	Level	3	0	0.985	1.00	5834
Ramp	270	0.92	Level	2	0	0.990	1.00	296
UpStream								
DownStream	650	0.92	Level	2	0	0.990	1.00	714

Merge Areas

Diverge Areas

Estimation of v₁₂

Estimation of v₁₂

$V_{12} = V_F (P_{FM})$
 (Equation 13-6 or 13-7)
 $P_{FM} = 0.181$ using Equation (Exhibit 13-6)
 $V_{12} = 1055$ pc/h
 V_3 or $V_{av34} = 2389$ pc/h (Equation 13-14 or 13-17)
 Is V_3 or $V_{av34} > 2,700$ pc/h? Yes No
 Is V_3 or $V_{av34} > 1.5 * V_{12}/2$ Yes No
 If Yes, $V_{12a} = 2333$ pc/h (Equation 13-16, 13-18, or 13-19)

$V_{12} = V_R + (V_F - V_R)P_{FD}$
 (Equation 13-12 or 13-13)
 $P_{FD} =$ using Equation (Exhibit 13-7)
 $V_{12} =$ pc/h
 V_3 or $V_{av34} =$ pc/h (Equation 13-14 or 13-17)
 Is V_3 or $V_{av34} > 2,700$ pc/h? Yes No
 Is V_3 or $V_{av34} > 1.5 * V_{12}/2$ Yes No
 If Yes, $V_{12a} =$ pc/h (Equation 13-16, 13-18, or 13-19)

Capacity Checks

Capacity Checks

	Actual	Capacity	LOS F?		Actual	Capacity	LOS F?
V _{FO}	6130	Exhibit 13-8	No	V _F		Exhibit 13-8	
				V _{FO} = V _F - V _R		Exhibit 13-8	
				V _R		Exhibit 13-10	

Flow Entering Merge Influence Area

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?		Actual	Max Desirable	Violation?
V _{R12}	2629	Exhibit 13-8	4600:All	No	V ₁₂	Exhibit 13-8	

Level of Service Determination (if not F)

Level of Service Determination (if not F)

$D_R = 5.475 + 0.00734 V_R + 0.0078 V_{12} - 0.00627 L_A$
 $D_R = 22.1$ (pc/mi/ln)
 LOS = C (Exhibit 13-2)

$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$
 $D_R =$ (pc/mi/ln)
 LOS = (Exhibit 13-2)

Speed Determination

Speed Determination

$M_S = 0.315$ (Exhibit 13-11)
 $S_R = 61.2$ mph (Exhibit 13-11)
 $S_0 = 65.5$ mph (Exhibit 13-11)
 $S = 63.6$ mph (Exhibit 13-13)

$D_S =$ (Exhibit 13-12)
 $S_R =$ mph (Exhibit 13-12)
 $S_0 =$ mph (Exhibit 13-12)
 $S =$ mph (Exhibit 13-13)

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 SB
Agency or Company	AECOM	Junction	Seg 11- Diverge to Express
Date Performed		Jurisdiction	
Analysis Time Period	AM	Analysis Year	2020 Build 2

Project Description SW 10th Street SIMR

Inputs			
Upstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L _{up} = 1150 ft V _u = 270 veh/h	<table style="width: 100%;"> <tr> <td style="width: 50%;"> Freeway Number of Lanes, N 4 Ramp Number of Lanes, N 1 Acceleration Lane Length, L_A Deceleration Lane Length L_D 200 Freeway Volume, V_F 5730 Ramp Volume, V_R 650 Freeway Free-Flow Speed, S_{FF} 70.0 Ramp Free-Flow Speed, S_{FR} 45.0 </td> <td style="width: 50%;"> Downstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L_{down} = ft V_D = veh/h </td> </tr> </table>	Freeway Number of Lanes, N 4 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A Deceleration Lane Length L _D 200 Freeway Volume, V _F 5730 Ramp Volume, V _R 650 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 45.0	Downstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L _{down} = ft V _D = veh/h
Freeway Number of Lanes, N 4 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A Deceleration Lane Length L _D 200 Freeway Volume, V _F 5730 Ramp Volume, V _R 650 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 45.0	Downstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L _{down} = ft V _D = veh/h		

Conversion to pc/h Under Base Conditions								
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p
Freeway	5730	0.95	Level	3	0	0.985	1.00	6122
Ramp	650	0.92	Level	2	0	0.990	1.00	714
UpStream	270	0.92	Level	2	0	0.990	1.00	296
DownStream								

Merge Areas	Diverge Areas
Estimation of v₁₂ $V_{12} = V_F (P_{FM})$ L _{EQ} = (Equation 13-6 or 13-7) P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)	Estimation of v₁₂ $V_{12} = V_R + (V_F - V_R)P_{FD}$ L _{EQ} = (Equation 13-12 or 13-13) P _{FD} = 0.436 using Equation (Exhibit 13-7) V ₁₂ = 3072 pc/h V ₃ or V _{av34} 1525 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)

Capacity Checks				Capacity Checks			
	Actual	Capacity	LOS F?		Actual	Capacity	LOS F?
V _{FO}		Exhibit 13-8		V _F	6122	Exhibit 13-8	9600 No
				V _{FO} = V _F - V _R	5408	Exhibit 13-8	9600 No
				V _R	714	Exhibit 13-10	2100 No


Flow Entering Merge Influence Area				Flow Entering Diverge Influence Area			
	Actual	Max Desirable	Violation?		Actual	Max Desirable	Violation?
V _{R12}		Exhibit 13-8		V ₁₂	3072	Exhibit 13-8	4400:All No

Level of Service Determination (if not F)	Level of Service Determination (if not F)
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)	$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 31.5 (pc/mi/ln) LOS = D (Exhibit 13-2)

Speed Determination	Speed Determination
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)	D _s = 0.362 (Exhibit 13-12) S _R = 59.9 mph (Exhibit 13-12) S ₀ = 75.3 mph (Exhibit 13-12) S = 65.9 mph (Exhibit 13-13)

Job: SW 10th Street SIMR
Analyst: AECOM

Location: Seg 12: I-95 SB Off-Ramp to Sample Road EB & WB
Analysis Period: AM Peak Hour
Analysis Year: 2020 Build 2



PHF =	0.95	
v_{fr} =	5,080	vph
v_r =	860	vph
v_f =	4,220	
Upstream Freeway Tr % =	3%	
Ramp Tr % =	2%	
Downstream Freeway Tr % =	3%	
Freeway f_{HV} =	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	0.985
Ramp f_{HV} =	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	0.9901
flat terrain E_T =	1.5	
RV % =	0	
Driver Population adj. f_P =	1.000	
V_{fr} =	$=v_{fr}/(PHF)(f_{HV})(f_P) =$	5,428 pc/h
V_r =	$=v_r/(PHF)(f_{HV})(f_P) =$	914 pc/h
V_f =	$=v_f/(PHF)(f_{HV})(f_P) =$	4,509 pc/h
No. lanes upstream of ramp N =	4	

Average Freeway Density Upstream of Diverge (see Equation 13-26):

D = 0.0175 (V_{fr}/N) = 23.7 pc/ln

LOS in the Diverge Area (from Density and Exhibit 13-2) =

C

No. Ln	Capacity Check (see Exhibits 13-2, 13-8 and 13.10)	Maximum	Actual	LOS F?
4	Fwy upstream of ramp (assume 70 mph free-flow speed) =	9,600	5,428	No
3	Fwy downstream of ramp (assume 70 mph free-flow speed) =	7,200	4,509	No
1	Capacity on Off-Ramp (assume 45 mph free-flow speed) =	2,100	914	No

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *AM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 13-Bet Off & On Ramps*
 Jurisdiction
 Analysis Year *2020 Build 2*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	4220	veh/h	Peak-Hour Factor, PHF	0.95
AADT		veh/day	%Trucks and Buses, P _T	3
Peak-Hr Prop. of AADT, K			%RVs, P _R	0
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	1.00	E _R	1.2
E _T	1.5	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	0.985

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N 3
 Total Ramp Density, TRD ramps/mi
 FFS (measured) 70.0 mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS 70.0 mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1503* pc/h/ln
 S 68.9 mph
 $D = v_p / S$ 21.8 pc/mi/ln
 LOS C

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes S - Speed
 V - Hourly volume D - Density
 v_p - Flow rate FFS - Free-flow speed
 LOS - Level of service BFFS - Base free-flow speed
 DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12 f_{LW} - Exhibit 11-8
 E_T - Exhibits 11-10, 11-11, 11-13 f_{LC} - Exhibit 11-9
 f_p - Page 11-18 TRD - Page 11-11
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3

FREEWAY WEAVING WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 SB
Agency/Company	AECOM	Weaving Segment Location	Seg 14- Bet Sample & Copans
Date Performed		Analysis Year	2020 Build 2
Analysis Time Period	AM		

Project Description SW 10th Street SIMR

Inputs

Weaving configuration	One-Sided	Segment type	Freeway
Weaving number of lanes, N	4	Freeway minimum speed, S_{MIN}	15
Weaving segment length, L_S	2520ft	Freeway maximum capacity, C_{IFL}	2400
Freeway free-flow speed, FFS	70 mph	Terrain type	Level

Conversions to pc/h Under Base Conditions

	V (veh/h)	PHF	Truck (%)	RV (%)	E_T	E_R	f_{HV}	f_p	v (pc/h)
V_{FF}	3605	0.95	3	0	1.5	1.2	0.985	1.00	3852
V_{RF}	1780	0.92	2	0	1.5	1.2	0.990	1.00	1954
V_{FR}	615	0.92	2	0	1.5	1.2	0.990	1.00	675
V_{RR}	0	0.95	0	0	1.5	1.2	1.000	1.00	0
V_{NW}	3852							V =	6481
V_W	2629								
VR	0.406								

Configuration Characteristics

Minimum maneuver lanes, N_{WL}	2 lc	Minimum weaving lane changes, LC_{MIN}	lc/h
Interchange density, ID	0.7 int/mi	Weaving lane changes, LC_W	lc/h
Minimum RF lane changes, LC_{RF}	1 lc/pc	Non-weaving lane changes, LC_{NW}	lc/h
Minimum FR lane changes, LC_{FR}	1 lc/pc	Total lane changes, LC_{ALL}	lc/h
Minimum RR lane changes, LC_{RR}	lc/pc	Non-weaving vehicle index, I_{NW}	

Weaving Segment Speed, Density, Level of Service, and Capacity

Weaving segment flow rate, v	6398 veh/h	Weaving intensity factor, W	
Weaving segment capacity, c_w	5829 veh/h	Weaving segment speed, S	mph
Weaving segment v/c ratio	1.098	Average weaving speed, S_W	mph
Weaving segment density, D	pc/mi/ln	Average non-weaving speed, S_{NW}	mph
Level of Service, LOS	F	Maximum weaving length, L_{MAX}	6745 ft

Notes

- a. Weaving segments longer than the calculated maximum length should be treated as isolated merge and diverge areas using the procedures of Chapter 13, "Freeway Merge and Diverge Segments".
- b. For volumes that exceed the weaving segment capacity, the level of service is "F".

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *PM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 1-Bet Hillsboro & Palmetto*
 Jurisdiction
 Analysis Year *2020 Build 2*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>4680</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *4*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1250* pc/h/ln
 S *70.0* mph
 $D = v_p / S$ *17.9* pc/mi/ln
 LOS *B*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume

S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3

f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

FREEWAY WEAVING WORKSHEET									
General Information					Site Information				
Analyst Agency/Company AECOM Date Performed Analysis Time Period PM					Freeway/Dir of Travel 195/SB Weaving Segment Location Seg 2-Bet On from Exp & Off Analysis Year 2020 Build 2				
Project Description SW 10th Street SIMR									
Inputs									
Weaving configuration Two-Sided Weaving number of lanes, N 4 Weaving segment length, L _s 3900ft Freeway free-flow speed, FFS 70 mph					Segment type Freeway Freeway minimum speed, S _{MIN} 15 Freeway maximum capacity, C _{IFL} 2400 Terrain type Level				
Conversions to pc/h Under Base Conditions									
	V (veh/h)	PHF	Truck (%)	RV (%)	E _T	E _R	f _{HV}	f _p	v (pc/h)
V _{FF}	3730	0.95	3	0	1.5	1.2	0.985	1.00	3985
V _{RF}	870	0.92	2	0	1.5	1.2	0.990	1.00	955
V _{FR}	950	0.92	2	0	1.5	1.2	0.990	1.00	1043
V _{RR}	100	0.92	2	0	1.5	1.2	0.990	1.00	110
V _{NW}	5983							V =	6093
V _W	110								
VR	0.018								
Configuration Characteristics									
Minimum maneuver lanes, N _{WL} 0 lc					Minimum weaving lane changes, LC _{MIN} 330 lc/h				
Interchange density, ID 0.7 int/mi					Weaving lane changes, LC _W 902 lc/h				
Minimum RF lane changes, LC _{RF} 0 lc/pc					Non-weaving lane changes, LC _{NW} 2805 lc/h				
Minimum FR lane changes, LC _{FR} 0 lc/pc					Total lane changes, LC _{ALL} 3707 lc/h				
Minimum RR lane changes, LC _{RR} 3 lc/pc					Non-weaving vehicle index, I _{NW} 1633				
Weaving Segment Speed, Density, Level of Service, and Capacity									
Weaving segment flow rate, v 6014 veh/h					Weaving intensity factor, W 0.217				
Weaving segment capacity, c _w 8855 veh/h					Weaving segment speed, S 60.3 mph				
Weaving segment v/c ratio 0.679					Average weaving speed, S _w 60.2 mph				
Weaving segment density, D 25.3 pc/mi/ln					Average non-weaving speed, S _{NW} 60.3 mph				
Level of Service, LOS C					Maximum weaving length, L _{MAX} 5894 ft				
Notes									
a. Weaving segments longer than the calculated maximum length should be treated as isolated merge and diverge areas using the procedures of Chapter 13, "Freeway Merge and Diverge Segments".									
b. For volumes that exceed the weaving segment capacity, the level of service is "F".									

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *PM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 3-Bet Off & On Ramp*
 Jurisdiction
 Analysis Year *2020 Build 2*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>4600</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1638* pc/h/ln
 S *67.8* mph
 $D = v_p / S$ *24.2* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 SB
Agency or Company	AECOM	Junction	Seg 4-Diverge to SW 10th St
Date Performed		Jurisdiction	
Analysis Time Period	PM	Analysis Year	2020 Build 2

Project Description SW 10th Street SIMR

Inputs			
Upstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L _{up} = ft V _u = veh/h	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;"> Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L_A Deceleration Lane Length L_D 200 Freeway Volume, V_F 4600 Ramp Volume, V_R 840 Freeway Free-Flow Speed, S_{FF} 70.0 Ramp Free-Flow Speed, S_{FR} 45.0 </td> <td style="width: 50%; vertical-align: top;"> Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L_{down} = 2400 ft V_D = 1410 veh/h </td> </tr> </table>	Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A Deceleration Lane Length L _D 200 Freeway Volume, V _F 4600 Ramp Volume, V _R 840 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 45.0	Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L _{down} = 2400 ft V _D = 1410 veh/h
Freeway Number of Lanes, N 3 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A Deceleration Lane Length L _D 200 Freeway Volume, V _F 4600 Ramp Volume, V _R 840 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 45.0	Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L _{down} = 2400 ft V _D = 1410 veh/h		

Conversion to pc/h Under Base Conditions								
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p
Freeway	4600	0.95	Level	3	0	0.985	1.00	4915
Ramp	840	0.92	Level	2	0	0.990	1.00	922
UpStream								
DownStream	1410	0.92	Level	2	0	0.990	1.00	1548

Merge Areas	Diverge Areas
Estimation of v₁₂ $V_{12} = V_F (P_{FM})$ L _{EQ} = (Equation 13-6 or 13-7) P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)	Estimation of v₁₂ $V_{12} = V_R + (V_F - V_R)P_{FD}$ L _{EQ} = (Equation 13-12 or 13-13) P _{FD} = 0.595 using Equation (Exhibit 13-7) V ₁₂ = 3297 pc/h V ₃ or V _{av34} 1618 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)

Capacity Checks				Capacity Checks			
	Actual	Capacity	LOS F?		Actual	Capacity	LOS F?
V _{FO}		Exhibit 13-8		V _F	4915	Exhibit 13-8	7200 No
				V _{FO} = V _F - V _R	3993	Exhibit 13-8	7200 No
				V _R	922	Exhibit 13-10	2100 No

Flow Entering Merge Influence Area				Flow Entering Diverge Influence Area			
	Actual	Max Desirable	Violation?		Actual	Max Desirable	Violation?
V _{R12}		Exhibit 13-8		V ₁₂	3297	Exhibit 13-8	4400:All No

Level of Service Determination (if not F)	Level of Service Determination (if not F)
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)	$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 30.8 (pc/mi/ln) LOS = D (Exhibit 13-2)

Speed Determination	Speed Determination
M _S = (Exhibit 13-11)	D _s = 0.381 (Exhibit 13-12)
S _R = mph (Exhibit 13-11)	S _R = 59.3 mph (Exhibit 13-12)
S ₀ = mph (Exhibit 13-11)	S ₀ = 74.4 mph (Exhibit 13-12)
S = mph (Exhibit 13-13)	S = 63.6 mph (Exhibit 13-13)

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *PM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 5-Bet Off & On Ramps*
 Jurisdiction
 Analysis Year *2020 Build 2*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>3760</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1339* pc/h/ln
 S *69.8* mph
 $D = v_p / S$ *19.2* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes S - Speed
 V - Hourly volume D - Density
 v_p - Flow rate FFS - Free-flow speed
 LOS - Level of service BFFS - Base free-flow speed
 DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12 f_{LW} - Exhibit 11-8
 E_T - Exhibits 11-10, 11-11, 11-13 f_{LC} - Exhibit 11-9
 f_p - Page 11-18 TRD - Page 11-11
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 SB
Agency or Company	AECOM	Junction	Seg 6-Merge from Hillsboro E&W
Date Performed		Jurisdiction	
Analysis Time Period	PM	Analysis Year	2020 Build 2
Project Description SW 10th Street SIMR			

Inputs

Upstream Adj Ramp	Freeway Number of Lanes, N	3	Downstream Adj Ramp
<input checked="" type="checkbox"/> Yes <input type="checkbox"/> On	Ramp Number of Lanes, N	1	<input type="checkbox"/> Yes <input type="checkbox"/> On
<input type="checkbox"/> No <input checked="" type="checkbox"/> Off	Acceleration Lane Length, L_A	300	<input checked="" type="checkbox"/> No <input type="checkbox"/> Off
$L_{up} =$ 2400 ft	Deceleration Lane Length L_D		$L_{down} =$ ft
$V_u =$ 840 veh/h	Freeway Volume, V_F	3760	$V_D =$ veh/h
	Ramp Volume, V_R	1410	
	Freeway Free-Flow Speed, S_{FF}	70.0	
	Ramp Free-Flow Speed, S_{FR}	50.0	

Conversion to pc/h Under Base Conditions

(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f_{HV}	f_p	$v = V/PHF \times f_{HV} \times f_p$
Freeway	3760	0.95	Level	3	0	0.985	1.00	4017
Ramp	1410	0.92	Level	2	0	0.990	1.00	1548
UpStream	840	0.92	Level	2	0	0.990	1.00	922
DownStream								

Merge Areas	Diverge Areas
-------------	---------------

Estimation of v_{12}

$V_{12} = V_F (P_{FM})$
$L_{EQ} =$ 1537.11 (Equation 13-6 or 13-7)
$P_{FM} =$ 0.586 using Equation (Exhibit 13-6)
$V_{12} =$ 2354 pc/h
V_3 or $V_{av34} =$ 1663 pc/h (Equation 13-14 or 13-17)
Is V_3 or $V_{av34} > 2,700$ pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Is V_3 or $V_{av34} > 1.5 * V_{12}/2$ <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
If Yes, $V_{12a} =$ 2354 pc/h (Equation 13-16, 13-18, or 13-19)

Estimation of v_{12}

$V_{12} = V_R + (V_F - V_R)P_{FD}$
$L_{EQ} =$ (Equation 13-12 or 13-13)
$P_{FD} =$ using Equation (Exhibit 13-7)
$V_{12} =$ pc/h
V_3 or $V_{av34} =$ pc/h (Equation 13-14 or 13-17)
Is V_3 or $V_{av34} > 2,700$ pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No
Is V_3 or $V_{av34} > 1.5 * V_{12}/2$ <input type="checkbox"/> Yes <input type="checkbox"/> No
If Yes, $V_{12a} =$ pc/h (Equation 13-16, 13-18, or 13-19)

Capacity Checks

	Actual	Capacity	LOS F?
V_{FO}	5565	Exhibit 13-8	No

Capacity Checks

	Actual	Capacity	LOS F?
V_F		Exhibit 13-8	
$V_{FO} = V_F - V_R$		Exhibit 13-8	
V_R		Exhibit 13-10	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
V_{R12}	3902	Exhibit 13-8 4600:All	No

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
V_{12}		Exhibit 13-8	

Level of Service Determination (if not F)

$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$
$D_R =$ 33.3 (pc/mi/ln)
LOS = D (Exhibit 13-2)

Level of Service Determination (if not F)

$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$
$D_R =$ (pc/mi/ln)
LOS = (Exhibit 13-2)

Speed Determination

$M_S =$ 0.484 (Exhibit 13-11)
$S_R =$ 56.4 mph (Exhibit 13-11)
$S_0 =$ 65.8 mph (Exhibit 13-11)
$S =$ 59.0 mph (Exhibit 13-13)

Speed Determination

$D_s =$ (Exhibit 13-12)
$S_R =$ mph (Exhibit 13-12)
$S_0 =$ mph (Exhibit 13-12)
$S =$ mph (Exhibit 13-13)

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *PM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 7-Bet On Ramps*
 Jurisdiction
 Analysis Year *2020 Build 2*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>5170</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width *ft*
 Rt-Side Lat. Clearance *ft*
 Number of Lanes, N *3*
 Total Ramp Density, TRD *ramps/mi*
 FFS (measured) *70.0* *mph*
 Base free-flow Speed, BFFS *mph*

Calc Speed Adj and FFS

f_{LW} *mph*
 f_{LC} *mph*
 TRD Adjustment *mph*
 FFS *70.0* *mph*

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1841* *pc/h/ln*
 S *65.2* *mph*
 $D = v_p / S$ *28.2* *pc/mi/ln*
 LOS *D*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *pc/h/ln*
 S *mph*
 $D = v_p / S$ *pc/mi/ln*
 Required Number of Lanes, N

Glossary


N - Number of lanes S - Speed
 V - Hourly volume D - Density
 v_p - Flow rate FFS - Free-flow speed
 LOS - Level of service BFFS - Base free-flow speed
 DDHV - Directional design hour volume

Factor Location

E_R - Exhibits 11-10, 11-12 f_{LW} - Exhibit 11-8
 E_T - Exhibits 11-10, 11-11, 11-13 f_{LC} - Exhibit 11-9
 f_p - Page 11-18 TRD - Page 11-11
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3

Job: SW 10th Street SIMR
Analyst: AECOM

Location: Seg 8: I-95 Southbound On-Ramp from SW 10th Street EB & WB
Analysis Period: PM Peak Hour
Analysis Year: 2020 Build 2



	PHF =	0.95	
	v_{fr} =	6,220	vph
	v_r =	1,050	vph
	v_f =	5,170	
Upstream Freeway	Tr % =	3%	
Ramp	Tr % =	2%	
Downstream Freeway	Tr % =	3%	
Freeway	f_{HV} =	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	0.985
Ramp	f_{HV} =	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	0.9901
flat terrain	E_T =	1.5	
	RV % =	0	
Driver Population adj.	f_P =	1.000	
	V_{fr} =	$=v_{fr}/(PHF)(f_{HV})(f_P) =$	6,646 pc/h
	V_r =	$=v_r/(PHF)(f_{HV})(f_P) =$	1,116 pc/h
	V_f =	$=v_f/(PHF)(f_{HV})(f_P) =$	5,524 pc/h
No. lanes upstream of ramp	N =	3	

No. Ln	Capacity Check (see Exhibits 25-3 and 25-7):	Maximum	Actual	V/c	LOS F?
4	Fwy downstream of ramp (assume 70 mph free-flow speed) =	9,600	6,646	0.69	No
3	Fwy upstream of ramp (assume 70 mph free-flow speed) =	7,200	5,524	0.77	No
1	Capacity on On-Ramp (assume 45 mph free-flow speed) =	2,100	1,116	0.53	No

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *PM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 9-Bet 10th & Exit to Exp*
 Jurisdiction
 Analysis Year *2020 Build 2*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	6220	veh/h	Peak-Hour Factor, PHF	0.95
AADT		veh/day	%Trucks and Buses, P _T	3
Peak-Hr Prop. of AADT, K			%RVs, P _R	0
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	1.00	E _R	1.2
E _T	1.5	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	0.985

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *4*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1661* pc/h/ln
 S *67.5* mph
 $D = v_p / S$ *24.6* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 SB
Agency or Company	AECOM	Junction	Seg 10-Merge from Ex to GP
Date Performed		Jurisdiction	
Analysis Time Period	PM	Analysis Year	2020 Build 2
Project Description SW 10th Street SIMR			

Inputs

Upstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off $L_{up} =$ ft $V_u =$ veh/h	Freeway Number of Lanes, N 4 Ramp Number of Lanes, N 1 Acceleration Lane Length, L_A 600 Deceleration Lane Length L_D Freeway Volume, V_F 6220 Ramp Volume, V_R 190 Freeway Free-Flow Speed, S_{FF} 70.0 Ramp Free-Flow Speed, S_{FR} 50.0	Downstream Adj Ramp <input checked="" type="checkbox"/> Yes <input type="checkbox"/> On <input type="checkbox"/> No <input checked="" type="checkbox"/> Off $L_{down} =$ 1150 ft $V_D =$ 700 veh/h
--	---	--

Conversion to pc/h Under Base Conditions

(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f_{HV}	f_p	$v = V/PHF \times f_{HV} \times f_p$
Freeway	6220	0.95	Level	3	0	0.985	1.00	6646
Ramp	190	0.92	Level	2	0	0.990	1.00	209
UpStream								
DownStream	700	0.92	Level	2	0	0.990	1.00	768

Merge Areas

Diverge Areas

Estimation of v_{12}

$V_{12} = V_F (P_{FM})$
 (Equation 13-6 or 13-7)
 $L_{EQ} =$
 $P_{FM} =$ 0.192 using Equation (Exhibit 13-6)
 $V_{12} =$ 1274 pc/h
 V_3 or V_{av34} 2686 pc/h (Equation 13-14 or 13-17)
 Is V_3 or $V_{av34} > 2,700$ pc/h? Yes No
 Is V_3 or $V_{av34} > 1.5 * V_{12}/2$ Yes No
 If Yes, $V_{12a} =$ 2658 pc/h (Equation 13-16, 13-18, or 13-19)

Estimation of v_{12}

$V_{12} = V_R + (V_F - V_R)P_{FD}$
 (Equation 13-12 or 13-13)
 $L_{EQ} =$
 $P_{FD} =$ using Equation (Exhibit 13-7)
 $V_{12} =$ pc/h
 V_3 or V_{av34} pc/h (Equation 13-14 or 13-17)
 Is V_3 or $V_{av34} > 2,700$ pc/h? Yes No
 Is V_3 or $V_{av34} > 1.5 * V_{12}/2$ Yes No
 If Yes, $V_{12a} =$ pc/h (Equation 13-16, 13-18, or 13-19)

Capacity Checks

	Actual	Capacity	LOS F?		Actual	Capacity	LOS F?
V_{FO}	6855	Exhibit 13-8	No	V_F		Exhibit 13-8	
				$V_{FO} = V_F - V_R$		Exhibit 13-8	
				V_R		Exhibit 13-10	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
V_{R12}	2867	Exhibit 13-8	4600:All
			No

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
V_{12}		Exhibit 13-8	

Level of Service Determination (if not F)

$D_R = 5.475 + 0.00734 V_R + 0.0078 V_{12} - 0.00627 L_A$
 $D_R =$ 24.0 (pc/mi/ln)
 LOS = C (Exhibit 13-2)

Level of Service Determination (if not F)

$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$
 $D_R =$ (pc/mi/ln)
 LOS = (Exhibit 13-2)

Speed Determination

$M_S =$ 0.330 (Exhibit 13-11)
 $S_R =$ 60.8 mph (Exhibit 13-11)
 $S_0 =$ 64.6 mph (Exhibit 13-11)
 $S =$ 63.0 mph (Exhibit 13-13)

Speed Determination

$D_s =$ (Exhibit 13-12)
 $S_R =$ mph (Exhibit 13-12)
 $S_0 =$ mph (Exhibit 13-12)
 $S =$ mph (Exhibit 13-13)

RAMPS AND RAMP JUNCTIONS WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 SB
Agency or Company	AECOM	Junction	Seg 11- Diverge to Express
Date Performed		Jurisdiction	
Analysis Time Period	PM	Analysis Year	2020 Build 2

Project Description SW 10th Street SIMR

Inputs			
Upstream Adj Ramp <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> On <input type="checkbox"/> No <input type="checkbox"/> Off L _{up} = 1150 ft V _u = 190 veh/h	<table style="width: 100%;"> <tr> <td style="width: 50%;"> Freeway Number of Lanes, N 4 Ramp Number of Lanes, N 1 Acceleration Lane Length, L_A Deceleration Lane Length L_D 200 Freeway Volume, V_F 6410 Ramp Volume, V_R 700 Freeway Free-Flow Speed, S_{FF} 70.0 Ramp Free-Flow Speed, S_{FR} 45.0 </td> <td style="width: 50%;"> Downstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L_{down} = ft V_D = veh/h </td> </tr> </table>	Freeway Number of Lanes, N 4 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A Deceleration Lane Length L _D 200 Freeway Volume, V _F 6410 Ramp Volume, V _R 700 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 45.0	Downstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L _{down} = ft V _D = veh/h
Freeway Number of Lanes, N 4 Ramp Number of Lanes, N 1 Acceleration Lane Length, L _A Deceleration Lane Length L _D 200 Freeway Volume, V _F 6410 Ramp Volume, V _R 700 Freeway Free-Flow Speed, S _{FF} 70.0 Ramp Free-Flow Speed, S _{FR} 45.0	Downstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L _{down} = ft V _D = veh/h		

Conversion to pc/h Under Base Conditions								
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p
Freeway	6410	0.95	Level	3	0	0.985	1.00	6849
Ramp	700	0.92	Level	2	0	0.990	1.00	768
UpStream	190	0.92	Level	2	0	0.990	1.00	209
DownStream								

Merge Areas				Diverge Areas			
Estimation of v ₁₂				Estimation of v ₁₂			
$V_{12} = V_F (P_{FM})$ L _{EQ} = (Equation 13-6 or 13-7) P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)	$V_{12} = V_R + (V_F - V_R)P_{FD}$ L _{EQ} = (Equation 13-12 or 13-13) P _{FD} = 0.436 using Equation (Exhibit 13-7) V ₁₂ = 3419 pc/h V ₃ or V _{av34} 1715 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)						

Capacity Checks				Capacity Checks			
	Actual	Capacity	LOS F?		Actual	Capacity	LOS F?
V _{FO}		Exhibit 13-8		V _F	6849	Exhibit 13-8	9600 No
				V _{FO} = V _F - V _R	6081	Exhibit 13-8	9600 No
				V _R	768	Exhibit 13-10	2100 No


Flow Entering Merge Influence Area				Flow Entering Diverge Influence Area			
	Actual	Max Desirable	Violation?		Actual	Max Desirable	Violation?
V _{R12}		Exhibit 13-8		V ₁₂	3419	Exhibit 13-8	4400:All No

Level of Service Determination (if not F)		Level of Service Determination (if not F)	
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)	$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 34.8 (pc/mi/ln) LOS = D (Exhibit 13-2)		

Speed Determination		Speed Determination	
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)	D _s = 0.367 (Exhibit 13-12) S _R = 59.7 mph (Exhibit 13-12) S ₀ = 74.7 mph (Exhibit 13-12) S = 65.6 mph (Exhibit 13-13)		

Job: SW 10th Street SIMR
Analyst: AECOM

Location: Seg 12: I-95 SB Off-Ramp to Sample Road EB & WB
Analysis Period: AM Peak Hour
Analysis Year: 2020 Build 2



PHF =	0.95	
v_{fr} =	5,710	vph
v_r =	1,070	vph
v_f =	4,640	
Upstream Freeway Tr % =	3%	
Ramp Tr % =	2%	
Downstream Freeway Tr % =	3%	
Freeway f_{HV} =	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	0.985
Ramp f_{HV} =	$1/(1+P_T(E_T-1)+P_R(E_R-1)) =$	0.9901
flat terrain E_T =	1.5	
RV % =	0	
Driver Population adj. f_P =	1.000	
V_{fr} =	$=v_{fr}/(PHF)(f_{HV})(f_P) =$	6,101 pc/h
V_r =	$=v_r/(PHF)(f_{HV})(f_P) =$	1,138 pc/h
V_f =	$=v_f/(PHF)(f_{HV})(f_P) =$	4,957 pc/h
No. lanes upstream of ramp N =	4	

Average Freeway Density Upstream of Diverge (see Equation 13-26):

$D = 0.0175 (V_{fr}/N) = 26.7 \text{ pc/ln}$

LOS in the Diverge Area (from Density and Exhibit 13-2) =

C

No. Ln	Capacity Check (see Exhibits 13-2, 13-8 and 13.10)	Maximum	Actual	LOS F?
4	Fwy upstream of ramp (assume 70 mph free-flow speed) =	9,600	6,101	No
3	Fwy downstream of ramp (assume 70 mph free-flow speed) =	7,200	4,957	No
1	Capacity on Off-Ramp (assume 45 mph free-flow speed) =	2,100	1,138	No

BASIC FREEWAY SEGMENTS WORKSHEET

General Information

Analyst
 Agency or Company *AECOM*
 Date Performed
 Analysis Time Period *PM*

Site Information

Highway/Direction of Travel *I-95 SB*
 From/To *Seg 13-Bet Off & On Ramps*
 Jurisdiction
 Analysis Year *2020 Build 2*

Project Description *SW 10th Street SIMR*

Oper.(LOS)

Des.(N)

Planning Data

Flow Inputs

Volume, V	<i>4640</i>	veh/h	Peak-Hour Factor, PHF	<i>0.95</i>
AADT		veh/day	%Trucks and Buses, P _T	<i>3</i>
Peak-Hr Prop. of AADT, K			%RVs, P _R	<i>0</i>
Peak-Hr Direction Prop, D			General Terrain:	<i>Level</i>
DDHV = AADT x K x D		veh/h	Grade % Length	<i>mi</i>
			Up/Down %	

Calculate Flow Adjustments

f _p	<i>1.00</i>	E _R	<i>1.2</i>
E _T	<i>1.5</i>	f _{HV} = 1/[1+P _T (E _T - 1) + P _R (E _R - 1)]	<i>0.985</i>

Speed Inputs

Lane Width ft
 Rt-Side Lat. Clearance ft
 Number of Lanes, N *3*
 Total Ramp Density, TRD ramps/mi
 FFS (measured) *70.0* mph
 Base free-flow Speed, BFFS mph

Calc Speed Adj and FFS

f_{LW} mph
 f_{LC} mph
 TRD Adjustment mph
 FFS *70.0* mph

LOS and Performance Measures

Operational (LOS)
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ *1652* pc/h/ln
 S *67.6* mph
 $D = v_p / S$ *24.4* pc/mi/ln
 LOS *C*

Design (N)

Design (N)
 Design LOS
 $v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$ pc/h/ln
 S mph
 $D = v_p / S$ pc/mi/ln
 Required Number of Lanes, N

Glossary

N - Number of lanes
 V - Hourly volume
 v_p - Flow rate
 LOS - Level of service
 DDHV - Directional design hour volume
 S - Speed
 D - Density
 FFS - Free-flow speed
 BFFS - Base free-flow speed

Factor Location

E_R - Exhibits 11-10, 11-12
 E_T - Exhibits 11-10, 11-11, 11-13
 f_p - Page 11-18
 LOS, S, FFS, v_p - Exhibits 11-2, 11-3
 f_{LW} - Exhibit 11-8
 f_{LC} - Exhibit 11-9
 TRD - Page 11-11

FREEWAY WEAVING WORKSHEET

General Information		Site Information	
Analyst		Freeway/Dir of Travel	I-95 SB
Agency/Company	AECOM	Weaving Segment Location	Seg 14- Bet Sample & Copans
Date Performed		Analysis Year	2020 Build 2
Analysis Time Period	PM		

Project Description SW 10th Street SIMR

Inputs

Weaving configuration	One-Sided	Segment type	Freeway
Weaving number of lanes, N	4	Freeway minimum speed, S_{MIN}	15
Weaving segment length, L_S	2520ft	Freeway maximum capacity, C_{IFL}	2400
Freeway free-flow speed, FFS	70 mph	Terrain type	Level

Conversions to pc/h Under Base Conditions

	V (veh/h)	PHF	Truck (%)	RV (%)	E_T	E_R	f_{HV}	f_p	v (pc/h)
V_{FF}	3995	0.95	3	0	1.5	1.2	0.985	1.00	4268
V_{RF}	1410	0.92	2	0	1.5	1.2	0.990	1.00	1548
V_{FR}	645	0.92	2	0	1.5	1.2	0.990	1.00	708
V_{RR}	0	0.95	0	0	1.5	1.2	1.000	1.00	0
V_{NW}	4268							V =	6524
V_W	2256								
VR	0.346								

Configuration Characteristics

Minimum maneuver lanes, N_{WL}	2 lc	Minimum weaving lane changes, LC_{MIN}	2256 lc/h
Interchange density, ID	0.7 int/mi	Weaving lane changes, LC_W	2705 lc/h
Minimum RF lane changes, LC_{RF}	1 lc/pc	Non-weaving lane changes, LC_{NW}	1475 lc/h
Minimum FR lane changes, LC_{FR}	1 lc/pc	Total lane changes, LC_{ALL}	4180 lc/h
Minimum RR lane changes, LC_{RR}	lc/pc	Non-weaving vehicle index, I_{NW}	753

Weaving Segment Speed, Density, Level of Service, and Capacity

Weaving segment flow rate, v	6439 veh/h	Weaving intensity factor, W	0.337
Weaving segment capacity, c_w	6838 veh/h	Weaving segment speed, S	49.0 mph
Weaving segment v/c ratio	0.942	Average weaving speed, S_W	56.1 mph
Weaving segment density, D	33.3 pc/mi/ln	Average non-weaving speed, S_{NW}	45.9 mph
Level of Service, LOS	D	Maximum weaving length, L_{MAX}	6080 ft

Notes

- a. Weaving segments longer than the calculated maximum length should be treated as isolated merge and diverge areas using the procedures of Chapter 13, "Freeway Merge and Diverge Segments".
- b. For volumes that exceed the weaving segment capacity, the level of service is "F".

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Freeway/Dir of Travel			I-95 NB Express Lane				
Agency or Company		AECOM			Junction				
Date Performed					Off to SW 10th Connector				
Analysis Time Period		AM			Jurisdiction				
					Analysis Year				
					2020 Build 2				
Project Description SW 10th Street SIMR									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2			Downstream Adj Ramp	
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1			<input type="checkbox"/> Yes <input type="checkbox"/> On	
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A						<input checked="" type="checkbox"/> No <input type="checkbox"/> Off	
L _{up} = ft		Deceleration Lane Length L _D			345			L _{down} = ft	
V _u = veh/h		Freeway Volume, V _F			1110			V _D = veh/h	
		Ramp Volume, V _R			60				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			60.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1110	0.95	Level	3	0	0.985	1.00	1186	
Ramp	60	0.95	Level	2	0	0.990	1.00	64	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13)				
L _{EQ} =					L _{EQ} =				
P _{FM} = using Equation (Exhibit 13-6)					P _{FD} = 1.000 using Equation (Exhibit 13-7)				
V ₁₂ = pc/h					V ₁₂ = 1186 pc/h				
V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17)					V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17)				
Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No					Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				
Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No					Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				
If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	1186	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	1122	Exhibit 13-8	4800	No
					V _R	64	Exhibit 13-10	2200	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	1186	Exhibit 13-8	4400:All	No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
D _R = 5.475 + 0.00734 v _R + 0.0078 V ₁₂ - 0.00627 L _A					D _R = 4.252 + 0.0086 V ₁₂ - 0.009 L _D				
D _R = (pc/mi/ln)					D _R = 11.3 (pc/mi/ln)				
LOS = (Exhibit 13-2)					LOS = B (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11)					D _S = 0.109 (Exhibit 13-12)				
S _R = mph (Exhibit 13-11)					S _R = 67.0 mph (Exhibit 13-12)				
S ₀ = mph (Exhibit 13-11)					S ₀ = N/A mph (Exhibit 13-12)				
S = mph (Exhibit 13-13)					S = 67.0 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET										
General Information					Site Information					
Analyst		Freeway/Dir of Travel			I-95 NB Express Lanes					
Agency or Company		AECOM			Junction					On from SW 10th St. Connector
Date Performed		Jurisdiction								
Analysis Time Period		AM			Analysis Year					2020 Build 2
Project Description SW 10th Street SIMR										
Inputs										
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp			
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On			
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			1040		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off			
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft			
V _u = veh/h		Freeway Volume, V _F			1050		V _D = veh/h			
		Ramp Volume, V _R			760					
		Freeway Free-Flow Speed, S _{FF}			70.0					
		Ramp Free-Flow Speed, S _{FR}			60.0					
Conversion to pc/h Under Base Conditions										
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p		
Freeway	1050	0.95	Level	3	0	0.985	1.00	1122		
Ramp	760	0.95	Level	2	0	0.990	1.00	808		
UpStream										
DownStream										
Merge Areas					Diverge Areas					
Estimation of v ₁₂					Estimation of v ₁₂					
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13)					
L _{EO} = 1.000 using Equation (Exhibit 13-6)					L _{EO} = using Equation (Exhibit 13-7)					
P _{FM} = 1122 pc/h					P _{FD} = pc/h					
V ₁₂ = 1122 pc/h					V ₁₂ = pc/h					
V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17)					V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17)					
Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No					Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No					
Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No					Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No					
If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					
Capacity Checks					Capacity Checks					
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?	
V _{FO}	1930	Exhibit 13-8		No	V _F		Exhibit 13-8			
					V _{FO} = V _F - V _R		Exhibit 13-8			
					V _R		Exhibit 13-10			
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area					
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?	
V _{R12}	2064	Exhibit 13-8		4600:All	No	V ₁₂	Exhibit 13-8			
Level of Service Determination (if not F)					Level of Service Determination (if not F)					
$D_R = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A$ D _R = 13.6 (pc/mi/ln)					$D_R = 4.252 + 0.0086 v_{12} - 0.009 L_D$ D _R = (pc/mi/ln)					
LOS = B (Exhibit 13-2)					LOS = (Exhibit 13-2)					
Speed Determination					Speed Determination					
M _S = 0.227 (Exhibit 13-11)					D _S = (Exhibit 13-12)					
S _R = 63.6 mph (Exhibit 13-11)					S _R = mph (Exhibit 13-12)					
S ₀ = N/A mph (Exhibit 13-11)					S ₀ = mph (Exhibit 13-12)					
S = 63.6 mph (Exhibit 13-13)					S = mph (Exhibit 13-13)					

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Freeway/Dir of Travel			I-95 SB Express Lane				
Agency or Company		AECOM			Junction				
Date Performed					Off to SW 10th Connector				
Analysis Time Period		AM			Jurisdiction				
					Analysis Year				
					2020 Build 2				
Project Description SW 10th Street SIMR									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2			Downstream Adj Ramp	
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1			<input type="checkbox"/> Yes <input type="checkbox"/> On	
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A						<input checked="" type="checkbox"/> No <input type="checkbox"/> Off	
L _{up} = ft		Deceleration Lane Length L _D			250			L _{down} = ft	
V _u = veh/h		Freeway Volume, V _F			1010			V _D = veh/h	
		Ramp Volume, V _R			370				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			60.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1010	0.95	Level	3	0	0.985	1.00	1079	
Ramp	370	0.95	Level	2	0	0.990	1.00	393	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13)				
L _{EQ} =					L _{EQ} =				
P _{FM} = using Equation (Exhibit 13-6)					P _{FD} = 1.000 using Equation (Exhibit 13-7)				
V ₁₂ = pc/h					V ₁₂ = 1079 pc/h				
V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17)					V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17)				
Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No					Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				
Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No					Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				
If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	1079	Exhibit 13-8	4800	No
			V _{FO} = V _F - V _R	686	Exhibit 13-8	4800	No		
			V _R	393	Exhibit 13-10	2200	No		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	1079	Exhibit 13-8	4400:All	No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
D _R = 5.475 + 0.00734 v _R + 0.0078 V ₁₂ - 0.00627 L _A					D _R = 4.252 + 0.0086 V ₁₂ - 0.009 L _D				
D _R = (pc/mi/ln)					D _R = 11.3 (pc/mi/ln)				
LOS = (Exhibit 13-2)					LOS = B (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11)					D _S = 0.138 (Exhibit 13-12)				
S _R = mph (Exhibit 13-11)					S _R = 66.1 mph (Exhibit 13-12)				
S ₀ = mph (Exhibit 13-11)					S ₀ = N/A mph (Exhibit 13-12)				
S = mph (Exhibit 13-13)					S = 66.1 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Freeway/Dir of Travel			I-95 SB Express Lanes				
Agency or Company		AECOM			Junction				
Date Performed					On from SW 10th St. Connector				
Analysis Time Period		AM			Jurisdiction				
Project Description		SW 10th Street SIMR			Analysis Year				
					2020 Build 2				
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2			Downstream Adj Ramp	
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1			<input type="checkbox"/> Yes <input type="checkbox"/> On	
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			1100			<input checked="" type="checkbox"/> No <input type="checkbox"/> Off	
L _{up} = ft		Deceleration Lane Length L _D						L _{down} = ft	
V _u = veh/h		Freeway Volume, V _F			640			V _D = veh/h	
		Ramp Volume, V _R			160				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			60.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	640	0.95	Level	3	0	0.985	1.00	684	
Ramp	160	0.95	Level	2	0	0.990	1.00	170	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13)				
L _{EO} = 1.000 using Equation (Exhibit 13-6)					L _{EO} = using Equation (Exhibit 13-7)				
P _{FM} = 684 pc/h					P _{FD} = pc/h				
V ₁₂ = 684 pc/h					V ₁₂ = pc/h				
V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17)					V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17)				
Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No					Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No				
Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No					Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No				
If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	854	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	936	Exhibit 13-8		No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 5.2 (pc/mi/ln)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln)				
LOS = A (Exhibit 13-2)					LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.199 (Exhibit 13-11)					D _S = (Exhibit 13-12)				
S _R = 64.4 mph (Exhibit 13-11)					S _R = mph (Exhibit 13-12)				
S ₀ = N/A mph (Exhibit 13-11)					S ₀ = mph (Exhibit 13-12)				
S = 64.4 mph (Exhibit 13-13)					S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Freeway/Dir of Travel			I-95 NB Express Lane				
Agency or Company		AECOM			Junction				
Date Performed		Jurisdiction			Off to SW 10th Connector				
Analysis Time Period		PM			Analysis Year				
					2020 Build 2				
Project Description SW 10th Street SIMR									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			345		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			890		V _D = veh/h		
		Ramp Volume, V _R			150				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			60.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	890	0.95	Level	3	0	0.985	1.00	951	
Ramp	150	0.95	Level	2	0	0.990	1.00	159	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 951 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	951	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	792	Exhibit 13-8	4800	No
					V _R	159	Exhibit 13-10	2200	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	951	Exhibit 13-8	4400:All	No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 9.3 (pc/mi/ln) LOS = A (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.117 (Exhibit 13-12) S _R = 66.7 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 66.7 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Freeway/Dir of Travel			I-95 NB Express Lanes				
Agency or Company		AECOM			Junction				
Date Performed					On from SW 10th St. Connector				
Analysis Time Period		PM			Jurisdiction				
Project Description		SW 10th Street SIMR			Analysis Year				
					2020 Build 2				
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2			Downstream Adj Ramp	
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1			<input type="checkbox"/> Yes <input type="checkbox"/> On	
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			1040			<input checked="" type="checkbox"/> No <input type="checkbox"/> Off	
L _{up} = ft		Deceleration Lane Length L _D						L _{down} = ft	
V _u = veh/h		Freeway Volume, V _F			740			V _D = veh/h	
		Ramp Volume, V _R			390				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			60.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	740	0.95	Level	3	0	0.985	1.00	791	
Ramp	390	0.95	Level	2	0	0.990	1.00	415	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 791 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	1206	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	1300	Exhibit 13-8		No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 8.2 (pc/mi/ln) LOS = A (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.211 (Exhibit 13-11) S _R = 64.1 mph (Exhibit 13-11) S ₀ = N/A mph (Exhibit 13-11) S = 64.1 mph (Exhibit 13-13)					D _S = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Freeway/Dir of Travel			I-95 SB Express Lane				
Agency or Company		AECOM			Junction				
Date Performed		Jurisdiction			Off to SW 10th Connector				
Analysis Time Period		PM			Analysis Year				
					2020 Build 2				
Project Description SW 10th Street SIMR									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			250		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1730		V _D = veh/h		
		Ramp Volume, V _R			560				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			60.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1730	0.95	Level	3	0	0.985	1.00	1848	
Ramp	560	0.95	Level	2	0	0.990	1.00	595	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13)				
L _{EQ} =					L _{EQ} =				
P _{FM} = using Equation (Exhibit 13-6)					P _{FD} = 1.000 using Equation (Exhibit 13-7)				
V ₁₂ = pc/h					V ₁₂ = 1848 pc/h				
V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17)					V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17)				
Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No					Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				
Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No					Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				
If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	1848	Exhibit 13-8	4800	No
			V _{FO} = V _F - V _R	1253	Exhibit 13-8	4800	No		
			V _R	595	Exhibit 13-10	2200	No		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	1848	Exhibit 13-8	4400:All	No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
D _R = 5.475 + 0.00734 v _R + 0.0078 V ₁₂ - 0.00627 L _A					D _R = 4.252 + 0.0086 V ₁₂ - 0.009 L _D				
D _R = (pc/mi/ln)					D _R = 17.9 (pc/mi/ln)				
LOS = (Exhibit 13-2)					LOS = B (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11)					D _S = 0.157 (Exhibit 13-12)				
S _R = mph (Exhibit 13-11)					S _R = 65.6 mph (Exhibit 13-12)				
S ₀ = mph (Exhibit 13-11)					S ₀ = N/A mph (Exhibit 13-12)				
S = mph (Exhibit 13-13)					S = 65.6 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Freeway/Dir of Travel			I-95 SB Express Lanes				
Agency or Company		AECOM			Junction				
Date Performed					On from SW 10th St. Connector				
Analysis Time Period		PM			Jurisdiction				
Project Description		SW 10th Street SIMR			Analysis Year				
					2020 Build 2				
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2			Downstream Adj Ramp	
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1			<input type="checkbox"/> Yes <input type="checkbox"/> On	
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			1100			<input checked="" type="checkbox"/> No <input type="checkbox"/> Off	
L _{up} = ft		Deceleration Lane Length L _D						L _{down} = ft	
V _u = veh/h		Freeway Volume, V _F			1170			V _D = veh/h	
		Ramp Volume, V _R			80				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			60.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1170	0.95	Level	3	0	0.985	1.00	1250	
Ramp	80	0.95	Level	2	0	0.990	1.00	85	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ L _{EO} = (Equation 13-6 or 13-7) P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1250 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ L _{EO} = (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	1335	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	1485	Exhibit 13-8		No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 9.0 (pc/mi/ln) LOS = A (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.206 (Exhibit 13-11) S _R = 64.2 mph (Exhibit 13-11) S ₀ = N/A mph (Exhibit 13-11) S = 64.2 mph (Exhibit 13-13)					D _S = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET										
General Information					Site Information					
Analyst		Freeway/Dir of Travel			I-95 NB CD					
Agency or Company		AECOM			Junction					N. of Hillsboro Blvd
Date Performed		Jurisdiction								
Analysis Time Period		AM			Analysis Year					2020 Build 2
Project Description SW 10th Street SIMR										
Inputs										
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp			
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On			
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			890		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off			
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft			
V _u = veh/h		Freeway Volume, V _F			1230		V _D = veh/h			
		Ramp Volume, V _R			710					
		Freeway Free-Flow Speed, S _{FF}			55.0					
		Ramp Free-Flow Speed, S _{FR}			40.0					
Conversion to pc/h Under Base Conditions										
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p		
Freeway	1230	0.95	Level	3	0	0.985	1.00	1314		
Ramp	710	0.95	Level	2	0	0.990	1.00	755		
UpStream										
DownStream										
Merge Areas					Diverge Areas					
Estimation of v ₁₂					Estimation of v ₁₂					
$V_{12} = V_F (P_{FM})$ L _{EO} = (Equation 13-6 or 13-7) P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1314 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ L _{EO} = (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					
Capacity Checks					Capacity Checks					
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?	
V _{FO}	2069	Exhibit 13-8		No	V _F		Exhibit 13-8			
					V _{FO} = V _F - V _R		Exhibit 13-8			
					V _R		Exhibit 13-10			
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area					
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?	
V _{R12}	2069	Exhibit 13-8		No	V ₁₂		Exhibit 13-8			
Level of Service Determination (if not F)					Level of Service Determination (if not F)					
$D_R = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A$ D _R = 15.7 (pc/mi/ln) LOS = B (Exhibit 13-2)					$D_R = 4.252 + 0.0086 v_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					
Speed Determination					Speed Determination					
M _S = 0.281 (Exhibit 13-11) S _R = 51.4 mph (Exhibit 13-11) S ₀ = N/A mph (Exhibit 13-11) S = 51.4 mph (Exhibit 13-13)					D _S = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)					

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Freeway/Dir of Travel			I-95 NB CD				
Agency or Company		AECOM			Junction				
Date Performed					N. of Hillsboro Blvd.				
Analysis Time Period		PM			Jurisdiction				
Project Description		SW 10th Street SIMR			Analysis Year				
					2020 Build 2				
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			890		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1520		V _D = veh/h		
		Ramp Volume, V _R			640				
		Freeway Free-Flow Speed, S _{FF}			55.0				
		Ramp Free-Flow Speed, S _{FR}			40.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1520	0.95	Level	3	0	0.985	1.00	1624	
Ramp	640	0.95	Level	2	0	0.990	1.00	680	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13)				
L _{EO} = 1.000 using Equation (Exhibit 13-6)					L _{EO} = using Equation (Exhibit 13-7)				
P _{FM} = 1624 pc/h					P _{FD} = pc/h				
V ₁₂ = 1624 pc/h					V ₁₂ = pc/h				
V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17)					V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17)				
Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No					Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No				
Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No					Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No				
If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2304	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2304	Exhibit 13-8		No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 17.6 (pc/mi/ln)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln)				
LOS = B (Exhibit 13-2)					LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.289 (Exhibit 13-11)					D _S = (Exhibit 13-12)				
S _R = 51.2 mph (Exhibit 13-11)					S _R = mph (Exhibit 13-12)				
S ₀ = N/A mph (Exhibit 13-11)					S ₀ = mph (Exhibit 13-12)				
S = 51.2 mph (Exhibit 13-13)					S = mph (Exhibit 13-13)				